

Package ‘D3partitionR’

October 12, 2022

Title Interactive Charts of Nested and Hierarchical Data with 'D3.js'

Version 0.5.0

Description Builds interactive 'd3.js' hierarchical visualisation easily. D3partitionR makes it easy to build and customize sunburst, circle treemap, treemap, partition chart, ...

Depends R (>= 3.3.1)

Imports data.table, magrittr, htmlwidgets, functional, RColorBrewer, titanic

License AGPL-3

Encoding UTF-8

LazyData true

RoxygenNote 6.0.1

NeedsCompilation no

Author Antoine Guillot [aut, cre],
Mike Bostock [aut, cph] (d3.js library, <http://d3js.org>, nested treemap, icycle, zoomable circle treemap and sunb),
Susie Lu [aut, cph] (d3-legend, <http://d3-legend.susielu.com/>),
Kerry Rodden [aut, cph] (Breadcrumb Code for fixed sized breadcrumb.),
Nadieh Bremer [aut, cph] (Placement of labels on arcs, <https://www.visualcinnamon.com/2015/09/placing-text-on-arcs.html>),
Hub Spot [aut, cph] (tether.js)

Maintainer Antoine Guillot <antoine.guil@outlook.fr>

Repository CRAN

Date/Publication 2017-10-07 14:36:03 UTC

R topics documented:

| | |
|--------------------------------------|---|
| add_data | 2 |
| add_nodes_data | 3 |
| add_title | 3 |
| aggregate_sessions_to_path | 4 |

| | |
|--------------------------------------|----|
| compile_D3_partitionR | 4 |
| compute_unique_leaf_name | 5 |
| D3partitionR | 5 |
| D3partitionR-shiny | 6 |
| df_to_nest | 6 |
| find_min_max_tree | 7 |
| get_all_nodes_names | 7 |
| is_present_variable | 8 |
| plot.D3partitionR | 8 |
| scale_type | 9 |
| set_chart_type | 10 |
| set_continuous_color_scale | 10 |
| set_discrete_color_scale | 11 |
| set_labels_parameters | 11 |
| set_legend_parameters | 12 |
| set_shiny_input | 12 |
| set_tooltip_parameters | 13 |
| set_trail | 13 |
| strip_path | 14 |
| tooltip_builder | 14 |

Index 15

| | |
|----------|---|
| add_data | <i>Append data to a D3partitionR object</i> |
|----------|---|

Description

Append data to a D3partitionR object

Usage

```
add_data(D3partitionR_object, data, steps, count = "value", color = "name",
         label = "name", tooltip = "name", aggregate_fun = NULL)
```

Arguments

| | |
|---------------------|---|
| D3partitionR_object | The D3partitionR object to which the data should be appended |
| data | a data.frame object |
| steps | The vector of steps to be used |
| count | The variable to be used as the count variable, typically, the number of occurrences. |
| color | a variable to use as color (default: name) |
| label | a variable to use as label (default: name) |
| tooltip | a variable to use as tooltip (default: name) |
| aggregate_fun | A named list of function which will be used to aggregates to variables used in color, label or tooltips. This only applies to variable in the provided dataset. |

Value

The D3partitionR object with the appended data

| | |
|----------------|---|
| add_nodes_data | <i>Add informations (for instance new names, colors,) to the nodes of a D3_partitionR object</i> |
|----------------|---|

Description

Add informations (for instance new names, colors,) to the nodes of a D3_partitionR object

Usage

```
add_nodes_data(D3partitionR_object, nodes_data)
```

Arguments

| | |
|---------------------|---|
| D3partitionR_object | The D3partitionR object to which the data should be appended |
| nodes_data | a names list where the name of each element is the name of a node. The data will be appended to the node in the nested list |

Value

The D3partitionR object with the appended nodes data

| | |
|-----------|---|
| add_title | <i>Add a title to a D3partitionR object</i> |
|-----------|---|

Description

Add a title to a D3partitionR object

Usage

```
add_title(D3partitionR_object, text, style = NULL)
```

Arguments

| | |
|---------------------|--|
| D3partitionR_object | The D3partitionR object to which the data should be appended |
| text | Title text |
| style | A valid CSS string which will be applied to the title) |

Value

A D3partitionR object

aggregate_sessions_to_path

Aggregate a data.frame in long format with a column containing steps of each session For instance the function can be used with a frame of the form Unique ID - Step - Value 1 - ... -Value N

Description

Aggregate a data.frame in long format with a column containing steps of each session For instance the function can be used with a frame of the form Unique ID - Step - Value 1 - ... -Value N

Usage

```
aggregate_sessions_to_path(data, step_col = "step", id_col = "ID",
  values_cols = NULL, agg_function_path = sum, agg_function_session = sum,
  sep = "->")
```

Arguments

| | |
|----------------------|---|
| data | A dataframe |
| step_col | The name of the column containig the steps. The steps are assumed to be ordered |
| id_col | Column containing the unique identifier of each session |
| values_cols | Names of the other columns to keep. Default: NULL |
| agg_function_path | Aggregation function on a path level |
| agg_function_session | Aggregation function on a session level |
| sep | String used to separate the different steps. Default: "->" |

Value

A data.table with the columns specified in count_col, value_cols and one column per step in the path

compile_D3_partitionR *Compile D3partitionR object to plot it*

Description

Compile D3partitionR object to plot it

Usage

```
compile_D3_partitionR(D3partitionR_object)
```

Arguments

`D3partitionR_object`
The `D3partitionR` object to which the data should be appended

Value

A `D3partitionR` compiled object

`compute_unique_leaf_name`
Return al the leaf names

Description

Return al the leaf names

Usage

`compute_unique_leaf_name(nested_list)`

Arguments

`nested_list` A `nested_list` where each node has a name attribute

`D3partitionR` *Creates a `D3partitionR` object*

Description

Creates a `D3partitionR` object

Usage

`D3partitionR()`

Value

A blank `D3partitionR` object (S3 class)

D3partitionR-shiny *Shiny bindings for D3partitionR*

Description

Output and render functions for using D3partitionR within Shiny applications and interactive Rmd documents.

Usage

```
D3partitionROutput(outputId, width = "100%", height = "400px")
```

```
renderD3partitionR(expr, env = parent.frame(), quoted = FALSE)
```

Arguments

| | |
|---------------|--|
| outputId | output variable to read from |
| width, height | Must be a valid CSS unit (like '100%', '400px', 'auto') or a number, which will be coerced to a string and have 'px' appended. |
| expr | An expression that generates a D3partitionR |
| env | The environment in which to evaluate expr. |
| quoted | Is expr a quoted expression (with quote())? This is useful if you want to save an expression in a variable. |

df_to_nest *Transform a dataframe to a nested lists structure (i.e. hierarchical).*

Description

Transform a dataframe to a nested lists structure (i.e. hierarchical).

Usage

```
df_to_nest(data, step_cols, nodes_data = NULL, count_col = "value",
  value_cols = NULL, agg_function = sum, na_behavior = "rm")
```

Arguments

| | |
|------------|--|
| data | The data frame to convert to the nested structure. It needs to have several columns, each ones account for a given step |
| step_cols | vector containing the names of the columns which should be used as steps. The vector should be ordered. ex: c('step1','step2','step3') |
| nodes_data | A named list to add addition informations to each nodes |

| | |
|--------------|---|
| count_col | Number of occurrences in this path (succession of steps). Default: NULL |
| value_cols | Names of the other columns to keep. Default: NULL |
| agg_function | aggregation function to be applied to value_cols.Ex: mean, sum. Default: sum. Weighted version can also be used, the weighting will be done using the counting variable |
| na_behavior | How to deal with missing data ? |

Value

A data.table with the columns specified in count_col, value_cols and one column per step in the path

| | |
|-------------------|---|
| find_min_max_tree | <i>Find the maximum values of a given var in a tree</i> |
|-------------------|---|

Description

Find the maximum values of a given var in a tree

Usage

```
find_min_max_tree(nested_list, variable = "value")
```

Arguments

| | |
|-------------|--|
| nested_list | A nested_list where each node has a name attribute |
| variable | A nested_list where each node has a name attribute |

| | |
|---------------------|---|
| get_all_nodes_names | <i>Return al the possible nodes names</i> |
|---------------------|---|

Description

Return al the possible nodes names

Usage

```
get_all_nodes_names(nested_list, variable = "name")
```

Arguments

| | |
|-------------|--|
| nested_list | A nested_list where each node has a name attribute |
| variable | the variable to collect |

`is_present_variable` *Check if a variable is present in a D3partitionR object*

Description

Check if a variable is present in a D3partitionR object

Usage

```
is_present_variable(variable, D3partitionR_object)
```

Arguments

`variable` The variable which presence is to be checked
`D3partitionR_object`
 The D3partitionR object

Value

TRUE/FALSE

`plot.D3partitionR` *Plot D3partitionR object*

Description

Plot D3partitionR object

Usage

```
## S3 method for class 'D3partitionR'
plot(x, width = NULL, height = NULL,
      elementId = NULL, sizingPolicy = NULL, ...)
```

Arguments

`x` A D3partitionR object to plot
`width` width of the widget in pixel/percent
`height` height of the widget in pixel/percent
`elementId` html id of the widget
`sizingPolicy` sizing policy
`...` parameters for method consistency

Examples

```

require(titanic)
require(data.table)
## Reading data
titanic_data = data.table(titanic::titanic_train)

##Agregating data to have unique sequence for the 4 variables
var_names=c('Sex','Embarked','Pclass','Survived')
data_plot=titanic_data[,.N,by=var_names]
data_plot[, (var_names):=lapply(var_names,function(x){data_plot[[x]]=paste0(x,' ',data_plot[[x]])
}]]

## Plotting the chart
library("magrittr")
d3=D3partitionR() %>%
  add_data(data_plot,count = 'N',steps=c('Sex','Embarked','Pclass','Survived')) %>%
  add_title('Titanic')
## Not run:
plot(d3)

## End(Not run)

```

scale_type

Check if the scale variable is discrete or continuous

Description

Check if the scale variable is discrete or continuous

Usage

```
scale_type(color_variable, D3partitionR_object)
```

Arguments

color_variable The color variable to be assessed
D3partitionR_object
The D3partitionR object

Value

TRUE/FALSE

| | |
|----------------|---------------------------|
| set_chart_type | <i>Set the chart_type</i> |
|----------------|---------------------------|

Description

Set the chart_type

Usage

```
set_chart_type(D3partitionR_object, chart_type)
```

Arguments

D3partitionR_object

The D3partitionR object to which the data should be appended

chart_type type fo chart to use (in c('sunburst','treemap','circle_treemap','partition_chart','icicle'))

Value

A D3partitionR object

| | |
|----------------------------|--|
| set_continuous_color_scale | <i>Add a custom discrete color scale</i> |
|----------------------------|--|

Description

Add a custom discrete color scale

Usage

```
set_continuous_color_scale(D3partitionR_object, color_palette)
```

Arguments

D3partitionR_object

The D3partitionR object to which the data should be appended

color_palette a vector of two colors, the first one is use on the bottom of the scale, the other on the top.

Value

A D3partitionR object

set_legend_parameters *Set the legend parameter*

Description

Set the legend parameter

Usage

```
set_legend_parameters(D3partitionR_object, visible = T, zoom_subset = F,
  width = 100)
```

Arguments

| | |
|---------------------|---|
| D3partitionR_object | The D3partitionR object to which the data should be appended |
| visible | boolean, should the trail be displayed ? Default: TRUE |
| zoom_subset | boolean, if TRUE, only the modalities present in the children of the zoomed root are displayed in the legend. |
| width | legend width in pixel |

Value

A D3partitionR object

set_shiny_input *Configuration of a D3partitionR object as a Shiny input*

Description

Configuration of a D3partitionR object as a Shiny input

Usage

```
set_shiny_input(D3partitionR_object, input_id,
  enabled_inputs = list(clicked_node = T, leaves = T, nodes = T, ancestors =
  T, children_path = F))
```

Arguments

| | |
|---------------------|--|
| D3partitionR_object | The D3partitionR object to which the data should be appended |
| input_id | The id of the input |
| enabled_inputs | which inputs should be enabled ? default to list(clicked_node=T,leaf=T,nodes=T,ancestors=T,child_path=F) |

Value

A D3partitionR object

set_tooltip_parameters

Set the tooltips parameter

Description

Set the tooltips parameter

Usage

```
set_tooltip_parameters(D3partitionR_object, visible = T, style = NULL,
  builder = "table")
```

Arguments

D3partitionR_object

The D3partitionR object to which the data should be appended

visible boolean, should the trail be displayed ? Default: TRUE

style a valid CSS string to be applied to the tooltip. Default: NULL

builder Tooltip builder to use for the tooltip. Can either one of the predefined tooltip ('table', 'basic') or a js expression returning a tooltip.

Value

A D3partitionR object

set_trail

Enable/disable the trail of steps

Description

Enable/disable the trail of steps

Usage

```
set_trail(D3partitionR_object, visible = T)
```

Arguments

D3partitionR_object

The D3partitionR object to which the data should be appended

visible boolean, should the trail be displayed ? Default: TRUE

Value

A D3partitionR object

| | |
|------------|--|
| strip_path | <i>Strip a dataframe containing a step into separate columns</i> |
|------------|--|

Description

Strip a dataframe containing a step into separate columns

Usage

```
strip_path(data, path_col = "path", count_col = "count",
           value_cols = NULL, sep = "->")
```

Arguments

| | |
|------------|---|
| data | A dataframe containing the path. |
| path_col | Name of the column containing the path. The path should be a string of the format "step 1 -> step 2 -> step 3". Default: "path" |
| count_col | Name of the column containing the number of occurrences of the path. Default: "count" |
| value_cols | Names of the other columns to keep. Default: NULL |
| sep | String used to separate the different steps. Default: "->" |

Value

A data.table with the columns specified in count_col, value_cols and one column per step in the path

| | |
|-----------------|------------------------------------|
| tooltip_builder | <i>Build tooltip html function</i> |
|-----------------|------------------------------------|

Description

Build tooltip html function

Usage

```
tooltip_builder(type)
```

Arguments

| | |
|------|---|
| type | a tooltip type: 'basic' (i.e the variable value) or 'table' (i.e. a table with the variables names and value) |
|------|---|

Index

add_data, 2
add_nodes_data, 3
add_title, 3
aggregate_sessions_to_path, 4

compile_D3_partitionR, 4
compute_unique_leaf_name, 5

D3partitionR, 5
D3partitionR-shiny, 6
D3partitionROutput
 (D3partitionR-shiny), 6
df_to_nest, 6

find_min_max_tree, 7

get_all_nodes_names, 7

is_present_variable, 8

plot.D3partitionR, 8

renderD3partitionR
 (D3partitionR-shiny), 6

scale_type, 9
set_chart_type, 10
set_continuous_color_scale, 10
set_discrete_color_scale, 11
set_labels_parameters, 11
set_legend_parameters, 12
set_shiny_input, 12
set_tooltip_parameters, 13
set_trail, 13
strip_path, 14

tooltip_builder, 14