

Package ‘TidyDensity’

January 9, 2024

Title Functions for Tidy Analysis and Generation of Random Data

Version 1.3.0

Description To make it easy to generate random numbers based upon the underlying stats distribution functions. All data is returned in a tidy and structured format making working with the data simple and straight forward. Given that the data is returned in a tidy 'tibble' it lends itself to working with the rest of the 'tidyverse'.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.2.3

URL <https://github.com/spsanderson/TidyDensity>

BugReports <https://github.com/spsanderson/TidyDensity/issues>

Depends R (>= 4.1.0)

Imports magrittr, rlang (>= 0.4.11), dplyr, ggplot2, plotly, tidyr, purrr, actuar, methods, stats, patchwork, survival, nloptr, broom, tidyselect, data.table

Suggests rmarkdown, knitr, roxygen2, EnvStats

VignetteBuilder knitr

NeedsCompilation no

Author Steven Sanderson [aut, cre, cph]
(<<https://orcid.org/0009-0006-7661-8247>>)

Maintainer Steven Sanderson <spsanderson@gmail.com>

Repository CRAN

Date/Publication 2024-01-09 11:10:19 UTC

R topics documented:

bootstrap_density_augment	4
bootstrap_p_augment	5
bootstrap_p_vec	6

bootstrap_q_augment	7
bootstrap_q_vec	8
bootstrap_stat_plot	9
bootstrap_unnest_tbl	10
cgmean	11
chmean	12
ci_hi	13
ci_lo	14
ckurtosis	15
cmean	16
cmedian	17
color_blind	18
convert_to_ts	18
csd	19
cskewness	20
cvar	21
dist_type_extractor	22
td_scale_color_colorblind	23
td_scale_fill_colorblind	23
tidy_autoplot	24
tidy_bernoulli	25
tidy_beta	27
tidy_binomial	28
tidy_bootstrap	30
tidy_burr	31
tidy_cauchy	32
tidy_chisquare	34
tidy_combined_autoplot	35
tidy_combine_distributions	37
tidy_distribution_comparison	38
tidy_distribution_summary_tbl	40
tidy_empirical	42
tidy_exponential	43
tidy_f	44
tidy_four_autoplot	46
tidy_gamma	47
tidy_generalized_beta	49
tidy_generalized_pareto	50
tidy_geometric	52
tidy_hypergeometric	53
tidy_inverse_burr	55
tidy_inverse_exponential	57
tidy_inverse_gamma	58
tidy_inverse_normal	60
tidy_inverse_pareto	61
tidy_inverse_weibull	63
tidy_kurtosis_vec	64
tidy_logistic	65

tidy_lognormal	67
tidy_mixture_density	68
tidy_multi_dist_autoplot	69
tidy_multi_single_dist	71
tidy_negative_binomial	72
tidy_normal	74
tidy_paralogistic	75
tidy_pareto	77
tidy_pareto1	78
tidy_poisson	80
tidy_random_walk	81
tidy_random_walk_autoplot	82
tidy_range_statistic	84
tidy_scale_zero_one_vec	85
tidy_skewness_vec	86
tidy_stat_tbl	87
tidy_t	88
tidy_triangular	90
tidy_uniform	91
tidy_weibull	92
tidy_zero_truncated_binomial	94
tidy_zero_truncated_geometric	95
tidy_zero_truncated_negative_binomial	97
tidy_zero_truncated_poisson	98
triangle_plot	100
util_bernoulli_param_estimate	101
util_bernoulli_stats_tbl	102
util_beta_param_estimate	103
util_beta_stats_tbl	104
util_binomial_param_estimate	105
util_binomial_stats_tbl	107
util_burr_param_estimate	108
util_burr_stats_tbl	109
util_cauchy_param_estimate	110
util_cauchy_stats_tbl	111
util_chisquare_stats_tbl	112
util_exponential_param_estimate	113
util_exponential_stats_tbl	115
util_f_stats_tbl	116
util_gamma_param_estimate	117
util_gamma_stats_tbl	118
util_geometric_param_estimate	119
util_geometric_stats_tbl	120
util_hypergeometric_param_estimate	121
util_hypergeometric_stats_tbl	123
util_logistic_param_estimate	124
util_logistic_stats_tbl	125
util_lognormal_param_estimate	126

util_lognormal_stats_tbl	128
util_negative_binomial_param_estimate	129
util_negative_binomial_stats_tbl	130
util_normal_param_estimate	131
util_normal_stats_tbl	133
util_pareto_param_estimate	134
util_pareto_stats_tbl	135
util_poisson_param_estimate	137
util_poisson_stats_tbl	138
util_triangular_param_estimate	139
util_triangular_stats_tbl	140
util_t_stats_tbl	141
util_uniform_param_estimate	142
util_uniform_stats_tbl	144
util_weibull_param_estimate	145
util_weibull_stats_tbl	146

Index	148
--------------	------------

bootstrap_density_augment
Bootstrap Density Tibble

Description

Add density information to the output of `tidy_bootstrap()`, and `bootstrap_unnest_tbl()`.

Usage

```
bootstrap_density_augment(.data)
```

Arguments

.data	The data that is passed from the <code>tidy_bootstrap()</code> or <code>bootstrap_unnest_tbl()</code> functions.
-------	--

Details

This function takes as input the output of the `tidy_bootstrap()` or `bootstrap_unnest_tbl()` and returns an augmented tibble that has the following columns added to it: `x`, `y`, `dx`, and `dy`.

It looks for an attribute that comes from using `tidy_bootstrap()` or `bootstrap_unnest_tbl()` so it will not work unless the data comes from one of those functions.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Bootstrap: [bootstrap_p_augment\(\)](#), [bootstrap_p_vec\(\)](#), [bootstrap_q_augment\(\)](#), [bootstrap_q_vec\(\)](#), [bootstrap_stat_plot\(\)](#), [bootstrap_unnest_tbl\(\)](#), [tidy_bootstrap\(\)](#)

Other Augment Function: [bootstrap_p_augment\(\)](#), [bootstrap_q_augment\(\)](#)

Examples

```
x <- mtcars$mpg

tidy_bootstrap(x) |>
  bootstrap_density_augment()

tidy_bootstrap(x) |>
  bootstrap_unnest_tbl() |>
  bootstrap_density_augment()
```

bootstrap_p_augment *Augment Bootstrap P*

Description

Takes a numeric vector and will return the ecdf probability.

Usage

```
bootstrap_p_augment(.data, .value, .names = "auto")
```

Arguments

- .data The data being passed that will be augmented by the function.
- .value This is passed [rlang::enquo\(\)](#) to capture the vectors you want to augment.
- .names The default is "auto"

Details

Takes a numeric vector and will return the ecdf probability of that vector. This function is intended to be used on its own in order to add columns to a tibble.

Value

A augmented tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Augment Function: [bootstrap_density_augment\(\)](#), [bootstrap_q_augment\(\)](#)

Other Bootstrap: [bootstrap_density_augment\(\)](#), [bootstrap_p_vec\(\)](#), [bootstrap_q_augment\(\)](#),
[bootstrap_q_vec\(\)](#), [bootstrap_stat_plot\(\)](#), [bootstrap_unnest_tbl\(\)](#), [tidy_bootstrap\(\)](#)

Examples

```
x <- mtcars$mpg
tidy_bootstrap(x) |>
  bootstrap_unnest_tbl() |>
  bootstrap_p_augment(y)
```

bootstrap_p_vec *Compute Bootstrap P of a Vector*

Description

This function takes in a vector as it's input and will return the ecdf probability of a vector.

Usage

```
bootstrap_p_vec(.x)
```

Arguments

.x A numeric

Details

A function to return the ecdf probability of a vector.

Value

A vector

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Bootstrap: [bootstrap_density_augment\(\)](#), [bootstrap_p_augment\(\)](#), [bootstrap_q_augment\(\)](#), [bootstrap_q_vec\(\)](#), [bootstrap_stat_plot\(\)](#), [bootstrap_unnest_tbl\(\)](#), [tidy_bootstrap\(\)](#)
 Other Vector Function: [bootstrap_q_vec\(\)](#), [cgmean\(\)](#), [chmean\(\)](#), [ckurtosis\(\)](#), [cmean\(\)](#), [cmedian\(\)](#),
[csd\(\)](#), [cskewness\(\)](#), [cvar\(\)](#), [tidy_kurtosis_vec\(\)](#), [tidy_scale_zero_one_vec\(\)](#), [tidy_skewness_vec\(\)](#)

Examples

```
x <- mtcars$mpg
bootstrap_p_vec(x)
```

bootstrap_q_augment *Augment Bootstrap Q*

Description

Takes a numeric vector and will return the quantile.

Usage

```
bootstrap_q_augment(.data, .value, .names = "auto")
```

Arguments

- .data The data being passed that will be augmented by the function.
- .value This is passed [rlang::enquo\(\)](#) to capture the vectors you want to augment.
- .names The default is "auto"

Details

Takes a numeric vector and will return the quantile of that vector. This function is intended to be used on its own in order to add columns to a tibble.

Value

A augmented tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Augment Function: [bootstrap_density_augment\(\)](#), [bootstrap_p_augment\(\)](#)
 Other Bootstrap: [bootstrap_density_augment\(\)](#), [bootstrap_p_augment\(\)](#), [bootstrap_p_vec\(\)](#),
[bootstrap_q_vec\(\)](#), [bootstrap_stat_plot\(\)](#), [bootstrap_unnest_tbl\(\)](#), [tidy_bootstrap\(\)](#)

Examples

```
x <- mtcars$mpg

tidy_bootstrap(x) |>
  bootstrap_unnest_tbl() |>
  bootstrap_q_augment(y)
```

bootstrap_q_vec

Compute Bootstrap Q of a Vector

Description

This function takes in a vector as it's input and will return the quantile of a vector.

Usage

```
bootstrap_q_vec(.x)
```

Arguments

.x	A numeric
----	-----------

Details

A function to return the quantile of a vector.

Value

A vector

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Bootstrap: [bootstrap_density_augment\(\)](#), [bootstrap_p_augment\(\)](#), [bootstrap_p_vec\(\)](#), [bootstrap_q_augment\(\)](#), [bootstrap_stat_plot\(\)](#), [bootstrap_unnest_tbl\(\)](#), [tidy_bootstrap\(\)](#)

Other Vector Function: [bootstrap_p_vec\(\)](#), [cgmean\(\)](#), [chmean\(\)](#), [ckurtosis\(\)](#), [cmean\(\)](#), [cmedian\(\)](#), [csd\(\)](#), [cskewness\(\)](#), [cvar\(\)](#), [tidy_kurtosis_vec\(\)](#), [tidy_scale_zero_one_vec\(\)](#), [tidy_skewness_vec\(\)](#)

Examples

```
x <- mtcars$mpg

bootstrap_q_vec(x)
```

bootstrap_stat_plot *Bootstrap Stat Plot*

Description

This function produces a plot of a cumulative statistic function applied to the bootstrap variable from `tidy_bootstrap()` or after `bootstrap_unnest_tbl()` has been applied to it.

Usage

```
bootstrap_stat_plot(  
  .data,  
  .value,  
  .stat = "cmean",  
  .show_groups = FALSE,  
  .show_ci_labels = TRUE,  
  .interactive = FALSE  
)
```

Arguments

.data	The data that comes from either <code>tidy_bootstrap()</code> or after <code>bootstrap_unnest_tbl()</code> is applied to it.
.value	The value column that the calculations are being applied to.
.stat	The cumulative statistic function being applied to the <code>.value</code> column. It must be quoted. The default is "cmean".
.show_groups	The default is FALSE, set to TRUE to get output of all simulations of the bootstrap data.
.show_ci_labels	The default is TRUE, this will show the last value of the upper and lower quantile.
.interactive	The default is FALSE, set to TRUE to get a plotly plot object back.

Details

This function will take in data from either `tidy_bootstrap()` directly or after apply `bootstrap_unnest_tbl()` to its output. There are several different cumulative functions that can be applied to the data. The accepted values are:

- "cmean" - Cumulative Mean
- "chmean" - Cumulative Harmonic Mean
- "cgmean" - Cumulative Geometric Mean
- "csum" = Cumulative Sum
- "cmedian" = Cumulative Median

- "cmax" = Cumulative Max
- "cmin" = Cumulative Min
- "cprod" = Cumulative Product
- "csd" = Cumulative Standard Deviation
- "cvar" = Cumulative Variance
- "cskewness" = Cumulative Skewness
- "ckurtosis" = Cumulative Kurtosis

Value

A plot either ggplot2 or plotly.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Bootstrap: [bootstrap_density_augment\(\)](#), [bootstrap_p_augment\(\)](#), [bootstrap_p_vec\(\)](#), [bootstrap_q_augment\(\)](#), [bootstrap_q_vec\(\)](#), [bootstrap_unnest_tbl\(\)](#), [tidy_bootstrap\(\)](#)

Other Autoplot: [tidy_autoplot\(\)](#), [tidy_combined_autoplot\(\)](#), [tidy_four_autoplot\(\)](#), [tidy_multi_dist_autoplot\(\)](#), [tidy_random_walk_autoplot\(\)](#)

Examples

```
x <- mtcars$mpg

tidy_bootstrap(x) |>
  bootstrap_stat_plot(y, "cmean")

tidy_bootstrap(x, .num_sims = 10) |>
  bootstrap_stat_plot(y,
    .stat = "chmean", .show_groups = TRUE,
    .show_ci_label = FALSE
  )
```

bootstrap_unnest_tbl *Unnest Tidy Bootstrap Tibble*

Description

Unnest the data output from `tidy_bootstrap()`.

Usage

```
bootstrap_unnest_tbl(.data)
```

Arguments

- .data The data that is passed from the `tidy_bootstrap()` function.

Details

This function takes as input the output of the `tidy_bootstrap()` function and returns a two column tibble. The columns are `sim_number` and `y`

It looks for an attribute that comes from using `tidy_bootstrap()` so it will not work unless the data comes from that function.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Bootstrap: `bootstrap_density_augment()`, `bootstrap_p_augment()`, `bootstrap_p_vec()`,
`bootstrap_q_augment()`, `bootstrap_q_vec()`, `bootstrap_stat_plot()`, `tidy_bootstrap()`

Examples

```
tb <- tidy_bootstrap(.x = mtcars$mpg)
bootstrap_unnest_tbl(tb)

bootstrap_unnest_tbl(tb) |>
  tidy_distribution_summary_tbl(sim_number)
```

Description

A function to return the cumulative geometric mean of a vector.

Usage

```
cgmean(.x)
```

Arguments

- .x A numeric vector

Details

A function to return the cumulative geometric mean of a vector. `exp(cummean(log(.x)))`

Value

A numeric vector

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Vector Function: `bootstrap_p_vec()`, `bootstrap_q_vec()`, `chmean()`, `ckurtosis()`, `cmean()`, `cmedian()`, `csd()`, `cskewness()`, `cvar()`, `tidy_kurtosis_vec()`, `tidy_scale_zero_one_vec()`, `tidy_skewness_vec()`

Examples

```
x <- mtcars$mpg
cgmean(x)
```

chmean

Cumulative Harmonic Mean

Description

A function to return the cumulative harmonic mean of a vector.

Usage

`chmean(.x)`

Arguments

.x	A numeric vector
----	------------------

Details

A function to return the cumulative harmonic mean of a vector. $1 / (\text{cumsum}(1 / .x))$

Value

A numeric vector

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Vector Function: [bootstrap_p_vec\(\)](#), [bootstrap_q_vec\(\)](#), [cgmean\(\)](#), [ckurtosis\(\)](#), [cmean\(\)](#), [cmedian\(\)](#), [csd\(\)](#), [cskewness\(\)](#), [cvar\(\)](#), [tidy_kurtosis_vec\(\)](#), [tidy_scale_zero_one_vec\(\)](#), [tidy_skewness_vec\(\)](#)

Examples

```
x <- mtcars$mpg  
chmean(x)
```

ci_hi	<i>Confidence Interval Generic</i>
-------	------------------------------------

Description

Gets the upper 97.5% quantile of a numeric vector.

Usage

```
ci_hi(.x, .na_rm = FALSE)
```

Arguments

.x	A vector of numeric values
.na_rm	A Boolean, defaults to FALSE. Passed to the quantile function.

Details

Gets the upper 97.5% quantile of a numeric vector.

Value

A numeric value.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Statistic: [ci_lo\(\)](#), [tidy_kurtosis_vec\(\)](#), [tidy_range_statistic\(\)](#), [tidy_skewness_vec\(\)](#), [tidy_stat_tbl\(\)](#)

Examples

```
x <- mtcars$mpg
ci_hi(x)
```

ci_lo*Confidence Interval Generic***Description**

Gets the lower 2.5% quantile of a numeric vector.

Usage

```
ci_lo(.x, .na_rm = FALSE)
```

Arguments

- .x A vector of numeric values
- .na_rm A Boolean, defaults to FALSE. Passed to the quantile function.

Details

Gets the lower 2.5% quantile of a numeric vector.

Value

A numeric value.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Statistic: [ci_hi\(\)](#), [tidy_kurtosis_vec\(\)](#), [tidy_range_statistic\(\)](#), [tidy_skewness_vec\(\)](#), [tidy_stat_tbl\(\)](#)

Examples

```
x <- mtcars$mpg
ci_lo(x)
```

ckurtosis

Cumulative Kurtosis

Description

A function to return the cumulative kurtosis of a vector.

Usage

```
ckurtosis(.x)
```

Arguments

.x	A numeric vector
----	------------------

Details

A function to return the cumulative kurtosis of a vector.

Value

A numeric vector

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Vector Function: [bootstrap_p_vec\(\)](#), [bootstrap_q_vec\(\)](#), [cgmean\(\)](#), [chmean\(\)](#), [cmean\(\)](#), [cmedian\(\)](#), [csd\(\)](#), [cskewness\(\)](#), [cvar\(\)](#), [tidy_kurtosis_vec\(\)](#), [tidy_scale_zero_one_vec\(\)](#), [tidy_skewness_vec\(\)](#)

Examples

```
x <- mtcars$mpg  
ckurtosis(x)
```

cmean

Cumulative Mean

Description

A function to return the cumulative mean of a vector.

Usage

```
cmean(.x)
```

Arguments

.x	A numeric vector
----	------------------

Details

A function to return the cumulative mean of a vector. It uses [dplyr::cummean\(\)](#) as the basis of the function.

Value

A numeric vector

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Vector Function: [bootstrap_p_vec\(\)](#), [bootstrap_q_vec\(\)](#), [cgmean\(\)](#), [chmean\(\)](#), [ckurtosis\(\)](#), [cmedian\(\)](#), [csd\(\)](#), [cskewness\(\)](#), [cvar\(\)](#), [tidy_kurtosis_vec\(\)](#), [tidy_scale_zero_one_vec\(\)](#), [tidy_skewness_vec\(\)](#)

Examples

```
x <- mtcars$mpg  
cmean(x)
```

cmedian

Cumulative Median

Description

A function to return the cumulative median of a vector.

Usage

```
cmedian(.x)
```

Arguments

.x	A numeric vector
----	------------------

Details

A function to return the cumulative median of a vector.

Value

A numeric vector

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Vector Function: [bootstrap_p_vec\(\)](#), [bootstrap_q_vec\(\)](#), [cgmean\(\)](#), [chmean\(\)](#), [ckurtosis\(\)](#), [cmean\(\)](#), [csd\(\)](#), [cskewness\(\)](#), [cvar\(\)](#), [tidy_kurtosis_vec\(\)](#), [tidy_scale_zero_one_vec\(\)](#), [tidy_skewness_vec\(\)](#)

Examples

```
x <- mtcars$mpg  
cmedian(x)
```

`color_blind`*Provide Colorblind Compliant Colors*

Description

8 Hex RGB color definitions suitable for charts for colorblind people.

Usage

```
color_blind()
```

`convert_to_ts`*Convert Data to Time Series Format*

Description

This function converts data in a data frame or tibble into a time series format. It is designed to work with data generated from tidy_ distribution functions. The function can return time series data, pivot it into long format, or both.

Usage

```
convert_to_ts(.data, .return_ts = TRUE, .pivot_longer = FALSE)
```

Arguments

- .data A data frame or tibble to be converted into a time series format.
- .return_ts A logical value indicating whether to return the time series data. Default is TRUE.
- .pivot_longer A logical value indicating whether to pivot the data into long format. Default is FALSE.

Details

The function takes a data frame or tibble as input and processes it based on the specified options. It performs the following actions:

1. Checks if the input is a data frame or tibble; otherwise, it raises an error.
2. Checks if the data comes from a tidy_ distribution function; otherwise, it raises an error.
3. Converts the data into a time series format, grouping it by "sim_number" and transforming the "y" column into a time series.
4. Returns the result based on the chosen options:
 - If `ret_ts` is set to TRUE, it returns the time series data.
 - If `pivot_longer` is set to TRUE, it pivots the data into long format.
 - If both options are set to FALSE, it returns the data as a tibble.

Value

The function returns the processed data based on the chosen options:

- If `ret_ts` is set to TRUE, it returns time series data.
- If `pivot_longer` is set to TRUE, it returns the data in long format.
- If both options are set to FALSE, it returns the data as a tibble.

Author(s)

Steven P. Sanderson II, MPH

Examples

```
# Example 1: Convert data to time series format without returning time series data
x <- tidy_normal()
result <- convert_to_ts(x, FALSE)
head(result)

# Example 2: Convert data to time series format and pivot it into long format
x <- tidy_normal()
result <- convert_to_ts(x, FALSE, TRUE)
head(result)

# Example 3: Convert data to time series format and return the time series data
x <- tidy_normal()
result <- convert_to_ts(x)
head(result)
```

Description

A function to return the cumulative standard deviation of a vector.

Usage

```
csd(.x)
```

Arguments

.x	A numeric vector
----	------------------

Details

A function to return the cumulative standard deviation of a vector.

Value

A numeric vector. Note: The first entry will always be NaN.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Vector Function: [bootstrap_p_vec\(\)](#), [bootstrap_q_vec\(\)](#), [cgmean\(\)](#), [chmean\(\)](#), [ckurtosis\(\)](#), [cmean\(\)](#), [cmedian\(\)](#), [cskewness\(\)](#), [cvar\(\)](#), [tidy_kurtosis_vec\(\)](#), [tidy_scale_zero_one_vec\(\)](#), [tidy_skewness_vec\(\)](#)

Examples

```
x <- mtcars$mpg
```

```
csd(x)
```

cskewness

Cumulative Skewness

Description

A function to return the cumulative skewness of a vector.

Usage

```
cskewness(.x)
```

Arguments

.x	A numeric vector
----	------------------

Details

A function to return the cumulative skewness of a vector.

Value

A numeric vector

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Vector Function: [bootstrap_p_vec\(\)](#), [bootstrap_q_vec\(\)](#), [cgmean\(\)](#), [chmean\(\)](#), [ckurtosis\(\)](#), [cmean\(\)](#), [cmedian\(\)](#), [csd\(\)](#), [cvar\(\)](#), [tidy_kurtosis_vec\(\)](#), [tidy_scale_zero_one_vec\(\)](#), [tidy_skewness_vec\(\)](#)

Examples

```
x <- mtcars$mpg  
cskewness(x)
```

cvar*Cumulative Variance*

Description

A function to return the cumulative variance of a vector.

Usage

```
cvar(.x)
```

Arguments

.x	A numeric vector
----	------------------

Details

A function to return the cumulative variance of a vector. `exp(cummean(log(.x)))`

Value

A numeric vector. Note: The first entry will always be NaN.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Vector Function: [bootstrap_p_vec\(\)](#), [bootstrap_q_vec\(\)](#), [cgmean\(\)](#), [chmean\(\)](#), [ckurtosis\(\)](#), [cmean\(\)](#), [cmedian\(\)](#), [csd\(\)](#), [cskewness\(\)](#), [tidy_kurtosis_vec\(\)](#), [tidy_scale_zero_one_vec\(\)](#), [tidy_skewness_vec\(\)](#)

Examples

```
x <- mtcars$mpg  
cvar(x)
```

dist_type_extractor *Extract Distribution Type from Tidy Distribution Object*

Description

Get the distribution name in title case from the `tidy_` distribution function.

Usage

```
dist_type_extractor(.x)
```

Arguments

.x The attribute list passed from a `tidy_` distribution function.

Details

This will extract the distribution type from a `tidy_` distribution function output using the attributes of that object. You must pass the attribute directly to the function. It is meant really to be used internally.

You should be passing if using manually the `$tibble_type` attribute.

Value

A character string

Author(s)

Steven P. Sanderson II,

Examples

```
tn <- tidy_normal()
atb <- attributes(tn)
dist_type_extractor(atb$tibble_type)
```

td_scale_color_colorblind

Provide Colorblind Compliant Colors

Description

Provide Colorblind Compliant Colors

Usage

```
td_scale_color_colorblind(..., theme = "td")
```

Arguments

- | | |
|-------|--|
| ... | Data passed to the function |
| theme | This defaults to td and that is the only allowed value |
-

td_scale_fill_colorblind

Provide Colorblind Compliant Colors

Description

Provide Colorblind Compliant Colors

Usage

```
td_scale_fill_colorblind(..., theme = "td")
```

Arguments

- | | |
|-------|--|
| ... | Data passed to the function |
| theme | This defaults to td and that is the only allowed value |

 tidy_autoplot *Automatic Plot of Density Data*

Description

This is an auto plotting function that will take in a `tidy_` distribution function and a few arguments, one being the plot type, which is a quoted string of one of the following:

- `density`
- `quantile`
- `probablity`
- `qq`
- `mcmc`

If the number of simulations exceeds 9 then the legend will not print. The plot subtitle is put together by the attributes of the table passed to the function.

Usage

```
tidy_autoplot(
  .data,
  .plot_type = "density",
  .line_size = 0.5,
  .geom_point = FALSE,
  .point_size = 1,
  .geom_rug = FALSE,
  .geom_smooth = FALSE,
  .geom_jitter = FALSE,
  .interactive = FALSE
)
```

Arguments

<code>.data</code>	The data passed in from a <code>tidy_distribution</code> function like <code>tidy_normal()</code>
<code>.plot_type</code>	This is a quoted string like <code>'density'</code>
<code>.line_size</code>	The size param <code>ggplot</code>
<code>.geom_point</code>	A Boolean value of TRUE/FALSE, FALSE is the default. TRUE will return a plot with <code>ggplot2::ggeom_point()</code>
<code>.point_size</code>	The point size param for <code>ggplot</code>
<code>.geom_rug</code>	A Boolean value of TRUE/FALSE, FALSE is the default. TRUE will return the use of <code>ggplot2::geom_rug()</code>
<code>.geom_smooth</code>	A Boolean value of TRUE/FALSE, FALSE is the default. TRUE will return the use of <code>ggplot2::geom_smooth()</code> The <code>aes</code> parameter of <code>group</code> is set to FALSE. This ensures a single smoothing band returned with <code>SE</code> also set to FALSE. Color is set to <code>'black'</code> and <code>linetype</code> is <code>'dashed'</code> .

- .geom_jitter A Boolean value of TRUE/FALSE, FALSE is the default. TRUE will return the use of `ggplot2::geom_jitter()`
- .interactive A Boolean value of TRUE/FALSE, FALSE is the default. TRUE will return an interactive `plotly` plot.

Details

This function will spit out one of the following plots:

- `density`
- `quantile`
- `probability`
- `qq`
- `mcmc`

Value

A `ggplot` or a `plotly` plot.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Autoplot: `bootstrap_stat_plot()`, `tidy_combined_autoplot()`, `tidy_four_autoplot()`,
`tidy_multi_dist_autoplot()`, `tidy_random_walk_autoplot()`

Examples

```
tidy_normal(.num_sims = 5) |>
  tidy_autoplot()

tidy_normal(.num_sims = 20) |>
  tidy_autoplot(.plot_type = "qq")
```

`tidy_bernoulli`

Tidy Randomly Generated Bernoulli Distribution Tibble

Description

This function will generate n random points from a Bernoulli distribution with a user provided, `.prob`, and number of random simulations to be produced. The function returns a tibble with the simulation number column the `x` column which corresponds to the n randomly generated points, the `d_`, `p_` and `q_` data points as well.

The data is returned un-grouped.

The columns that are output are:

- `sim_number` The current simulation number.
- `x` The current value of `n` for the current simulation.
- `y` The randomly generated data point.
- `dx` The `x` value from the `stats::density()` function.
- `dy` The `y` value from the `stats::density()` function.
- `p` The values from the resulting `p_` function of the distribution family.
- `q` The values from the resulting `q_` function of the distribution family.

Usage

```
tidy_bernoulli(.n = 50, .prob = 0.1, .num_sims = 1, .return_tibble = TRUE)
```

Arguments

<code>.n</code>	The number of randomly generated points you want.
<code>.prob</code>	The probability of success/failure.
<code>.num_sims</code>	The number of randomly generated simulations you want.
<code>.return_tibble</code>	A logical value indicating whether to return the result as a tibble. Default is <code>TRUE</code> .

Details

This function uses the `rbinom()`, and its underlying `p`, `d`, and `q` functions. The *Bernoulli* distribution is a special case of the *Binomial* distribution with `size = 1` hence this is why the `binom` functions are used and set to `size = 1`.

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

https://en.wikipedia.org/wiki/Bernoulli_distribution

Other Discrete Distribution: `tidy_binomial()`, `tidy_hypergeometric()`, `tidy_negative_binomial()`, `tidy_poisson()`, `tidy_zero_truncated_binomial()`, `tidy_zero_truncated_negative_binomial()`, `tidy_zero_truncated_poisson()`

Other Bernoulli: `util_bernoulli_param_estimate()`, `util_bernoulli_stats_tbl()`

Examples

```
tidy_bernoulli()
```

tidy_beta*Tidy Randomly Generated Beta Distribution Tibble*

Description

This function will generate n random points from a beta distribution with a user provided, .shape1, .shape2, .ncp or non-centrality parameter, and number of random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the [stats::density\(\)](#) function.
- dy The y value from the [stats::density\(\)](#) function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_beta(
  .n = 50,
  .shape1 = 1,
  .shape2 = 1,
  .ncp = 0,
  .num_sims = 1,
  .return_tibble = TRUE
)
```

Arguments

.n	The number of randomly generated points you want.
.shape1	A non-negative parameter of the Beta distribution.
.shape2	A non-negative parameter of the Beta distribution.
.ncp	The non-centrality parameter of the Beta distribution.
.num_sims	The number of randomly generated simulations you want.
.return_tibble	A logical value indicating whether to return the result as a tibble. Default is TRUE.

Details

This function uses the underlying [stats::rbeta\(\)](#), and its underlying p, d, and q functions. For more information please see [stats::rbeta\(\)](#)

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://statisticsglobe.com/beta-distribution-in-r-dbeta-pbeta-qbeta-rbeta>

https://en.wikipedia.org/wiki/Beta_distribution

Other Continuous Distribution: [tidy_burr\(\)](#), [tidy_cauchy\(\)](#), [tidy_chisquare\(\)](#), [tidy_exponential\(\)](#), [tidy_f\(\)](#), [tidy_gamma\(\)](#), [tidy_generalized_beta\(\)](#), [tidy_generalized_pareto\(\)](#), [tidy_geometric\(\)](#), [tidy_inverse_burr\(\)](#), [tidy_inverse_exponential\(\)](#), [tidy_inverse_gamma\(\)](#), [tidy_inverse_normal\(\)](#), [tidy_inverse_pareto\(\)](#), [tidy_inverse_weibull\(\)](#), [tidy_logistic\(\)](#), [tidy_lognormal\(\)](#), [tidy_normal\(\)](#), [tidy_paralogistic\(\)](#), [tidy_pareto1\(\)](#), [tidy_pareto\(\)](#), [tidy_triangular\(\)](#), [tidy_t\(\)](#), [tidy_uniform\(\)](#), [tidy_weibull\(\)](#), [tidy_zero_truncated_geometric\(\)](#)

Other Beta: [tidy_generalized_beta\(\)](#), [util_beta_param_estimate\(\)](#), [util_beta_stats_tbl\(\)](#)

Examples

```
tidy_beta()
```

tidy_binomial

Tidy Randomly Generated Binomial Distribution Tibble

Description

This function will generate n random points from a binomial distribution with a user provided, .size, .prob, and number of random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the [stats::density\(\)](#) function.
- dy The y value from the [stats::density\(\)](#) function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_binomial(  
  .n = 50,  
  .size = 0,  
  .prob = 1,  
  .num_sims = 1,  
  .return_tibble = TRUE  
)
```

Arguments

.n	The number of randomly generated points you want.
.size	Number of trials, zero or more.
.prob	Probability of success on each trial.
.num_sims	The number of randomly generated simulations you want.
.return_tibble	A logical value indicating whether to return the result as a tibble. Default is TRUE.

Details

This function uses the underlying `stats::rbinom()`, and its underlying p, d, and q functions. For more information please see [stats::rbinom\(\)](#)

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://www.itl.nist.gov/div898/handbook/eda/section3/eda366i.htm>

Other Discrete Distribution: `tidy_bernoulli()`, `tidy_hypergeometric()`, `tidy_negative_binomial()`, `tidy_poisson()`, `tidy_zero_truncated_binomial()`, `tidy_zero_truncated_negative_binomial()`, `tidy_zero_truncated_poisson()`

Other Binomial: `tidy_negative_binomial()`, `tidy_zero_truncated_binomial()`, `tidy_zero_truncated_negative_binomial()`, `util_binomial_param_estimate()`, `util_binomial_stats_tbl()`, `util_negative_binomial_param_estimate()`

Examples

```
tidy_binomial()
```

`tidy_bootstrap` *Bootstrap Empirical Data*

Description

Takes an input vector of numeric data and produces a bootstrapped nested tibble by simulation number.

Usage

```
tidy_bootstrap(
  .x,
  .num_sims = 2000,
  .proportion = 0.8,
  .distribution_type = "continuous"
)
```

Arguments

.x	The vector of data being passed to the function. Must be a numeric vector.
.num_sims	The default is 2000, can be set to anything desired. A warning will pass to the console if the value is less than 2000.
.proportion	How much of the original data do you want to pass through to the sampling function. The default is 0.80 (80%)
.distribution_type	This can either be 'continuous' or 'discrete'

Details

This function will take in a numeric input vector and produce a tibble of bootstrapped values in a list. The table that is output will have two columns: `sim_number` and `bootstrap_samples`

The `sim_number` corresponds to how many times you want the data to be resampled, and the `bootstrap_samples` column contains a list of the bootstrapped resampled data.

Value

A nested tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Bootstrap: [bootstrap_density_augment\(\)](#), [bootstrap_p_augment\(\)](#), [bootstrap_p_vec\(\)](#), [bootstrap_q_augment\(\)](#), [bootstrap_q_vec\(\)](#), [bootstrap_stat_plot\(\)](#), [bootstrap_unnest_tbl\(\)](#)

Examples

```
x <- mtcars$mpg
tidy_bootstrap(x)
```

tidy_burr

Tidy Randomly Generated Burr Distribution Tibble

Description

This function will generate n random points from a Burr distribution with a user provided, .shape1, .shape2, .scale, .rate, and number of random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the `stats::density()` function.
- dy The y value from the `stats::density()` function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_burr(
  .n = 50,
  .shape1 = 1,
  .shape2 = 1,
  .rate = 1,
  .scale = 1/.rate,
  .num_sims = 1,
  .return_tibble = TRUE
)
```

Arguments

.n	The number of randomly generated points you want.
.shape1	Must be strictly positive.
.shape2	Must be strictly positive.
.rate	An alternative way to specify the .scale.

- .scale Must be strictly positive.
- .num_sims The number of randomly generated simulations you want.
- .return_tibble A logical value indicating whether to return the result as a tibble. Default is TRUE.

Details

This function uses the underlying `actuar::rburr()`, and its underlying `p`, `d`, and `q` functions. For more information please see [actuar::rburr\(\)](#)

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://openacttexts.github.io/Loss-Data-Analytics/ChapSummaryDistributions.html>

Other Continuous Distribution: [tidy_beta\(\)](#), [tidy_cauchy\(\)](#), [tidy_chisquare\(\)](#), [tidy_exponential\(\)](#), [tidy_f\(\)](#), [tidy_gamma\(\)](#), [tidy_generalized_beta\(\)](#), [tidy_generalized_pareto\(\)](#), [tidy_geometric\(\)](#), [tidy_inverse_burr\(\)](#), [tidy_inverse_exponential\(\)](#), [tidy_inverse_gamma\(\)](#), [tidy_inverse_normal\(\)](#), [tidy_inverse_pareto\(\)](#), [tidy_inverse_weibull\(\)](#), [tidy_logistic\(\)](#), [tidy_lognormal\(\)](#), [tidy_normal\(\)](#), [tidy_paralogistic\(\)](#), [tidy_pareto1\(\)](#), [tidy_pareto\(\)](#), [tidy_triangular\(\)](#), [tidy_t\(\)](#), [tidy_uniform\(\)](#), [tidy_weibull\(\)](#), [tidy_zero_truncated_geometric\(\)](#)

Other Burr: [tidy_inverse_burr\(\)](#), [util_burr_param_estimate\(\)](#), [util_burr_stats_tbl\(\)](#)

Examples

`tidy_burr()`

`tidy_cauchy`

Tidy Randomly Generated Cauchy Distribution Tibble

Description

This function will generate `n` random points from a cauchy distribution with a user provided, `.location`, `.scale`, and number of random simulations to be produced. The function returns a tibble with the simulation number column the `x` column which corresponds to the `n` randomly generated points, the `d_`, `p_` and `q_` data points as well.

The data is returned un-grouped.

The columns that are output are:

- `sim_number` The current simulation number.

- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the `stats::density()` function.
- dy The y value from the `stats::density()` function.
- p The values from the resulting $p_{\text{--}}$ function of the distribution family.
- q The values from the resulting $q_{\text{--}}$ function of the distribution family.

Usage

```
tidy_cauchy(
  .n = 50,
  .location = 0,
  .scale = 1,
  .num_sims = 1,
  .return_tibble = TRUE
)
```

Arguments

<code>.n</code>	The number of randomly generated points you want.
<code>.location</code>	The location parameter.
<code>.scale</code>	The scale parameter, must be greater than or equal to 0.
<code>.num_sims</code>	The number of randomly generated simulations you want.
<code>.return_tibble</code>	A logical value indicating whether to return the result as a tibble. Default is TRUE.

Details

This function uses the underlying `stats::rcauchy()`, and its underlying p , d , and q functions. For more information please see [stats::rcauchy\(\)](#)

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://www.itl.nist.gov/div898/handbook/eda/section3/eda3663.htm>

Other Continuous Distribution: `tidy_beta()`, `tidy_burr()`, `tidy_chisquare()`, `tidy_exponential()`, `tidy_f()`, `tidy_gamma()`, `tidy_generalized_beta()`, `tidy_generalized_pareto()`, `tidy_geometric()`, `tidy_inverse_burr()`, `tidy_inverse_exponential()`, `tidy_inverse_gamma()`, `tidy_inverse_normal()`, `tidy_inverse_pareto()`, `tidy_inverse_weibull()`, `tidy_logistic()`, `tidy_lognormal()`, `tidy_normal()`,

```
tidy_paralogistic(), tidy_pareto1(), tidy_pareto(), tidy_triangular(), tidy_t(), tidy_uniform(),
tidy_weibull(), tidy_zero_truncated_geometric()
Other Cauchy: util_cauchy_param_estimate(), util_cauchy_stats_tbl()
```

Examples

```
tidy_cauchy()
```

tidy_chisquare	<i>Tidy Randomly Generated Chisquare (Non-Central) Distribution Tibble</i>
----------------	--

Description

This function will generate n random points from a chisquare distribution with a user provided, .df, .ncp, and number of random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the `stats::density()` function.
- dy The y value from the `stats::density()` function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_chisquare(
  .n = 50,
  .df = 1,
  .ncp = 1,
  .num_sims = 1,
  .return_tibble = TRUE
)
```

Arguments

- | | |
|----------------|---|
| .n | The number of randomly generated points you want. |
| .df | Degrees of freedom (non-negative but can be non-integer) |
| .ncp | Non-centrality parameter, must be non-negative. |
| .num_sims | The number of randomly generated simulations you want. |
| .return_tibble | A logical value indicating whether to return the result as a tibble. Default is TRUE. |

Details

This function uses the underlying `stats::rchiisq()`, and its underlying p, d, and q functions. For more information please see [stats::rchiisq\(\)](#)

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://www.itl.nist.gov/div898/handbook/eda/section3/eda3666.htm>

Other Continuous Distribution: `tidy_beta()`, `tidy_burr()`, `tidy_cauchy()`, `tidy_exponential()`, `tidy_f()`, `tidy_gamma()`, `tidy_generalized_beta()`, `tidy_generalized_pareto()`, `tidy_geometric()`, `tidy_inverse_burr()`, `tidy_inverse_exponential()`, `tidy_inverse_gamma()`, `tidy_inverse_normal()`, `tidy_inverse_pareto()`, `tidy_inverse_weibull()`, `tidy_logistic()`, `tidy_lognormal()`, `tidy_normal()`, `tidy_paralogistic()`, `tidy_pareto1()`, `tidy_pareto()`, `tidy_triangular()`, `tidy_t()`, `tidy_uniform()`, `tidy_weibull()`, `tidy_zero_truncated_geometric()`

Other Chisquare: `util_chisquare_stats_tbl()`

Examples

```
tidy_chisquare()
```

tidy_combined_autoplot

Automatic Plot of Combined Multi Dist Data

Description

This is an auto plotting function that will take in a `tidy_` distribution function and a few arguments, one being the plot type, which is a quoted string of one of the following:

- density
- quantile
- probability
- qq

If the number of simulations exceeds 9 then the legend will not print. The plot subtitle is put together by the attributes of the table passed to the function.

Usage

```
tidy_combined_autoplot(
  .data,
  .plot_type = "density",
  .line_size = 0.5,
  .geom_point = FALSE,
  .point_size = 1,
  .geom_rug = FALSE,
  .geom_smooth = FALSE,
  .geom_jitter = FALSE,
  .interactive = FALSE
)
```

Arguments

.data	The data passed in from a the function <code>tidy_multi_dist()</code>
.plot_type	This is a quoted string like 'density'
.line_size	The size param ggplot
.geom_point	A Boolean value of TRUE/FALSE, FALSE is the default. TRUE will return a plot with <code>ggplot2::ggeom_point()</code>
.point_size	The point size param for ggplot
.geom_rug	A Boolean value of TRUE/FALSE, FALSE is the default. TRUE will return the use of <code>ggplot2::geom_rug()</code>
.geom_smooth	A Boolean value of TRUE/FALSE, FALSE is the default. TRUE will return the use of <code>ggplot2::geom_smooth()</code> The aes parameter of group is set to FALSE. This ensures a single smoothing band returned with SE also set to FALSE. Color is set to 'black' and linetype is 'dashed'.
.geom_jitter	A Boolean value of TRUE/FALSE, FALSE is the default. TRUE will return the use of <code>ggplot2::geom_jitter()</code>
.interactive	A Boolean value of TRUE/FALSE, FALSE is the default. TRUE will return an interactive plotly plot.

Details

This function will spit out one of the following plots:

- density
- quantile
- probability
- qq

Value

A ggplot or a plotly plot.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Autoplot: [bootstrap_stat_plot\(\)](#), [tidy_autoplot\(\)](#), [tidy_four_autoplot\(\)](#), [tidy_multi_dist_autoplot\(\)](#), [tidy_random_walk_autoplot\(\)](#)

Examples

```
combined_tbl <- tidy_combine_distributions(  
  tidy_normal(),  
  tidy_gamma(),  
  tidy_beta()  
)  
  
combined_tbl  
  
combined_tbl |>  
  tidy_combined_autoplot()  
  
combined_tbl |>  
  tidy_combined_autoplot(.plot_type = "qq")
```

tidy_combine_distributions

Combine Multiple Tidy Distributions of Different Types

Description

This allows a user to specify any n number of tidy_ distributions that can be combined into a single tibble. This is the preferred method for combining multiple distributions of different types, for example a Gaussian distribution and a Beta distribution.

This generates a single tibble with an added column of dist_type that will give the distribution family name and its associated parameters.

Usage

```
tidy_combine_distributions(...)
```

Arguments

... The ... is where you can place your different distributions

Details

Allows a user to generate a tibble of different tidy_ distributions

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Multiple Distribution: [tidy_multi_single_dist\(\)](#)

Examples

```
tn <- tidy_normal()
tb <- tidy_beta()
tc <- tidy_cauchy()

tidy_combine_distributions(tn, tb, tc)

## OR

tidy_combine_distributions(
  tidy_normal(),
  tidy_beta(),
  tidy_cauchy(),
  tidy_logistic()
)
```

tidy_distribution_comparison
Compare Empirical Data to Distributions

Description

Compare some empirical data set against different distributions to help find the distribution that could be the best fit.

Usage

```
tidy_distribution_comparison(
  .x,
  .distribution_type = "continuous",
  .round_to_place = 3
)
```

Arguments

- .x The data set being passed to the function
- .distribution_type What kind of data is it, can be one of continuous or discrete
- .round_to_place How many decimal places should the parameter estimates be rounded off to for distribution construction. The default is 3

Details

The purpose of this function is to take some data set provided and to try to find a distribution that may fit the best. A parameter of .distribution_type must be set to either continuous or discrete in order for this the function to try the appropriate types of distributions.

The following distributions are used:

Continuous:

- tidy_beta
- tidy_cauchy
- tidy_exponential
- tidy_gamma
- tidy_logistic
- tidy_lognormal
- tidy_normal
- tidy_pareto
- tidy_uniform
- tidy_weibull

Discrete:

- tidy_binomial
- tidy_geometric
- tidy_hypergeometric
- tidy_poisson

The function itself returns a list output of tibbles. Here are the tibbles that are returned:

- comparison_tbl
- deviance_tbl
- total_deviance_tbl
- aic_tbl
- kolmogorov_smirnov_tbl
- multi_metric_tbl

The `comparison_tbl` is a long tibble that lists the values of the density function against the given data.

The `deviance_tbl` and the `total_deviance_tbl` just give the simple difference from the actual density to the estimated density for the given estimated distribution.

The `aic_tbl` will provide the AIC for a `lm` model of the estimated density against the empirical density.

The `kolmogorov_smirnov_tbl` for now provides a two.sided estimate of the `ks.test` of the estimated density against the empirical.

The `multi_metric_tbl` will summarise all of these metrics into a single tibble.

Value

An invisible list object. A tibble is printed.

Author(s)

Steven P. Sanderson II, MPH

Examples

```
xc <- mtcars$mpg
output_c <- tidy_distribution_comparison(xc, "continuous")

xd <- trunc(xc)
output_d <- tidy_distribution_comparison(xd, "discrete")

output_c
```

tidy_distribution_summary_tbl

Tidy Distribution Summary Statistics Tibble

Description

This function returns a summary statistics tibble. It will use the `y` column from the `tidy_ distribution` function.

Usage

```
tidy_distribution_summary_tbl(.data, ...)
```

Arguments

- .data The data that is going to be passed from a `tidy_ distribution` function.
- ... This is the grouping variable that gets passed to `dplyr::group_by()` and `dplyr::select()`.

Details

This function takes in a `tidy_` distribution table and will return a tibble of the following information:

- `sim_number`
- `mean_val`
- `median_val`
- `std_val`
- `min_val`
- `max_val`
- `skewness`
- `kurtosis`
- `range`
- `iqr`
- `variance`
- `ci_hi`
- `ci_lo`

The kurtosis and skewness come from the package `healthyR.ai`

Value

A summary stats tibble

Author(s)

Steven P. Sanderson II, MPH

Examples

```
library(dplyr)

tn <- tidy_normal(.num_sims = 5)
tb <- tidy_beta(.num_sims = 5)

tidy_distribution_summary_tbl(tn)
tidy_distribution_summary_tbl(tn, sim_number)

data_tbl <- tidy_combine_distributions(tn, tb)

tidy_distribution_summary_tbl(data_tbl)
tidy_distribution_summary_tbl(data_tbl, dist_type)
```

tidy_empirical *Tidy Empirical*

Description

This function takes in a single argument of `.x` a vector and will return a tibble of information similar to the `tidy_` distribution functions. The `y` column is set equal to `dy` from the `density` function.

Usage

```
tidy_empirical(.x, .num_sims = 1, .distribution_type = "continuous")
```

Arguments

- `.x` A vector of numbers
- `.num_sims` How many simulations should be run, defaults to 1.
- `.distribution_type`
 - A string of either "continuous" or "discrete". The function will default to "continuous"

Details

This function takes in a single argument of `.x` a vector

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

Examples

```
x <- mtcars$mpg
tidy_empirical(.x = x, .distribution_type = "continuous")
tidy_empirical(.x = x, .num_sims = 10, .distribution_type = "continuous")
```

tidy_exponential *Tidy Randomly Generated Exponential Distribution Tibble*

Description

This function will generate n random points from a exponential distribution with a user provided, .rate, and number of random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the `stats::density()` function.
- dy The y value from the `stats::density()` function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_exponential(.n = 50, .rate = 1, .num_sims = 1, .return_tibble = TRUE)
```

Arguments

- .n The number of randomly generated points you want.
- .rate A vector of rates
- .num_sims The number of randomly generated simulations you want.
- .return_tibble A logical value indicating whether to return the result as a tibble. Default is TRUE.

Details

This function uses the underlying `stats::rexp()`, and its underlying p, d, and q functions. For more information please see `stats::rexp()`

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://www.itl.nist.gov/div898/handbook/eda/section3/eda3667.htm>

Other Continuous Distribution: [tidy_beta\(\)](#), [tidy_burr\(\)](#), [tidy_cauchy\(\)](#), [tidy_chisquare\(\)](#), [tidy_f\(\)](#), [tidy_gamma\(\)](#), [tidy_generalized_beta\(\)](#), [tidy_generalized_pareto\(\)](#), [tidy_geometric\(\)](#), [tidy_inverse_burr\(\)](#), [tidy_inverse_exponential\(\)](#), [tidy_inverse_gamma\(\)](#), [tidy_inverse_normal\(\)](#), [tidy_inverse_pareto\(\)](#), [tidy_inverse_weibull\(\)](#), [tidy_logistic\(\)](#), [tidy_lognormal\(\)](#), [tidy_normal\(\)](#), [tidy_paralogistic\(\)](#), [tidy_pareto1\(\)](#), [tidy_pareto\(\)](#), [tidy_triangular\(\)](#), [tidy_t\(\)](#), [tidy_uniform\(\)](#), [tidy_weibull\(\)](#), [tidy_zero_truncated_geometric\(\)](#)

Other Exponential: [tidy_inverse_exponential\(\)](#), [util_exponential_param_estimate\(\)](#), [util_exponential_stats_](#)

Examples

```
tidy_exponential()
```

tidy_f

Tidy Randomly Generated F Distribution Tibble

Description

This function will generate n random points from a rf distribution with a user provided, df1,df2, and ncp, and number of random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the [stats::density\(\)](#) function.
- dy The y value from the [stats::density\(\)](#) function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_f(
  .n = 50,
  .df1 = 1,
  .df2 = 1,
  .ncp = 0,
  .num_sims = 1,
  .return_tibble = TRUE
)
```

Arguments

.n	The number of randomly generated points you want.
.df1	Degrees of freedom, Inf is allowed.
.df2	Degrees of freedom, Inf is allowed.
.ncp	Non-centrality parameter.
.num_sims	The number of randomly generated simulations you want.
.return_tibble	A logical value indicating whether to return the result as a tibble. Default is TRUE.

Details

This function uses the underlying `stats::rf()`, and its underlying p, d, and q functions. For more information please see [stats::rf\(\)](#)

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://www.itl.nist.gov/div898/handbook/eda/section3/eda3665.htm>

Other Continuous Distribution: `tidy_beta()`, `tidy_burr()`, `tidy_cauchy()`, `tidy_chisquare()`, `tidy_exponential()`, `tidy_gamma()`, `tidy_generalized_beta()`, `tidy_generalized_pareto()`, `tidy_geometric()`, `tidy_inverse_burr()`, `tidy_inverse_exponential()`, `tidy_inverse_gamma()`, `tidy_inverse_normal()`, `tidy_inverse_pareto()`, `tidy_inverse_weibull()`, `tidy_logistic()`, `tidy_lognormal()`, `tidy_normal()`, `tidy_paralogistic()`, `tidy_pareto1()`, `tidy_pareto()`, `tidy_triangular()`, `tidy_t()`, `tidy_uniform()`, `tidy_weibull()`, `tidy_zero_truncated_geometric()`

Other F Distribution: `util_f_stats_tbl()`

Examples

`tidy_f()`

tidy_four_autoplot *Automatic Plot of Density Data*

Description

This is an auto plotting function that will take in a `tidy_` distribution function and a few arguments, one being the plot type, which is a quoted string of one of the following:

- `density`
- `quantile`
- `probablity`
- `qq`

If the number of simulations exceeds 9 then the legend will not print. The plot subtitle is put together by the attributes of the table passed to the function.

Usage

```
tidy_four_autoplot(
  .data,
  .line_size = 0.5,
  .geom_point = FALSE,
  .point_size = 1,
  .geom_rug = FALSE,
  .geom_smooth = FALSE,
  .geom_jitter = FALSE,
  .interactive = FALSE
)
```

Arguments

<code>.data</code>	The data passed in from a <code>tidy_distribution</code> function like <code>tidy_normal()</code>
<code>.line_size</code>	The size param <code>ggplot</code>
<code>.geom_point</code>	A Boolean value of TRUE/FALSE, FALSE is the default. TRUE will return a plot with <code>ggplot2::ggeom_point()</code>
<code>.point_size</code>	The point size param for <code>ggplot</code>
<code>.geom_rug</code>	A Boolean value of TRUE/FALSE, FALSE is the default. TRUE will return the use of <code>ggplot2::geom_rug()</code>
<code>.geom_smooth</code>	A Boolean value of TRUE/FALSE, FALSE is the default. TRUE will return the use of <code>ggplot2::geom_smooth()</code> The <code>aes</code> parameter of group is set to FALSE. This ensures a single smoothing band returned with SE also set to FALSE. Color is set to 'black' and <code>linetype</code> is 'dashed'.
<code>.geom_jitter</code>	A Boolean value of TRUE/FALSE, FALSE is the default. TRUE will return the use of <code>ggplot2::geom_jitter()</code>
<code>.interactive</code>	A Boolean value of TRUE/FALSE, FALSE is the default. TRUE will return an interactive <code>plotly</code> plot.

Details

This function will spit out one of the following plots:

- density
- quantile
- probability
- qq

Value

A ggplot or a plotly plot.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Autoplot: [bootstrap_stat_plot\(\)](#), [tidy_autoplot\(\)](#), [tidy_combined_autoplot\(\)](#), [tidy_multi_dist_autoplot\(\)](#), [tidy_random_walk_autoplot\(\)](#)

Examples

```
tidy_normal(.num_sims = 5) |>  
  tidy_four_autoplot()
```

tidy_gamma

Tidy Randomly Generated Gamma Distribution Tibble

Description

This function will generate n random points from a gamma distribution with a user provided, .shape, .scale, and number of random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the [stats::density\(\)](#) function.
- dy The y value from the [stats::density\(\)](#) function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_gamma(
  .n = 50,
  .shape = 1,
  .scale = 0.3,
  .num_sims = 1,
  .return_tibble = TRUE
)
```

Arguments

.n	The number of randomly generated points you want.
.shape	This is strictly 0 to infinity.
.scale	The standard deviation of the randomly generated data. This is strictly from 0 to infinity.
.num_sims	The number of randomly generated simulations you want.
.return_tibble	A logical value indicating whether to return the result as a tibble. Default is TRUE.

Details

This function uses the underlying `stats::rgamma()`, and its underlying p, d, and q functions. For more information please see [stats::rgamma\(\)](#)

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://www.statology.org/fit-gamma-distribution-to-dataset-in-r/>

https://en.wikipedia.org/wiki/Gamma_distribution

Other Continuous Distribution: [tidy_beta\(\)](#), [tidy_burr\(\)](#), [tidy_cauchy\(\)](#), [tidy_chisquare\(\)](#), [tidy_exponential\(\)](#), [tidy_f\(\)](#), [tidy_generalized_beta\(\)](#), [tidy_generalized_pareto\(\)](#), [tidy_geometric\(\)](#), [tidy_inverse_burr\(\)](#), [tidy_inverse_exponential\(\)](#), [tidy_inverse_gamma\(\)](#), [tidy_inverse_normal\(\)](#), [tidy_inverse_pareto\(\)](#), [tidy_inverse_weibull\(\)](#), [tidy_logistic\(\)](#), [tidy_lognormal\(\)](#), [tidy_normal\(\)](#), [tidy_paralogistic\(\)](#), [tidy_pareto1\(\)](#), [tidy_pareto\(\)](#), [tidy_triangular\(\)](#), [tidy_t\(\)](#), [tidy_uniform\(\)](#), [tidy_weibull\(\)](#), [tidy_zero_truncated_geometric\(\)](#)

Other Gamma: [tidy_inverse_gamma\(\)](#), [util_gamma_param_estimate\(\)](#), [util_gamma_stats_tbl\(\)](#)

Examples

```
tidy_gamma()
```

tidy_generalized_beta *Tidy Randomly Generated Generalized Beta Distribution Tibble*

Description

This function will generate n random points from a generalized beta distribution with a user provided, .shape1, .shape2, .shape3, .rate, and/or .scale, and number of random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the `stats::density()` function.
- dy The y value from the `stats::density()` function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_generalized_beta(
  .n = 50,
  .shape1 = 1,
  .shape2 = 1,
  .shape3 = 1,
  .rate = 1,
  .scale = 1/.rate,
  .num_sims = 1,
  .return_tibble = TRUE
)
```

Arguments

.n	The number of randomly generated points you want.
.shape1	A non-negative parameter of the Beta distribution.
.shape2	A non-negative parameter of the Beta distribution.
.shape3	A non-negative parameter of the Beta distribution.
.rate	An alternative way to specify the .scale parameter.
.scale	Must be strictly positive.
.num_sims	The number of randomly generated simulations you want.
.return_tibble	A logical value indicating whether to return the result as a tibble. Default is TRUE.

Details

This function uses the underlying `stats::rbeta()`, and its underlying p, d, and q functions. For more information please see [stats::rbeta\(\)](#)

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://statisticsglobe.com/beta-distribution-in-r-rbeta-pbeta-qbeta-rbeta>
https://en.wikipedia.org/wiki/Beta_distribution
<https://openacttexts.github.io/Loss-Data-Analytics/ChapSummaryDistributions.html>

Other Continuous Distribution: [tidy_beta\(\)](#), [tidy_burr\(\)](#), [tidy_cauchy\(\)](#), [tidy_chisquare\(\)](#), [tidy_exponential\(\)](#), [tidy_f\(\)](#), [tidy_gamma\(\)](#), [tidy_generalized_pareto\(\)](#), [tidy_geometric\(\)](#), [tidy_inverse_burr\(\)](#), [tidy_inverse_exponential\(\)](#), [tidy_inverse_gamma\(\)](#), [tidy_inverse_normal\(\)](#), [tidy_inverse_pareto\(\)](#), [tidy_inverse_weibull\(\)](#), [tidy_logistic\(\)](#), [tidy_lognormal\(\)](#), [tidy_normal\(\)](#), [tidy_paralogistic\(\)](#), [tidy_pareto1\(\)](#), [tidy_pareto\(\)](#), [tidy_triangular\(\)](#), [tidy_t\(\)](#), [tidy_uniform\(\)](#), [tidy_weibull\(\)](#), [tidy_zero_truncated_geometric\(\)](#)

Other Beta: [tidy_beta\(\)](#), [util_beta_param_estimate\(\)](#), [util_beta_stats_tbl\(\)](#)

Examples

```
tidy_generalized_beta()
```

tidy_generalized_pareto

Tidy Randomly Generated Generalized Pareto Distribution Tibble

Description

This function will generate n random points from a generalized Pareto distribution with a user provided, .shape1, .shape2, .rate or .scale and number of #' random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.

- `y` The randomly generated data point.
- `dx` The `x` value from the `stats::density()` function.
- `dy` The `y` value from the `stats::density()` function.
- `p` The values from the resulting `p_` function of the distribution family.
- `q` The values from the resulting `q_` function of the distribution family.

Usage

```
tidy_generalized_pareto(  
  .n = 50,  
  .shape1 = 1,  
  .shape2 = 1,  
  .rate = 1,  
  .scale = 1/.rate,  
  .num_sims = 1,  
  .return_tibble = TRUE  
)
```

Arguments

<code>.n</code>	The number of randomly generated points you want.
<code>.shape1</code>	Must be positive.
<code>.shape2</code>	Must be positive.
<code>.rate</code>	An alternative way to specify the <code>.scale</code> argument
<code>.scale</code>	Must be positive.
<code>.num_sims</code>	The number of randomly generated simulations you want.
<code>.return_tibble</code>	A logical value indicating whether to return the result as a tibble. Default is <code>TRUE</code> .

Details

This function uses the underlying `actuar::rgenpareto()`, and its underlying `p`, `d`, and `q` functions. For more information please see [actuar::rgenpareto\(\)](#)

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://openacttexts.github.io/Loss-Data-Analytics/ChapSummaryDistributions.html>

Other Continuous Distribution: [tidy_beta\(\)](#), [tidy_burr\(\)](#), [tidy_cauchy\(\)](#), [tidy_chisquare\(\)](#), [tidy_exponential\(\)](#), [tidy_f\(\)](#), [tidy_gamma\(\)](#), [tidy_generalized_beta\(\)](#), [tidy_geometric\(\)](#), [tidy_inverse_burr\(\)](#), [tidy_inverse_exponential\(\)](#), [tidy_inverse_gamma\(\)](#), [tidy_inverse_normal\(\)](#), [tidy_inverse_pareto\(\)](#), [tidy_inverse_weibull\(\)](#), [tidy_logistic\(\)](#), [tidy_lognormal\(\)](#), [tidy_normal\(\)](#), [tidy_paralogistic\(\)](#), [tidy_pareto1\(\)](#), [tidy_pareto\(\)](#), [tidy_triangular\(\)](#), [tidy_t\(\)](#), [tidy_uniform\(\)](#), [tidy_weibull\(\)](#), [tidy_zero_truncated_geometric\(\)](#)

Other Pareto: [tidy_inverse_pareto\(\)](#), [tidy_pareto1\(\)](#), [tidy_pareto\(\)](#), [util_pareto_param_estimate\(\)](#), [util_pareto_stats_tbl\(\)](#)

Examples

```
tidy_generalized_pareto()
```

tidy_geometric

Tidy Randomly Generated Geometric Distribution Tibble

Description

This function will generate n random points from a geometric distribution with a user provided, .prob, and number of random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the [stats::density\(\)](#) function.
- dy The y value from the [stats::density\(\)](#) function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_geometric(.n = 50, .prob = 1, .num_sims = 1, .return_tibble = TRUE)
```

Arguments

- .n The number of randomly generated points you want.
- .prob A probability of success in each trial $0 < \text{prob} \leq 1$.
- .num_sims The number of randomly generated simulations you want.
- .return_tibble A logical value indicating whether to return the result as a tibble. Default is TRUE.

Details

This function uses the underlying `stats::rgeom()`, and its underlying p, d, and q functions. For more information please see [stats::rgeom\(\)](#)

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

https://en.wikipedia.org/wiki/Geometric_distribution

Other Continuous Distribution: `tidy_beta()`, `tidy_burr()`, `tidy_cauchy()`, `tidy_chisquare()`, `tidy_exponential()`, `tidy_f()`, `tidy_gamma()`, `tidy_generalized_beta()`, `tidy_generalized_pareto()`, `tidy_inverse_burr()`, `tidy_inverse_exponential()`, `tidy_inverse_gamma()`, `tidy_inverse_normal()`, `tidy_inverse_pareto()`, `tidy_inverse_weibull()`, `tidy_logistic()`, `tidy_lognormal()`, `tidy_normal()`, `tidy_paralogistic()`, `tidy_pareto1()`, `tidy_pareto()`, `tidy_triangular()`, `tidy_t()`, `tidy_uniform()`, `tidy_weibull()`, `tidy_zero_truncated_geometric()`

Other Geometric: `tidy_zero_truncated_geometric()`, `util_geometric_param_estimate()`, `util_geometric_stats_tbl()`

Examples

```
tidy_geometric()
```

Description

This function will generate n random points from a hypergeometric distribution with a user provided, m,nn, and k, and number of random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the `stats::density()` function.
- dy The y value from the `stats::density()` function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_hypergeometric(
  .n = 50,
  .m = 0,
  .nn = 0,
  .k = 0,
  .num_sims = 1,
  .return_tibble = TRUE
)
```

Arguments

.n	The number of randomly generated points you want.
.m	The number of white balls in the urn
.nn	The number of black balls in the urn
.k	The number of balls drawn fro the urn.
.num_sims	The number of randomly generated simulations you want.
.return_tibble	A logical value indicating whether to return the result as a tibble. Default is TRUE.

Details

This function uses the underlying `stats::rhyper()`, and its underlying p, d, and q functions. For more information please see `stats::rhyper()`

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

https://en.wikipedia.org/wiki/Hypergeometric_distribution

Other Discrete Distribution: [tidy_bernoulli\(\)](#), [tidy_binomial\(\)](#), [tidy_negative_binomial\(\)](#), [tidy_poisson\(\)](#), [tidy_zero_truncated_binomial\(\)](#), [tidy_zero_truncated_negative_binomial\(\)](#), [tidy_zero_truncated_poisson\(\)](#)

Other Hypergeometric: [util_hypergeometric_param_estimate\(\)](#), [util_hypergeometric_stats_tbl\(\)](#)

Examples

```
tidy_hypergeometric()
```

tidy_inverse_burr *Tidy Randomly Generated Inverse Burr Distribution Tibble*

Description

This function will generate n random points from an Inverse Burr distribution with a user provided, .shape1, .shape2, .scale, .rate, and number of random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the [stats::density\(\)](#) function.
- dy The y value from the [stats::density\(\)](#) function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_inverse_burr(  
  .n = 50,  
  .shape1 = 1,  
  .shape2 = 1,  
  .rate = 1,  
  .scale = 1/.rate,  
  .num_sims = 1,  
  .return_tibble = TRUE  
)
```

Arguments

.n	The number of randomly generated points you want.
.shape1	Must be strictly positive.
.shape2	Must be strictly positive.
.rate	An alternative way to specify the .scale.
.scale	Must be strictly positive.
.num_sims	The number of randomly generated simulations you want.
.return_tibble	A logical value indicating whether to return the result as a tibble. Default is TRUE.

Details

This function uses the underlying `actuar::rinvburr()`, and its underlying p, d, and q functions. For more information please see [actuar::rinvburr\(\)](#)

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://openacttexts.github.io/Loss-Data-Analytics/ChapSummaryDistributions.html>

Other Continuous Distribution: `tidy_beta()`, `tidy_burr()`, `tidy_cauchy()`, `tidy_chisquare()`, `tidy_exponential()`, `tidy_f()`, `tidy_gamma()`, `tidy_generalized_beta()`, `tidy_generalized_pareto()`, `tidy_geometric()`, `tidy_inverse_exponential()`, `tidy_inverse_gamma()`, `tidy_inverse_normal()`, `tidy_inverse_pareto()`, `tidy_inverse_weibull()`, `tidy_logistic()`, `tidy_lognormal()`, `tidy_normal()`, `tidy_paralogistic()`, `tidy_pareto1()`, `tidy_pareto()`, `tidy_triangular()`, `tidy_t()`, `tidy_uniform()`, `tidy_weibull()`, `tidy_zero_truncated_geometric()`

Other Burr: `tidy_burr()`, `util_burr_param_estimate()`, `util_burr_stats_tbl()`

Other Inverse Distribution: `tidy_inverse_exponential()`, `tidy_inverse_gamma()`, `tidy_inverse_normal()`, `tidy_inverse_pareto()`, `tidy_inverse_weibull()`

Examples

```
tidy_inverse_burr()
```

tidy_inverse_exponential

Tidy Randomly Generated Inverse Exponential Distribution Tibble

Description

This function will generate n random points from an inverse exponential distribution with a user provided, .rate or .scale and number of random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the `stats::density()` function.
- dy The y value from the `stats::density()` function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_inverse_exponential(  
  .n = 50,  
  .rate = 1,  
  .scale = 1/.rate,  
  .num_sims = 1,  
  .return_tibble = TRUE  
)
```

Arguments

.n	The number of randomly generated points you want.
.rate	An alternative way to specify the .scale
.scale	Must be strictly positive.
.num_sims	The number of randomly generated simulations you want.
.return_tibble	A logical value indicating whether to return the result as a tibble. Default is TRUE.

Details

This function uses the underlying `actuar::rinvexp()`, and its underlying p, d, and q functions. For more information please see [actuar::rinvexp\(\)](#)

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://openacttexts.github.io/Loss-Data-Analytics/ChapSummaryDistributions.html>

Other Continuous Distribution: [tidy_beta\(\)](#), [tidy_burr\(\)](#), [tidy_cauchy\(\)](#), [tidy_chisquare\(\)](#), [tidy_exponential\(\)](#), [tidy_f\(\)](#), [tidy_gamma\(\)](#), [tidy_generalized_beta\(\)](#), [tidy_generalized_pareto\(\)](#), [tidy_geometric\(\)](#), [tidy_inverse_burr\(\)](#), [tidy_inverse_gamma\(\)](#), [tidy_inverse_normal\(\)](#), [tidy_inverse_pareto\(\)](#), [tidy_inverse_weibull\(\)](#), [tidy_logistic\(\)](#), [tidy_lognormal\(\)](#), [tidy_normal\(\)](#), [tidy_paralogistic\(\)](#), [tidy_pareto1\(\)](#), [tidy_pareto\(\)](#), [tidy_triangular\(\)](#), [tidy_t\(\)](#), [tidy_uniform\(\)](#), [tidy_weibull\(\)](#), [tidy_zero_truncated_geometric\(\)](#)

Other Exponential: [tidy_exponential\(\)](#), [util_exponential_param_estimate\(\)](#), [util_exponential_stats_tbl\(\)](#)

Other Inverse Distribution: [tidy_inverse_burr\(\)](#), [tidy_inverse_gamma\(\)](#), [tidy_inverse_normal\(\)](#), [tidy_inverse_pareto\(\)](#), [tidy_inverse_weibull\(\)](#)

Examples

```
tidy_inverse_exponential()
```

tidy_inverse_gamma *Tidy Randomly Generated Inverse Gamma Distribution Tibble*

Description

This function will generate n random points from an inverse gamma distribution with a user provided, .shape, .rate, .scale, and number of random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the [stats::density\(\)](#) function.
- dy The y value from the [stats::density\(\)](#) function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_inverse_gamma(  
  .n = 50,  
  .shape = 1,  
  .rate = 1,  
  .scale = 1/.rate,  
  .num_sims = 1,  
  .return_tibble = TRUE  
)
```

Arguments

.n	The number of randomly generated points you want.
.shape	Must be strictly positive.
.rate	An alternative way to specify the .scale
.scale	Must be strictly positive.
.num_sims	The number of randomly generated simulations you want.
.return_tibble	A logical value indicating whether to return the result as a tibble. Default is TRUE.

Details

This function uses the underlying `actuar::rinvgamma()`, and its underlying p, d, and q functions. For more information please see [actuar::rinvgamma\(\)](#)

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://openacttexts.github.io/Loss-Data-Analytics/ChapSummaryDistributions.html>

Other Continuous Distribution: `tidy_beta()`, `tidy_burr()`, `tidy_cauchy()`, `tidy_chisquare()`, `tidy_exponential()`, `tidy_f()`, `tidy_gamma()`, `tidy_generalized_beta()`, `tidy_generalized_pareto()`, `tidy_geometric()`, `tidy_inverse_burr()`, `tidy_inverse_exponential()`, `tidy_inverse_normal()`, `tidy_inverse_pareto()`, `tidy_inverse_weibull()`, `tidy_logistic()`, `tidy_lognormal()`, `tidy_normal()`, `tidy_paralogistic()`, `tidy_pareto1()`, `tidy_pareto()`, `tidy_triangular()`, `tidy_t()`, `tidy_uniform()`, `tidy_weibull()`, `tidy_zero_truncated_geometric()`

Other Gamma: `tidy_gamma()`, `util_gamma_param_estimate()`, `util_gamma_stats_tbl()`

Other Inverse Distribution: `tidy_inverse_burr()`, `tidy_inverse_exponential()`, `tidy_inverse_normal()`, `tidy_inverse_pareto()`, `tidy_inverse_weibull()`

Examples

```
tidy_inverse_gamma()
```

tidy_inverse_normal *Tidy Randomly Generated Inverse Gaussian Distribution Tibble*

Description

This function will generate n random points from an Inverse Gaussian distribution with a user provided, .mean, .shape, .dispersionThe function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the `stats::density()` function.
- dy The y value from the `stats::density()` function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_inverse_normal(
  .n = 50,
  .mean = 1,
  .shape = 1,
  .dispersion = 1/.shape,
  .num_sims = 1,
  .return_tibble = TRUE
)
```

Arguments

.n	The number of randomly generated points you want.
.mean	Must be strictly positive.
.shape	Must be strictly positive.
.dispersion	An alternative way to specify the .shape.
.num_sims	The number of randomly generated simulations you want.
.return_tibble	A logical value indicating whether to return the result as a tibble. Default is TRUE.

Details

This function uses the underlying `actuar::rinvgauss()`. For more information please see [rinvgauss\(\)](#)

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Continuous Distribution: [tidy_beta\(\)](#), [tidy_burr\(\)](#), [tidy_cauchy\(\)](#), [tidy_chisquare\(\)](#), [tidy_exponential\(\)](#), [tidy_f\(\)](#), [tidy_gamma\(\)](#), [tidy_generalized_beta\(\)](#), [tidy_generalized_pareto\(\)](#), [tidy_geometric\(\)](#), [tidy_inverse_burr\(\)](#), [tidy_inverse_exponential\(\)](#), [tidy_inverse_gamma\(\)](#), [tidy_inverse_pareto\(\)](#), [tidy_inverse_weibull\(\)](#), [tidy_logistic\(\)](#), [tidy_lognormal\(\)](#), [tidy_normal\(\)](#), [tidy_paralogistic\(\)](#), [tidy_pareto1\(\)](#), [tidy_pareto\(\)](#), [tidy_triangular\(\)](#), [tidy_t\(\)](#), [tidy_uniform\(\)](#), [tidy_weibull\(\)](#), [tidy_zero_truncated_geometric\(\)](#)
 Other Gaussian: [tidy_normal\(\)](#), [util_normal_param_estimate\(\)](#), [util_normal_stats_tbl\(\)](#)
 Other Inverse Distribution: [tidy_inverse_burr\(\)](#), [tidy_inverse_exponential\(\)](#), [tidy_inverse_gamma\(\)](#), [tidy_inverse_pareto\(\)](#), [tidy_inverse_weibull\(\)](#)

Examples

```
tidy_inverse_normal()
```

`tidy_inverse_pareto` *Tidy Randomly Generated Inverse Pareto Distribution Tibble*

Description

This function will generate n random points from an inverse pareto distribution with a user provided, .shape, .scale, and number of random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the `stats::density()` function.
- dy The y value from the `stats::density()` function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_inverse_pareto(
  .n = 50,
  .shape = 1,
  .scale = 1,
  .num_sims = 1,
  .return_tibble = TRUE
)
```

Arguments

.n	The number of randomly generated points you want.
.shape	Must be positive.
.scale	Must be positive.
.num_sims	The number of randomly generated simulations you want.
.return_tibble	A logical value indicating whether to return the result as a tibble. Default is TRUE.

Details

This function uses the underlying `actuar::rinvpareto()`, and its underlying p, d, and q functions. For more information please see [actuar::rinvpareto\(\)](#)

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://openacttexts.github.io/Loss-Data-Analytics/ChapSummaryDistributions.html>

Other Continuous Distribution: `tidy_beta()`, `tidy_burr()`, `tidy_cauchy()`, `tidy_chisquare()`, `tidy_exponential()`, `tidy_f()`, `tidy_gamma()`, `tidy_generalized_beta()`, `tidy_generalized_pareto()`, `tidy_geometric()`, `tidy_inverse_burr()`, `tidy_inverse_exponential()`, `tidy_inverse_gamma()`, `tidy_inverse_normal()`, `tidy_inverse_weibull()`, `tidy_logistic()`, `tidy_lognormal()`, `tidy_normal()`, `tidy_paralogistic()`, `tidy_pareto1()`, `tidy_pareto()`, `tidy_triangular()`, `tidy_t()`, `tidy_uniform()`, `tidy_weibull()`, `tidy_zero_truncated_geometric()`

Other Pareto: `tidy_generalized_pareto()`, `tidy_pareto1()`, `tidy_pareto()`, `util_pareto_param_estimate()`, `util_pareto_stats_tbl()`

Other Inverse Distribution: `tidy_inverse_burr()`, `tidy_inverse_exponential()`, `tidy_inverse_gamma()`, `tidy_inverse_normal()`, `tidy_inverse_weibull()`

Examples

```
tidy_inverse_pareto()
```

tidy_inverse_weibull *Tidy Randomly Generated Inverse Weibull Distribution Tibble*

Description

This function will generate `n` random points from a weibull distribution with a user provided, `.shape`, `.scale`, `.rate`, and number of random simulations to be produced. The function returns a tibble with the simulation number column the `x` column which corresponds to the `n` randomly generated points, the `d_`, `p_` and `q_` data points as well.

The data is returned un-grouped.

The columns that are output are:

- `sim_number` The current simulation number.
- `x` The current value of `n` for the current simulation.
- `y` The randomly generated data point.
- `dx` The `x` value from the `stats::density()` function.
- `dy` The `y` value from the `stats::density()` function.
- `p` The values from the resulting `p_` function of the distribution family.
- `q` The values from the resulting `q_` function of the distribution family.

Usage

```
tidy_inverse_weibull(
  .n = 50,
  .shape = 1,
  .rate = 1,
  .scale = 1/.rate,
  .num_sims = 1,
  .return_tibble = TRUE
)
```

Arguments

<code>.n</code>	The number of randomly generated points you want.
<code>.shape</code>	Must be strictly positive.
<code>.rate</code>	An alternative way to specify the <code>.scale</code> .
<code>.scale</code>	Must be strictly positive.
<code>.num_sims</code>	The number of randomly generated simulations you want.
<code>.return_tibble</code>	A logical value indicating whether to return the result as a tibble. Default is <code>TRUE</code> .

Details

This function uses the underlying `actuar::rinvweibull()`, and its underlying `p`, `d`, and `q` functions. For more information please see [actuar::rinvweibull\(\)](#)

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://openacttexts.github.io/Loss-Data-Analytics/ChapSummaryDistributions.html>

Other Continuous Distribution: `tidy_beta()`, `tidy_burr()`, `tidy_cauchy()`, `tidy_chisquare()`, `tidy_exponential()`, `tidy_f()`, `tidy_gamma()`, `tidy_generalized_beta()`, `tidy_generalized_pareto()`, `tidy_geometric()`, `tidy_inverse_burr()`, `tidy_inverse_exponential()`, `tidy_inverse_gamma()`, `tidy_inverse_normal()`, `tidy_inverse_pareto()`, `tidy_logistic()`, `tidy_lognormal()`, `tidy_normal()`, `tidy_paralogistic()`, `tidy_pareto1()`, `tidy_pareto()`, `tidy_triangular()`, `tidy_t()`, `tidy_uniform()`, `tidy_weibull()`, `tidy_zero_truncated_geometric()`

Other Weibull: `tidy_weibull()`, `util_weibull_param_estimate()`, `util_weibull_stats_tbl()`

Other Inverse Distribution: `tidy_inverse_burr()`, `tidy_inverse_exponential()`, `tidy_inverse_gamma()`, `tidy_inverse_normal()`, `tidy_inverse_pareto()`

Examples

```
tidy_inverse_weibull()
```

`tidy_kurtosis_vec` *Compute Kurtosis of a Vector*

Description

This function takes in a vector as it's input and will return the kurtosis of that vector. The length of this vector must be at least four numbers. The kurtosis explains the sharpness of the peak of a distribution of data.

$$((1/n) * \text{sum}(x - \mu)^4) / (((1/n) * \text{sum}(x - \mu)^2)^2)$$

Usage

```
tidy_kurtosis_vec(.x)
```

Arguments

.x	A numeric vector of length four or more.
----	--

Details

A function to return the kurtosis of a vector.

Value

The kurtosis of a vector

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://en.wikipedia.org/wiki/Kurtosis>

Other Vector Function: `bootstrap_p_vec()`, `bootstrap_q_vec()`, `cgmean()`, `chmean()`, `ckurtosis()`, `cmean()`, `cmedian()`, `csd()`, `cskewness()`, `cvar()`, `tidy_scale_zero_one_vec()`, `tidy_skewness_vec()`

Other Statistic: `ci_hi()`, `ci_lo()`, `tidy_range_statistic()`, `tidy_skewness_vec()`, `tidy_stat_tbl()`

Other Vector Function: `bootstrap_p_vec()`, `bootstrap_q_vec()`, `cgmean()`, `chmean()`, `ckurtosis()`, `cmean()`, `cmedian()`, `csd()`, `cskewness()`, `cvar()`, `tidy_scale_zero_one_vec()`, `tidy_skewness_vec()`

Examples

```
tidy_kurtosis_vec(rnorm(100, 3, 2))
```

tidy_logistic

Tidy Randomly Generated Logistic Distribution Tibble

Description

This function will generate n random points from a logistic distribution with a user provided, .location, .scale, and number of random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the `stats::density()` function.
- dy The y value from the `stats::density()` function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_logistic(
  .n = 50,
  .location = 0,
  .scale = 1,
  .num_sims = 1,
  .return_tibble = TRUE
)
```

Arguments

.n	The number of randomly generated points you want.
.location	The location parameter
.scale	The scale parameter
.num_sims	The number of randomly generated simulations you want.
.return_tibble	A logical value indicating whether to return the result as a tibble. Default is TRUE.

Details

This function uses the underlying `stats::rlogis()`, and its underlying `p`, `d`, and `q` functions. For more information please see [stats::rlogis\(\)](#)

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

https://en.wikipedia.org/wiki/Logistic_distribution

Other Continuous Distribution: `tidy_beta()`, `tidy_burr()`, `tidy_cauchy()`, `tidy_chisquare()`, `tidy_exponential()`, `tidy_f()`, `tidy_gamma()`, `tidy_generalized_beta()`, `tidy_generalized_pareto()`, `tidy_geometric()`, `tidy_inverse_burr()`, `tidy_inverse_exponential()`, `tidy_inverse_gamma()`, `tidy_inverse_normal()`, `tidy_inverse_pareto()`, `tidy_inverse_weibull()`, `tidy_lognormal()`, `tidy_normal()`, `tidy_paralogistic()`, `tidy_pareto1()`, `tidy_pareto()`, `tidy_triangular()`, `tidy_t()`, `tidy_uniform()`, `tidy_weibull()`, `tidy_zero_truncated_geometric()`

Other Logistic: `tidy_paralogistic()`, `util_logistic_param_estimate()`, `util_logistic_stats_tbl()`

Examples

```
tidy_logistic()
```

tidy_lognormal *Tidy Randomly Generated Lognormal Distribution Tibble*

Description

This function will generate n random points from a lognormal distribution with a user provided, .meanlog, .sdlog, and number of random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the `stats::density()` function.
- dy The y value from the `stats::density()` function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_lognormal(  
  .n = 50,  
  .meanlog = 0,  
  .sdlog = 1,  
  .num_sims = 1,  
  .return_tibble = TRUE  
)
```

Arguments

- | | |
|----------------|---|
| .n | The number of randomly generated points you want. |
| .meanlog | Mean of the distribution on the log scale with default 0 |
| .sdlog | Standard deviation of the distribution on the log scale with default 1 |
| .num_sims | The number of randomly generated simulations you want. |
| .return_tibble | A logical value indicating whether to return the result as a tibble. Default is TRUE. |

Details

This function uses the underlying `stats::rlnorm()`, and its underlying p, d, and q functions. For more information please see `stats::rlnorm()`

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://www.itl.nist.gov/div898/handbook/eda/section3/eda3669.htm>

Other Continuous Distribution: `tidy_beta()`, `tidy_burr()`, `tidy_cauchy()`, `tidy_chisquare()`, `tidy_exponential()`, `tidy_f()`, `tidy_gamma()`, `tidy_generalized_beta()`, `tidy_generalized_pareto()`, `tidy_geometric()`, `tidy_inverse_burr()`, `tidy_inverse_exponential()`, `tidy_inverse_gamma()`, `tidy_inverse_normal()`, `tidy_inverse_pareto()`, `tidy_inverse_weibull()`, `tidy_logistic()`, `tidy_normal()`, `tidy_paralogistic()`, `tidy_pareto1()`, `tidy_pareto()`, `tidy_triangular()`, `tidy_t()`, `tidy_uniform()`, `tidy_weibull()`, `tidy_zero_truncated_geometric()`

Other Lognormal: `util_lognormal_param_estimate()`, `util_lognormal_stats_tbl()`

Examples

```
tidy_lognormal()
```

`tidy_mixture_density` *Tidy Mixture Data*

Description

Create mixture model data and resulting density and line plots.

Usage

```
tidy_mixture_density(...)
```

Arguments

... The random data you want to pass. Example `rnorm(50,0,1)` or something like
`tidy_normal(.mean = 5, .sd = 1)`

Details

This function allows you to make mixture model data. It allows you to produce density data and plots for data that is not strictly of one family or of one single type of distribution with a given set of parameters.

For example this function will allow you to mix say `tidy_normal(.mean = 0, .sd = 1)` and `tidy_normal(.mean = 5, .sd = 1)` or you can mix and match distributions.

The output is a list object with three components.

1. Data

- input_data (The random data passed)
- dist_tbl (A tibble of the passed random data)
- density_tbl (A tibble of the x and y data from stats::density())

1. Plots

- line_plot - Plots the dist_tbl
- dens_plot - Plots the density_tbl

1. Input Functions

- input_fns - A list of the functions and their parameters passed to the function itself

Value

A list object

Author(s)

Steven P. Sanderson II, MPH

Examples

```
output <- tidy_mixture_density(rnorm(100, 0, 1), tidy_normal(.mean = 5, .sd = 1))

output$data

output$plots

output$input_fns
```

tidy_multi_dist_autoplot
Automatic Plot of Multi Dist Data

Description

This is an auto plotting function that will take in a `tidy_` distribution function and a few arguments, one being the plot type, which is a quoted string of one of the following:

- density
- quantile
- probability
- qq

If the number of simulations exceeds 9 then the legend will not print. The plot subtitle is put together by the attributes of the table passed to the function.

Usage

```
tidy_multi_dist_autoplot(
  .data,
  .plot_type = "density",
  .line_size = 0.5,
  .geom_point = FALSE,
  .point_size = 1,
  .geom_rug = FALSE,
  .geom_smooth = FALSE,
  .geom_jitter = FALSE,
  .interactive = FALSE
)
```

Arguments

.data	The data passed in from a the function <code>tidy_multi_dist()</code>
.plot_type	This is a quoted string like 'density'
.line_size	The size param ggplot
.geom_point	A Boolean value of TRUE/FALSE, FALSE is the default. TRUE will return a plot with <code>ggplot2::ggeom_point()</code>
.point_size	The point size param for ggplot
.geom_rug	A Boolean value of TRUE/FALSE, FALSE is the default. TRUE will return the use of <code>ggplot2::geom_rug()</code>
.geom_smooth	A Boolean value of TRUE/FALSE, FALSE is the default. TRUE will return the use of <code>ggplot2::geom_smooth()</code> The aes parameter of group is set to FALSE. This ensures a single smoothing band returned with SE also set to FALSE. Color is set to 'black' and linetype is 'dashed'.
.geom_jitter	A Boolean value of TRUE/FALSE, FALSE is the default. TRUE will return the use of <code>ggplot2::geom_jitter()</code>
.interactive	A Boolean value of TRUE/FALSE, FALSE is the default. TRUE will return an interactive plotly plot.

Details

This function will spit out one of the following plots:

- density
- quantile
- probability
- qq

Value

A ggplot or a plotly plot.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Autoplot: [bootstrap_stat_plot\(\)](#), [tidy_autoplot\(\)](#), [tidy_combined_autoplot\(\)](#), [tidy_four_autoplot\(\)](#), [tidy_random_walk_autoplot\(\)](#)

Examples

```
tn <- tidy_multi_single_dist(  
  .tidy_dist = "tidy_normal",  
  .param_list = list(  
    .n = 100,  
    .mean = c(-2, 0, 2),  
    .sd = 1,  
    .num_sims = 5,  
    .return_tibble = TRUE  
  )  
)  
  
tn |>  
  tidy_multi_dist_autoplot()  
  
tn |>  
  tidy_multi_dist_autoplot(.plot_type = "qq")
```

tidy_multi_single_dist

Generate Multiple Tidy Distributions of a single type

Description

Generate multiple distributions of data from the same `tidy_` distribution function.

Usage

```
tidy_multi_single_dist(.tidy_dist = NULL, .param_list = list())
```

Arguments

- .tidy_dist The type of `tidy_` distribution that you want to run. You can only choose one.
- .param_list This must be a `list()` object of the parameters that you want to pass through to the TidyDensity `tidy_` distribution function.

Details

Generate multiple distributions of data from the same tidy_ distribution function. This allows you to simulate multiple distributions of the same family in order to view how shapes change with parameter changes. You can then visualize the differences however you choose.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Multiple Distribution: [tidy_combine_distributions\(\)](#)

Examples

```
tidy_multi_single_dist(
  .tidy_dist = "tidy_normal",
  .param_list = list(
    .n = 50,
    .mean = c(-1, 0, 1),
    .sd = 1,
    .num_sims = 3,
    .return_tibble = TRUE
  )
)
```

tidy_negative_binomial

Tidy Randomly Generated Negative Binomial Distribution Tibble

Description

This function will generate n random points from a negative binomial distribution with a user provided, .size, .prob, and number of random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.

- `dx` The `x` value from the `stats::density()` function.
- `dy` The `y` value from the `stats::density()` function.
- `p` The values from the resulting `p_` function of the distribution family.
- `q` The values from the resulting `q_` function of the distribution family.

Usage

```
tidy_negative_binomial(
  .n = 50,
  .size = 1,
  .prob = 0.1,
  .num_sims = 1,
  .return_tibble = TRUE
)
```

Arguments

<code>.n</code>	The number of randomly generated points you want.
<code>.size</code>	target for number of successful trials, or dispersion parameter (the shape parameter of the gamma mixing distribution). Must be strictly positive, need not be integer.
<code>.prob</code>	Probability of success on each trial where $0 < \text{prob} \leq 1$.
<code>.num_sims</code>	The number of randomly generated simulations you want.
<code>.return_tibble</code>	A logical value indicating whether to return the result as a tibble. Default is <code>TRUE</code> .

Details

This function uses the underlying `stats::rnbinom()`, and its underlying `p`, `d`, and `q` functions. For more information please see `stats::rnbinom()`

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://openacttexts.github.io/Loss-Data-Analytics/ChapSummaryDistributions.html>

Other Discrete Distribution: `tidy_bernoulli()`, `tidy_binomial()`, `tidy_hypergeometric()`, `tidy_poisson()`, `tidy_zero_truncated_binomial()`, `tidy_zero_truncated_negative_binomial()`, `tidy_zero_truncated_poisson()`

Other Binomial: `tidy_binomial()`, `tidy_zero_truncated_binomial()`, `tidy_zero_truncated_negative_binomial()`, `util_binomial_param_estimate()`, `util_binomial_stats_tbl()`, `util_negative_binomial_param_estimate()`

Examples

```
tidy_negative_binomial()
```

tidy_normal

Tidy Randomly Generated Gaussian Distribution Tibble

Description

This function will generate `n` random points from a Gaussian distribution with a user provided, `.mean`, `.sd` - standard deviation and number of random simulations to be produced. The function returns a tibble with the simulation number column the `x` column which corresponds to the `n` randomly generated points, the `dnorm`, `pnorm` and `qnorm` data points as well.

The data is returned un-grouped.

The columns that are output are:

- `sim_number` The current simulation number.
- `x` The current value of `n` for the current simulation.
- `y` The randomly generated data point.
- `dx` The `x` value from the `stats::density()` function.
- `dy` The `y` value from the `stats::density()` function.
- `p` The values from the resulting `p_` function of the distribution family.
- `q` The values from the resulting `q_` function of the distribution family.

Usage

```
tidy_normal(.n = 50, .mean = 0, .sd = 1, .num_sims = 1, .return_tibble = TRUE)
```

Arguments

<code>.n</code>	The number of randomly generated points you want.
<code>.mean</code>	The mean of the randomly generated data.
<code>.sd</code>	The standard deviation of the randomly generated data.
<code>.num_sims</code>	The number of randomly generated simulations you want.
<code>.return_tibble</code>	A logical value indicating whether to return the result as a tibble. Default is <code>TRUE</code> .

Details

This function uses the underlying `stats::rnorm()`, `stats::pnorm()`, and `stats::qnorm()` functions to generate data from the given parameters. For more information please see `stats::rnorm()`

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Continuous Distribution: [tidy_beta\(\)](#), [tidy_burr\(\)](#), [tidy_cauchy\(\)](#), [tidy_chisquare\(\)](#), [tidy_exponential\(\)](#), [tidy_f\(\)](#), [tidy_gamma\(\)](#), [tidy_generalized_beta\(\)](#), [tidy_generalized_pareto\(\)](#), [tidy_geometric\(\)](#), [tidy_inverse_burr\(\)](#), [tidy_inverse_exponential\(\)](#), [tidy_inverse_gamma\(\)](#), [tidy_inverse_normal\(\)](#), [tidy_inverse_pareto\(\)](#), [tidy_inverse_weibull\(\)](#), [tidy_logistic\(\)](#), [tidy_lognormal\(\)](#), [tidy_paralogistic\(\)](#), [tidy_pareto1\(\)](#), [tidy_pareto\(\)](#), [tidy_triangular\(\)](#), [tidy_t\(\)](#), [tidy_uniform\(\)](#), [tidy_weibull\(\)](#), [tidy_zero_truncated_geometric\(\)](#)

Other Gaussian: [tidy_inverse_normal\(\)](#), [util_normal_param_estimate\(\)](#), [util_normal_stats_tbl\(\)](#)

Examples

```
tidy_normal()
```

tidy_paralogistic *Tidy Randomly Generated Paralogistic Distribution Tibble*

Description

This function will generate n random points from a paralogistic distribution with a user provided, .shape, .rate, .scale and number of random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the [stats::density\(\)](#) function.
- dy The y value from the [stats::density\(\)](#) function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_paralogistic(
  .n = 50,
  .shape = 1,
  .rate = 1,
  .scale = 1/.rate,
  .num_sims = 1,
  .return_tibble = TRUE
)
```

Arguments

.n	The number of randomly generated points you want.
.shape	Must be strictly positive.
.rate	An alternative way to specify the .scale
.scale	Must be strictly positive.
.num_sims	The number of randomly generated simulations you want.
.return_tibble	A logical value indicating whether to return the result as a tibble. Default is TRUE.

Details

This function uses the underlying `actuar::rparalogis()`, and its underlying `p`, `d`, and `q` functions.
For more information please see [actuar::rparalogis\(\)](#)

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

https://en.wikipedia.org/wiki/Logistic_distribution

Other Continuous Distribution: `tidy_beta()`, `tidy_burr()`, `tidy_cauchy()`, `tidy_chisquare()`, `tidy_exponential()`, `tidy_f()`, `tidy_gamma()`, `tidy_generalized_beta()`, `tidy_generalized_pareto()`, `tidy_geometric()`, `tidy_inverse_burr()`, `tidy_inverse_exponential()`, `tidy_inverse_gamma()`, `tidy_inverse_normal()`, `tidy_inverse_pareto()`, `tidy_inverse_weibull()`, `tidy_logistic()`, `tidy_lognormal()`, `tidy_normal()`, `tidy_pareto1()`, `tidy_pareto()`, `tidy_triangular()`, `tidy_t()`, `tidy_uniform()`, `tidy_weibull()`, `tidy_zero_truncated_geometric()`

Other Logistic: `tidy_logistic()`, `util_logistic_param_estimate()`, `util_logistic_stats_tbl()`

Examples

```
tidy_paralogistic()
```

tidy_pareto*Tidy Randomly Generated Pareto Distribution Tibble*

Description

This function will generate n random points from a pareto distribution with a user provided, .shape, .scale, and number of random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the `stats::density()` function.
- dy The y value from the `stats::density()` function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_pareto(  
  .n = 50,  
  .shape = 10,  
  .scale = 0.1,  
  .num_sims = 1,  
  .return_tibble = TRUE  
)
```

Arguments

- | | |
|----------------|---|
| .n | The number of randomly generated points you want. |
| .shape | Must be positive. |
| .scale | Must be positive. |
| .num_sims | The number of randomly generated simulations you want. |
| .return_tibble | A logical value indicating whether to return the result as a tibble. Default is TRUE. |

Details

This function uses the underlying `actuar::rpareto()`, and its underlying p, d, and q functions. For more information please see [actuar::rpareto\(\)](#)

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://openacttexts.github.io/Loss-Data-Analytics/ChapSummaryDistributions.html>

Other Continuous Distribution: [tidy_beta\(\)](#), [tidy_burr\(\)](#), [tidy_cauchy\(\)](#), [tidy_chisquare\(\)](#), [tidy_exponential\(\)](#), [tidy_f\(\)](#), [tidy_gamma\(\)](#), [tidy_generalized_beta\(\)](#), [tidy_generalized_pareto\(\)](#), [tidy_geometric\(\)](#), [tidy_inverse_burr\(\)](#), [tidy_inverse_exponential\(\)](#), [tidy_inverse_gamma\(\)](#), [tidy_inverse_normal\(\)](#), [tidy_inverse_pareto\(\)](#), [tidy_inverse_weibull\(\)](#), [tidy_logistic\(\)](#), [tidy_lognormal\(\)](#), [tidy_normal\(\)](#), [tidy_paralogistic\(\)](#), [tidy_pareto1\(\)](#), [tidy_triangular\(\)](#), [tidy_t\(\)](#), [tidy_uniform\(\)](#), [tidy_weibull\(\)](#), [tidy_zero_truncated_geometric\(\)](#)

Other Pareto: [tidy_generalized_pareto\(\)](#), [tidy_inverse_pareto\(\)](#), [tidy_pareto1\(\)](#), [util_pareto_param_estimate\(\)](#), [util_pareto_stats_tbl\(\)](#)

Examples

`tidy_pareto()`

`tidy_pareto1`

Tidy Randomly Generated Pareto Single Parameter Distribution Tibble

Description

This function will generate n random points from a single parameter pareto distribution with a user provided, .shape, .min, and number of random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the `stats::density()` function.
- dy The y value from the `stats::density()` function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_pareto1(
  .n = 50,
  .shape = 1,
  .min = 1,
  .num_sims = 1,
  .return_tibble = TRUE
)
```

Arguments

.n	The number of randomly generated points you want.
.shape	Must be positive.
.min	The lower bound of the support of the distribution.
.num_sims	The number of randomly generated simulations you want.
.return_tibble	A logical value indicating whether to return the result as a tibble. Default is TRUE.

Details

This function uses the underlying `actuar::rpareto1()`, and its underlying p, d, and q functions. For more information please see [actuar::rpareto1\(\)](#)

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://openacttexts.github.io/Loss-Data-Analytics/ChapSummaryDistributions.html>

Other Continuous Distribution: `tidy_beta()`, `tidy_burr()`, `tidy_cauchy()`, `tidy_chisquare()`, `tidy_exponential()`, `tidy_f()`, `tidy_gamma()`, `tidy_generalized_beta()`, `tidy_generalized_pareto()`, `tidy_geometric()`, `tidy_inverse_burr()`, `tidy_inverse_exponential()`, `tidy_inverse_gamma()`, `tidy_inverse_normal()`, `tidy_inverse_pareto()`, `tidy_inverse_weibull()`, `tidy_logistic()`, `tidy_lognormal()`, `tidy_normal()`, `tidy_paralogistic()`, `tidy_pareto()`, `tidy_triangular()`, `tidy_t()`, `tidy_uniform()`, `tidy_weibull()`, `tidy_zero_truncated_geometric()`

Other Pareto: `tidy_generalized_pareto()`, `tidy_inverse_pareto()`, `tidy_pareto()`, `util_pareto_param_estimate`, `util_pareto_stats_tbl()`

Examples

```
tidy_pareto1()
```

tidy_poisson*Tidy Randomly Generated Poisson Distribution Tibble***Description**

This function will generate n random points from a Poisson distribution with a user provided, .lambda, and number of random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the `stats::density()` function.
- dy The y value from the `stats::density()` function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_poisson(.n = 50, .lambda = 1, .num_sims = 1, .return_tibble = TRUE)
```

Arguments

- | | |
|----------------|---|
| .n | The number of randomly generated points you want. |
| .lambda | A vector of non-negative means. |
| .num_sims | The number of randomly generated simulations you want. |
| .return_tibble | A logical value indicating whether to return the result as a tibble. Default is TRUE. |

Details

This function uses the underlying `stats::rpois()`, and its underlying p, d, and q functions. For more information please see [stats::rpois\(\)](#)

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://r-coder.com/poisson-distribution-r/>

https://en.wikipedia.org/wiki/Poisson_distribution

Other Poisson: [tidy_zero_truncated_poisson\(\)](#), [util_poisson_param_estimate\(\)](#), [util_poisson_stats_tbl\(\)](#)

Other Discrete Distribution: [tidy_bernoulli\(\)](#), [tidy_binomial\(\)](#), [tidy_hypergeometric\(\)](#),
[tidy_negative_binomial\(\)](#), [tidy_zero_truncated_binomial\(\)](#), [tidy_zero_truncated_negative_binomial\(\)](#),
[tidy_zero_truncated_poisson\(\)](#)

Examples

```
tidy_poisson()
```

tidy_random_walk

Tidy Random Walk

Description

Takes in the data from a `tidy_` distribution function and applies a random walk calculation of either `cum_prod` or `cum_sum` to `y`.

Usage

```
tidy_random_walk(
  .data,
  .initial_value = 0,
  .sample = FALSE,
  .replace = FALSE,
  .value_type = "cum_prod"
)
```

Arguments

- .data The data that is being passed from a `tidy_` distribution function.
- .initial_value The default is 0, this can be set to whatever you want.
- .sample This is a boolean value TRUE/FALSE. The default is FALSE. If set to TRUE then the `y` value from the `tidy_` distribution function is sampled.
- .replace This is a boolean value TRUE/FALSE. The default is FALSE. If set to TRUE AND `.sample` is set to TRUE then the `replace` parameter of the `sample` function will be set to TRUE.
- .value_type This can take one of three different values for now. These are the following:
 - "cum_prod" - This will take the cumprod of `y`
 - "cum_sum" - This will take the cumsum of `y`

Details

Monte Carlo simulations were first formally designed in the 1940's while developing nuclear weapons, and since have been heavily used in various fields to use randomness solve problems that are potentially deterministic in nature. In finance, Monte Carlo simulations can be a useful tool to give a sense of how assets with certain characteristics might behave in the future. While there are more complex and sophisticated financial forecasting methods such as ARIMA (Auto-Regressive Integrated Moving Average) and GARCH (Generalised Auto-Regressive Conditional Heteroskedasticity) which attempt to model not only the randomness but underlying macro factors such as seasonality and volatility clustering, Monte Carlo random walks work surprisingly well in illustrating market volatility as long as the results are not taken too seriously.

Value

An ungrouped tibble.

Author(s)

Steven P. Sanderson II, MPH

Examples

```
tidy_normal(.sd = .1, .num_sims = 25) %>%
  tidy_random_walk()
```

tidy_random_walk_autoplot

Automatic Plot of Random Walk Data

Description

This is an auto-plotting function that will take in a `tidy_` distribution function and a few arguments with regard to the output of the visualization.

If the number of simulations exceeds 9 then the legend will not print. The plot subtitle is put together by the attributes of the table passed to the function.

Usage

```
tidy_random_walk_autoplot(
  .data,
  .line_size = 0.5,
  .geom_rug = FALSE,
  .geom_smooth = FALSE,
  .interactive = FALSE
)
```

Arguments

.data	The data passed in from a tidy_distribution function like tidy_normal()
.line_size	The size param ggplot
.geom_rug	A Boolean value of TRUE/FALSE, FALSE is the default. TRUE will return the use of ggplot2::geom_rug()
.geom_smooth	A Boolean value of TRUE/FALSE, FALSE is the default. TRUE will return the use of ggplot2::geom_smooth() The aes parameter of group is set to FALSE. This ensures a single smoothing band returned with SE also set to FALSE. Color is set to 'black' and linetype is 'dashed'.
.interactive	A Boolean value of TRUE/FALSE, FALSE is the default. TRUE will return an interactive plotly plot.

Details

This function will produce a simple random walk plot from a tidy_ distribution function.

Value

A ggplot or a plotly plot.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Autoplot: [bootstrap_stat_plot\(\)](#), [tidy_autoplot\(\)](#), [tidy_combined_autoplot\(\)](#), [tidy_four_autoplot\(\)](#), [tidy_multi_dist_autoplot\(\)](#)

Examples

```
tidy_normal(.sd = .1, .num_sims = 5) |>
  tidy_random_walk(.value_type = "cum_sum") |>
  tidy_random_walk_autoplot()

tidy_normal(.sd = .1, .num_sims = 20) |>
  tidy_random_walk(.value_type = "cum_sum", .sample = TRUE, .replace = TRUE) |>
  tidy_random_walk_autoplot()
```

tidy_range_statistic *Get the range statistic*

Description

Takes in a numeric vector and returns back the range of that vector

Usage

```
tidy_range_statistic(.x)
```

Arguments

.x	A numeric vector
----	------------------

Details

Takes in a numeric vector and returns the range of that vector using the `diff` and `range` functions.

Value

A single number, the range statistic

Author(s)

Steven P. Sandeson II, MPH

See Also

Other Statistic: [ci_hi\(\)](#), [ci_lo\(\)](#), [tidy_kurtosis_vec\(\)](#), [tidy_skewness_vec\(\)](#), [tidy_stat_tbl\(\)](#)

Examples

```
tidy_range_statistic(seq(1:10))
```

tidy_scale_zero_one_vec*Vector Function Scale to Zero and One***Description**

Takes a numeric vector and will return a vector that has been scaled from $[0, 1]$

Usage

```
tidy_scale_zero_one_vec(.x)
```

Arguments

.x	A numeric vector to be scaled from $[0, 1]$ inclusive.
----	--

Details

Takes a numeric vector and will return a vector that has been scaled from $[0, 1]$ The input vector must be numeric. The computation is fairly straightforward. This may be helpful when trying to compare the distributions of data where a distribution like beta which requires data to be between 0 and 1

$$y[h] = (x - \min(x)) / (\max(x) - \min(x))$$

Value

A numeric vector

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Vector Function: [bootstrap_p_vec\(\)](#), [bootstrap_q_vec\(\)](#), [cgmean\(\)](#), [chmean\(\)](#), [ckurtosis\(\)](#), [cmean\(\)](#), [cmedian\(\)](#), [csd\(\)](#), [cskewness\(\)](#), [cvar\(\)](#), [tidy_kurtosis_vec\(\)](#), [tidy_skewness_vec\(\)](#)

Examples

```
vec_1 <- rnorm(100, 2, 1)
vec_2 <- tidy_scale_zero_one_vec(vec_1)

dens_1 <- density(vec_1)
dens_2 <- density(vec_2)
max_x <- max(dens_1$x, dens_2$x)
max_y <- max(dens_1$y, dens_2$y)
plot(dens_1,
```

```

asp = max_y / max_x, main = "Density vec_1 (Red) and vec_2 (Blue)",
col = "red", xlab = "", ylab = "Density of Vec 1 and Vec 2"
)
lines(dens_2, col = "blue")

```

tidy_skewness_vec *Compute Skewness of a Vector*

Description

This function takes in a vector as it's input and will return the skewness of that vector. The length of this vector must be at least four numbers. The skewness explains the 'tailedness' of the distribution of data.

$$((1/n) * \sum(x - \mu)^3) / (((1/n) * \sum(x - \mu)^2)^{3/2})$$

Usage

```
tidy_skewness_vec(.x)
```

Arguments

.x A numeric vector of length four or more.

Details

A function to return the skewness of a vector.

Value

The skewness of a vector

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://en.wikipedia.org/wiki/Skewness>

Other Statistic: [ci_hi\(\)](#), [ci_lo\(\)](#), [tidy_kurtosis_vec\(\)](#), [tidy_range_statistic\(\)](#), [tidy_stat_tbl\(\)](#)

Other Vector Function: [bootstrap_p_vec\(\)](#), [bootstrap_q_vec\(\)](#), [cgmean\(\)](#), [chmean\(\)](#), [ckurtosis\(\)](#), [cmean\(\)](#), [cmedian\(\)](#), [csd\(\)](#), [cskewness\(\)](#), [cvar\(\)](#), [tidy_kurtosis_vec\(\)](#), [tidy_scale_zero_one_vec\(\)](#)

Examples

```
tidy_skewness_vec(rnorm(100, 3, 2))
```

tidy_stat_tbl *Tidy Stats of Tidy Distribution*

Description

A function to return the stat function values of a given tidy_ distribution output.

Usage

```
tidy_stat_tbl(  
  .data,  
  .x = y,  
  .fns,  
  .return_type = "vector",  
  .use_data_table = FALSE,  
  ...  
)
```

Arguments

.data	The input data coming from a tidy_ distribution function.
.x	The default is y but can be one of the other columns from the input data.
.fns	The default is IQR, but this can be any stat function like quantile or median etc.
.return_type	The default is "vector" which returns an sapply object.
.use_data_table	The default is FALSE, TRUE will use data.table under the hood and still return a tibble. If this argument is set to TRUE then the .return_type parameter will be ignored.
...	Addition function arguments to be supplied to the parameters of .fns

Details

A function to return the value(s) of a given tidy_ distribution function output and chosen column from it. This function will only work with tidy_ distribution functions.

There are currently three different output types for this function. These are:

- "vector" - which gives an sapply() output
- "list" - which gives an lapply() output, and
- "tibble" - which returns a tibble in long format.

Currently you can pass any stat function that performs an operation on a vector input. This means you can pass things like IQR, quantile and their associated arguments in the ... portion of the function.

This function also by default will rename the value column of the `tibble` to the name of the function. This function will also give the column name of `sim_number` for the `tibble` output with the corresponding simulation numbers as the values.

For the `sapply` and `lapply` outputs the column names will also give the simulation number information by making column names like `sim_number_1` etc.

There is an option of `.use_data_table` which can greatly enhance the speed of the calculations performed if used while still returning a `tibble`. The calculations are performed after turning the input data into a `data.table` object, performing the necessary calculation and then converting back to a `tibble` object.

Value

A return of object of either `sapply` `lapply` or `tibble` based upon user input.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Statistic: [ci_hi\(\)](#), [ci_lo\(\)](#), [tidy_kurtosis_vec\(\)](#), [tidy_range_statistic\(\)](#), [tidy_skewness_vec\(\)](#)

Examples

```
tn <- tidy_normal(.num_sims = 3)

p <- c(0.025, 0.25, 0.5, 0.75, 0.95)

tidy_stat_tbl(tn, y, quantile, "vector", probs = p, na.rm = TRUE)
tidy_stat_tbl(tn, y, quantile, "list", probs = p)
tidy_stat_tbl(tn, y, quantile, "tibble", probs = p)
tidy_stat_tbl(tn, y, quantile, .use_data_table = TRUE, probs = p, na.rm = TRUE)
```

Description

This function will generate `n` random points from a `rt` distribution with a user provided, `df`, `ncp`, and number of random simulations to be produced. The function returns a `tibble` with the simulation number column the `x` column which corresponds to the `n` randomly generated points, the `d_`, `p_` and `q_` data points as well.

The data is returned un-grouped.

The columns that are output are:

- `sim_number` The current simulation number.

- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the `stats::density()` function.
- dy The y value from the `stats::density()` function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_t(.n = 50, .df = 1, .ncp = 0, .num_sims = 1, .return_tibble = TRUE)
```

Arguments

.n	The number of randomly generated points you want.
.df	Degrees of freedom, Inf is allowed.
.ncp	Non-centrality parameter.
.num_sims	The number of randomly generated simulations you want.
.return_tibble	A logical value indicating whether to return the result as a tibble. Default is TRUE.

Details

This function uses the underlying `stats::rt()`, and its underlying p, d, and q functions. For more information please see `stats::rt()`

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://www.itl.nist.gov/div898/handbook/eda/section3/eda3664.htm>

Other Continuous Distribution: `tidy_beta()`, `tidy_burr()`, `tidy_cauchy()`, `tidy_chisquare()`, `tidy_exponential()`, `tidy_f()`, `tidy_gamma()`, `tidy_generalized_beta()`, `tidy_generalized_pareto()`, `tidy_geometric()`, `tidy_inverse_burr()`, `tidy_inverse_exponential()`, `tidy_inverse_gamma()`, `tidy_inverse_normal()`, `tidy_inverse_pareto()`, `tidy_inverse_weibull()`, `tidy_logistic()`, `tidy_lognormal()`, `tidy_normal()`, `tidy_paralogistic()`, `tidy_pareto1()`, `tidy_pareto()`, `tidy_triangular()`, `tidy_uniform()`, `tidy_weibull()`, `tidy_zero_truncated_geometric()`

Other T Distribution: `util_t_stats_tbl()`

Examples

```
tidy_t()
```

tidy_triangular *Generate Tidy Data from Triangular Distribution*

Description

This function generates tidy data from the triangular distribution.

Usage

```
tidy_triangular(
  .n = 50,
  .min = 0,
  .max = 1,
  .mode = 1/2,
  .num_sims = 1,
  .return_tibble = TRUE
)
```

Arguments

.n	The number of x values for each simulation.
.min	The minimum value of the triangular distribution.
.max	The maximum value of the triangular distribution.
.mode	The mode (peak) value of the triangular distribution.
.num_sims	The number of simulations to perform.
.return_tibble	A logical value indicating whether to return the result as a tibble. Default is TRUE.

Details

The function takes parameters for the triangular distribution (minimum, maximum, mode), the number of x values (n), the number of simulations (num_sims), and an option to return the result as a tibble (return_tibble). It performs various checks on the input parameters to ensure validity. The result is a data frame or tibble with tidy data for further analysis.

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Continuous Distribution: [tidy_beta\(\)](#), [tidy_burr\(\)](#), [tidy_cauchy\(\)](#), [tidy_chisquare\(\)](#), [tidy_exponential\(\)](#), [tidy_f\(\)](#), [tidy_gamma\(\)](#), [tidy_generalized_beta\(\)](#), [tidy_generalized_pareto\(\)](#), [tidy_geometric\(\)](#), [tidy_inverse_burr\(\)](#), [tidy_inverse_exponential\(\)](#), [tidy_inverse_gamma\(\)](#), [tidy_inverse_normal\(\)](#), [tidy_inverse_pareto\(\)](#), [tidy_inverse_weibull\(\)](#), [tidy_logistic\(\)](#), [tidy_lognormal\(\)](#), [tidy_normal\(\)](#), [tidy_paralogistic\(\)](#), [tidy_pareto1\(\)](#), [tidy_pareto\(\)](#), [tidy_t\(\)](#), [tidy_uniform\(\)](#), [tidy_weibull\(\)](#), [tidy_zero_truncated_geometric\(\)](#)

Other Triangular: [util_triangular_param_estimate\(\)](#), [util_triangular_stats_tbl\(\)](#)

Examples

```
tidy_triangular(.return_tibble = TRUE)
```

`tidy_uniform`

Tidy Randomly Generated Uniform Distribution Tibble

Description

This function will generate n random points from a uniform distribution with a user provided, .min and .max values, and number of random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the [stats::density\(\)](#) function.
- dy The y value from the [stats::density\(\)](#) function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_uniform(.n = 50, .min = 0, .max = 1, .num_sims = 1, .return_tibble = TRUE)
```

Arguments

.n	The number of randomly generated points you want.
.min	A lower limit of the distribution.
.max	An upper limit of the distribution
.num_sims	The number of randomly generated simulations you want.
.return_tibble	A logical value indicating whether to return the result as a tibble. Default is TRUE.

Details

This function uses the underlying `stats::runif()`, and its underlying p, d, and q functions. For more information please see [stats::runif\(\)](#)

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://www.itl.nist.gov/div898/handbook/eda/section3/eda3662.htm>

Other Continuous Distribution: `tidy_beta()`, `tidy_burr()`, `tidy_cauchy()`, `tidy_chisquare()`, `tidy_exponential()`, `tidy_f()`, `tidy_gamma()`, `tidy_generalized_beta()`, `tidy_generalized_pareto()`, `tidy_geometric()`, `tidy_inverse_burr()`, `tidy_inverse_exponential()`, `tidy_inverse_gamma()`, `tidy_inverse_normal()`, `tidy_inverse_pareto()`, `tidy_inverse_weibull()`, `tidy_logistic()`, `tidy_lognormal()`, `tidy_normal()`, `tidy_paralogistic()`, `tidy_pareto1()`, `tidy_pareto()`, `tidy_triangular()`, `tidy_t()`, `tidy_weibull()`, `tidy_zero_truncated_geometric()`

Other Uniform: `util_uniform_param_estimate()`, `util_uniform_stats_tbl()`

Examples

`tidy_uniform()`

`tidy_weibull`

Tidy Randomly Generated Weibull Distribution Tibble

Description

This function will generate n random points from a weibull distribution with a user provided, .shape, .scale, and number of random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the `stats::density()` function.
- dy The y value from the `stats::density()` function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_weibull(  
  .n = 50,  
  .shape = 1,  
  .scale = 1,  
  .num_sims = 1,  
  .return_tibble = TRUE  
)
```

Arguments

.n	The number of randomly generated points you want.
.shape	Shape parameter defaults to 0.
.scale	Scale parameter defaults to 1.
.num_sims	The number of randomly generated simulations you want.
.return_tibble	A logical value indicating whether to return the result as a tibble. Default is TRUE.

Details

This function uses the underlying `stats:::rweibull()`, and its underlying `p`, `d`, and `q` functions. For more information please see `stats:::rweibull()`

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://www.itl.nist.gov/div898/handbook/eda/section3/eda3669.htm>

Other Continuous Distribution: `tidy_beta()`, `tidy_burr()`, `tidy_cauchy()`, `tidy_chisquare()`, `tidy_exponential()`, `tidy_f()`, `tidy_gamma()`, `tidy_generalized_beta()`, `tidy_generalized_pareto()`, `tidy_geometric()`, `tidy_inverse_burr()`, `tidy_inverse_exponential()`, `tidy_inverse_gamma()`, `tidy_inverse_normal()`, `tidy_inverse_pareto()`, `tidy_inverse_weibull()`, `tidy_logistic()`, `tidy_lognormal()`, `tidy_normal()`, `tidy_paralogistic()`, `tidy_pareto1()`, `tidy_pareto()`, `tidy_triangular()`, `tidy_t()`, `tidy_uniform()`, `tidy_zero_truncated_geometric()`

Other Weibull: `tidy_inverse_weibull()`, `util_weibull_param_estimate()`, `util_weibull_stats_tbl()`

Examples

```
tidy_weibull()
```

tidy_zero_truncated_binomial*Tidy Randomly Generated Binomial Distribution Tibble***Description**

This function will generate n random points from a zero truncated binomial distribution with a user provided, .size, .prob, and number of random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the `stats::density()` function.
- dy The y value from the `stats::density()` function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_zero_truncated_binomial(
  .n = 50,
  .size = 1,
  .prob = 1,
  .num_sims = 1,
  .return_tibble = TRUE
)
```

Arguments

.n	The number of randomly generated points you want.
.size	Number of trials, zero or more.
.prob	Probability of success on each trial $0 \leq prob \leq 1$.
.num_sims	The number of randomly generated simulations you want.
.return_tibble	A logical value indicating whether to return the result as a tibble. Default is TRUE.

Details

This function uses the underlying `actuar::rztbinom()`, and its underlying p, d, and q functions. For more information please see [actuar::rztbinom\(\)](#)

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://openacttexts.github.io/Loss-Data-Analytics/ChapSummaryDistributions.html>

Other Discrete Distribution: `tidy_bernoulli()`, `tidy_binomial()`, `tidy_hypergeometric()`,
`tidy_negative_binomial()`, `tidy_poisson()`, `tidy_zero_truncated_negative_binomial()`,
`tidy_zero_truncated_poisson()`

Other Binomial: `tidy_binomial()`, `tidy_negative_binomial()`, `tidy_zero_truncated_negative_binomial()`,
`util_binomial_param_estimate()`, `util_binomial_stats_tbl()`, `util_negative_binomial_param_estimate()`

Other Zero Truncated Distribution: `tidy_zero_truncated_geometric()`, `tidy_zero_truncated_poisson()`

Examples

```
tidy_zero_truncated_binomial()
```

`tidy_zero_truncated_geometric`

Tidy Randomly Generated Zero Truncated Geometric Distribution Tibble

Description

This function will generate n random points from a zero truncated Geometric distribution with a user provided, .prob, and number of random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the `stats::density()` function.
- dy The y value from the `stats::density()` function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_zero_truncated_geometric(
  .n = 50,
  .prob = 1,
  .num_sims = 1,
  .return_tibble = TRUE
)
```

Arguments

.n	The number of randomly generated points you want.
.prob	A probability of success in each trial $0 < \text{prob} \leq 1$.
.num_sims	The number of randomly generated simulations you want.
.return_tibble	A logical value indicating whether to return the result as a tibble. Default is TRUE.

Details

This function uses the underlying `actuar::rztgeom()`, and its underlying p, d, and q functions. For more information please see [actuar::rztgeom\(\)](#)

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://openacttexts.github.io/Loss-Data-Analytics/ChapSummaryDistributions.html>

Other Geometric: [tidy_geometric\(\)](#), [util_geometric_param_estimate\(\)](#), [util_geometric_stats_tbl\(\)](#)

Other Continuous Distribution: [tidy_beta\(\)](#), [tidy_burr\(\)](#), [tidy_cauchy\(\)](#), [tidy_chisquare\(\)](#), [tidy_exponential\(\)](#), [tidy_f\(\)](#), [tidy_gamma\(\)](#), [tidy_generalized_beta\(\)](#), [tidy_generalized_pareto\(\)](#), [tidy_geometric\(\)](#), [tidy_inverse_burr\(\)](#), [tidy_inverse_exponential\(\)](#), [tidy_inverse_gamma\(\)](#), [tidy_inverse_normal\(\)](#), [tidy_inverse_pareto\(\)](#), [tidy_inverse_weibull\(\)](#), [tidy_logistic\(\)](#), [tidy_lognormal\(\)](#), [tidy_normal\(\)](#), [tidy_paralogistic\(\)](#), [tidy_pareto1\(\)](#), [tidy_pareto\(\)](#), [tidy_triangular\(\)](#), [tidy_t\(\)](#), [tidy_uniform\(\)](#), [tidy_weibull\(\)](#)

Other Zero Truncated Distribution: [tidy_zero_truncated_binomial\(\)](#), [tidy_zero_truncated_poisson\(\)](#)

Examples

```
tidy_zero_truncated_geometric()
```

tidy_zero_truncated_negative_binomial*Tidy Randomly Generated Binomial Distribution Tibble*

Description

This function will generate n random points from a zero truncated binomial distribution with a user provided, .size, .prob, and number of random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the `stats::density()` function.
- dy The y value from the `stats::density()` function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_zero_truncated_negative_binomial(
  .n = 50,
  .size = 0,
  .prob = 1,
  .num_sims = 1,
  .return_tibble = TRUE
)
```

Arguments

.n	The number of randomly generated points you want.
.size	Number of trials, zero or more.
.prob	Probability of success on each trial $0 \leq prob \leq 1$.
.num_sims	The number of randomly generated simulations you want.
.return_tibble	A logical value indicating whether to return the result as a tibble. Default is TRUE.

Details

This function uses the underlying `actuar::rztnbinom()`, and its underlying p, d, and q functions. For more information please see [actuar::rztnbinom\(\)](#)

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://openacttexts.github.io/Loss-Data-Analytics/ChapSummaryDistributions.html>

Other Discrete Distribution: `tidy_bernoulli()`, `tidy_binomial()`, `tidy_hypergeometric()`,
`tidy_negative_binomial()`, `tidy_poisson()`, `tidy_zero_truncated_binomial()`, `tidy_zero_truncated_poisson()`

Other Binomial: `tidy_binomial()`, `tidy_negative_binomial()`, `tidy_zero_truncated_binomial()`,
`util_binomial_param_estimate()`, `util_binomial_stats_tbl()`, `util_negative_binomial_param_estimate()`

Examples

```
tidy_zero_truncated_negative_binomial()
```

tidy_zero_truncated_poisson

Tidy Randomly Generated Zero Truncated Poisson Distribution Tibble

Description

This function will generate n random points from a Zero Truncated Poisson distribution with a user provided, .lambda, and number of random simulations to be produced. The function returns a tibble with the simulation number column the x column which corresponds to the n randomly generated points, the d_, p_ and q_ data points as well.

The data is returned un-grouped.

The columns that are output are:

- sim_number The current simulation number.
- x The current value of n for the current simulation.
- y The randomly generated data point.
- dx The x value from the `stats::density()` function.
- dy The y value from the `stats::density()` function.
- p The values from the resulting p_ function of the distribution family.
- q The values from the resulting q_ function of the distribution family.

Usage

```
tidy_zero_truncated_poisson(  
  .n = 50,  
  .lambda = 1,  
  .num_sims = 1,  
  .return_tibble = TRUE  
)
```

Arguments

.n	The number of randomly generated points you want.
.lambda	A vector of non-negative means.
.num_sims	The number of randomly generated simulations you want.
.return_tibble	A logical value indicating whether to return the result as a tibble. Default is TRUE.

Details

This function uses the underlying `actuar::rztpois()`, and its underlying p, d, and q functions. For more information please see [actuar::rztpois\(\)](#)

Value

A tibble of randomly generated data.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://openacttexts.github.io/Loss-Data-Analytics/ChapSummaryDistributions.html>

Other Poisson: [tidy_poisson\(\)](#), [util_poisson_param_estimate\(\)](#), [util_poisson_stats_tbl\(\)](#)

Other Zero Truncated Distribution: [tidy_zero_truncated_binomial\(\)](#), [tidy_zero_truncated_geometric\(\)](#)

Other Discrete Distribution: [tidy_bernoulli\(\)](#), [tidy_binomial\(\)](#), [tidy_hypergeometric\(\)](#), [tidy_negative_binomial\(\)](#), [tidy_poisson\(\)](#), [tidy_zero_truncated_binomial\(\)](#), [tidy_zero_truncated_negative\(\)](#)

Examples

```
tidy_zero_truncated_poisson()
```

triangle_plot *Triangle Distribution PDF Plot*

Description

This function generates a probability density function (PDF) plot for the triangular distribution.

Usage

```
triangle_plot(.data, .interactive = FALSE)
```

Arguments

- | | |
|--------------|--|
| .data | Tidy data from the <code>tidy_triangular</code> function. |
| .interactive | A logical value indicating whether to return an interactive plot using <code>plotly</code> . Default is FALSE. |

Details

The function checks if the input data is a data frame or tibble, and if it comes from the `tidy_triangular` function. It then extracts necessary attributes for the plot and creates a PDF plot using `ggplot2`. The plot includes data points and segments to represent the triangular distribution.

Value

The function returns a `ggplot2` object representing the probability density function plot for the triangular distribution.

Author(s)

Steven P. Sanderson II, MPH

Examples

```
# Example: Generating a PDF plot for the triangular distribution
data <- tidy_triangular(.n = 50, .min = 0, .max = 1, .mode = 1/2, .num_sims = 1,
.return_tibble = TRUE)
triangle_plot(data)
```

util_bernoulli_param_estimate
Estimate Bernoulli Parameters

Description

This function will attempt to estimate the Bernoulli prob parameter given some vector of values .x. The function will return a list output by default, and if the parameter .auto_gen_empirical is set to TRUE then the empirical data given to the parameter .x will be run through the tidy_empirical() function and combined with the estimated Bernoulli data.

Usage

```
util_bernoulli_param_estimate(.x, .auto_gen_empirical = TRUE)
```

Arguments

- .x The vector of data to be passed to the function. Must be non-negative integers.
.auto_gen_empirical
This is a boolean value of TRUE/FALSE with default set to TRUE. This will automatically create the tidy_empirical() output for the .x parameter and use the tidy_combine_distributions(). The user can then plot out the data using \$combined_data_tbl from the function output.

Details

This function will see if the given vector .x is a numeric vector. It will attempt to estimate the prob parameter of a Bernoulli distribution.

Value

A tibble/list

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Parameter Estimation: [util_beta_param_estimate\(\)](#), [util_binomial_param_estimate\(\)](#),
[util_burr_param_estimate\(\)](#), [util_cauchy_param_estimate\(\)](#), [util_exponential_param_estimate\(\)](#),
[util_gamma_param_estimate\(\)](#), [util_geometric_param_estimate\(\)](#), [util_hypergeometric_param_estimate\(\)](#),
[util_logistic_param_estimate\(\)](#), [util_lognormal_param_estimate\(\)](#), [util_negative_binomial_param_estimate\(\)](#),
[util_normal_param_estimate\(\)](#), [util_pareto_param_estimate\(\)](#), [util_poisson_param_estimate\(\)](#),
[util_triangular_param_estimate\(\)](#), [util_uniform_param_estimate\(\)](#), [util_weibull_param_estimate\(\)](#)

Other Bernoulli: [tidy_bernoulli\(\)](#), [util_bernoulli_stats_tbl\(\)](#)

Examples

```
library(dplyr)
library(ggplot2)

tb <- tidy_bernoulli(.prob = .1) |> pull(y)
output <- util_bernoulli_param_estimate(tb)

output$parameter_tbl

output$combined_data_tbl |>
  tidy_combined_autoplot()
```

util_bernoulli_stats_tbl
Distribution Statistics

Description

Returns distribution statistics in a tibble.

Usage

```
util_bernoulli_stats_tbl(.data)
```

Arguments

.data The data being passed from a `tidy_` distribution function.

Details

This function will take in a tibble and returns the statistics of the given type of `tidy_` distribution. It is required that data be passed from a `tidy_` distribution function.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Bernoulli: [tidy_bernoulli\(\)](#), [util_bernoulli_param_estimate\(\)](#)
 Other Distribution Statistics: [util_beta_stats_tbl\(\)](#), [util_binomial_stats_tbl\(\)](#), [util_burr_stats_tbl\(\)](#),
[util_cauchy_stats_tbl\(\)](#), [util_chisquare_stats_tbl\(\)](#), [util_exponential_stats_tbl\(\)](#),
[util_f_stats_tbl\(\)](#), [util_gamma_stats_tbl\(\)](#), [util_geometric_stats_tbl\(\)](#), [util_hypergeometric_stats_tbl\(\)](#),
[util_logistic_stats_tbl\(\)](#), [util_lognormal_stats_tbl\(\)](#), [util_negative_binomial_stats_tbl\(\)](#),
[util_normal_stats_tbl\(\)](#), [util_pareto_stats_tbl\(\)](#), [util_poisson_stats_tbl\(\)](#), [util_t_stats_tbl\(\)](#),
[util_triangular_stats_tbl\(\)](#), [util_uniform_stats_tbl\(\)](#), [util_weibull_stats_tbl\(\)](#)

Examples

```
library(dplyr)

tidy_bernoulli() |>
  util_bernoulli_stats_tbl() |>
  glimpse()
```

util_beta_param_estimate

Estimate Beta Parameters

Description

This function will automatically scale the data from 0 to 1 if it is not already. This means you can pass a vector like `mtcars$mpg` and not worry about it.

The function will return a list output by default, and if the parameter `.auto_gen_empirical` is set to TRUE then the empirical data given to the parameter `.x` will be run through the `tidy_empirical()` function and combined with the estimated beta data.

Three different methods of shape parameters are supplied:

- Bayes
- NIST mme
- EnvStats mme, see [EnvStats::ebeta\(\)](#)

Usage

```
util_beta_param_estimate(.x, .auto_gen_empirical = TRUE)
```

Arguments

<code>.x</code>	The vector of data to be passed to the function. Must be numeric, and all values must be $0 \leq x \leq 1$
<code>.auto_gen_empirical</code>	This is a boolean value of TRUE/FALSE with default set to TRUE. This will automatically create the <code>tidy_empirical()</code> output for the <code>.x</code> parameter and use the <code>tidy_combine_distributions()</code> . The user can then plot out the data using <code>\$combined_data_tbl</code> from the function output.

Details

This function will attempt to estimate the beta shape1 and shape2 parameters given some vector of values.

Value

A tibble/list

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Parameter Estimation: [util_bernoulli_param_estimate\(\)](#), [util_binomial_param_estimate\(\)](#), [util_burr_param_estimate\(\)](#), [util_cauchy_param_estimate\(\)](#), [util_exponential_param_estimate\(\)](#), [util_gamma_param_estimate\(\)](#), [util_geometric_param_estimate\(\)](#), [util_hypergeometric_param_estimate\(\)](#), [util_logistic_param_estimate\(\)](#), [util_lognormal_param_estimate\(\)](#), [util_negative_binomial_param_estimate\(\)](#), [util_normal_param_estimate\(\)](#), [util_pareto_param_estimate\(\)](#), [util_poisson_param_estimate\(\)](#), [util_triangular_param_estimate\(\)](#), [util_uniform_param_estimate\(\)](#), [util_weibull_param_estimate\(\)](#)
 Other Beta: [tidy_beta\(\)](#), [tidy_generalized_beta\(\)](#), [util_beta_stats_tbl\(\)](#)

Examples

```
library(dplyr)
library(ggplot2)

x <- mtcars$mpg
output <- util_beta_param_estimate(x)

output$parameter_tbl

output$combined_data_tbl |>
  tidy_combined_autoplot()

tb <- rbeta(50, 2.5, 1.4)
util_beta_param_estimate(tb)$parameter_tbl
```

util_beta_stats_tbl *Distribution Statistics*

Description

Returns distribution statistics in a tibble.

Usage

```
util_beta_stats_tbl(.data)
```

Arguments

.data The data being passed from a tidy_ distribution function.

Details

This function will take in a tibble and returns the statistics of the given type of tidy_ distribution. It is required that data be passed from a tidy_ distribution function.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Beta: [tidy_beta\(\)](#), [tidy_generalized_beta\(\)](#), [util_beta_param_estimate\(\)](#)

Other Distribution Statistics: [util_bernoulli_stats_tbl\(\)](#), [util_binomial_stats_tbl\(\)](#), [util_burr_stats_tbl\(\)](#), [util_cauchy_stats_tbl\(\)](#), [util_chisquare_stats_tbl\(\)](#), [util_exponential_stats_tbl\(\)](#), [util_f_stats_tbl\(\)](#), [util_gamma_stats_tbl\(\)](#), [util_geometric_stats_tbl\(\)](#), [util_hypergeometric_stats_tbl\(\)](#), [util_logistic_stats_tbl\(\)](#), [util_lognormal_stats_tbl\(\)](#), [util_negative_binomial_stats_tbl\(\)](#), [util_normal_stats_tbl\(\)](#), [util_pareto_stats_tbl\(\)](#), [util_poisson_stats_tbl\(\)](#), [util_t_stats_tbl\(\)](#), [util_triangular_stats_tbl\(\)](#), [util_uniform_stats_tbl\(\)](#), [util_weibull_stats_tbl\(\)](#)

Examples

```
library(dplyr)

tidy_beta() |>
  util_beta_stats_tbl() |>
  glimpse()
```

util_binomial_param_estimate
Estimate Binomial Parameters

Description

This function will check to see if some given vector .x is either a numeric vector or a factor vector with at least two levels then it will cause an error and the function will abort. The function will return a list output by default, and if the parameter .auto_gen_empirical is set to TRUE then the empirical data given to the parameter .x will be run through the tidy_empirical() function and combined with the estimated binomial data.

Usage

```
util_binomial_param_estimate(.x, .size = NULL, .auto_gen_empirical = TRUE)
```

Arguments

- .x The vector of data to be passed to the function. Must be numeric, and all values must be $0 \leq x \leq 1$
- .size Number of trials, zero or more.
- .auto_gen_empirical This is a boolean value of TRUE/FALSE with default set to TRUE. This will automatically create the `tidy_empirical()` output for the `.x` parameter and use the `tidy_combine_distributions()`. The user can then plot out the data using `$combined_data_tbl` from the function output.

Details

This function will attempt to estimate the binomial p_hat and size parameters given some vector of values.

Value

A tibble/list

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Parameter Estimation: [util_bernoulli_param_estimate\(\)](#), [util_beta_param_estimate\(\)](#), [util_burr_param_estimate\(\)](#), [util_cauchy_param_estimate\(\)](#), [util_exponential_param_estimate\(\)](#), [util_gamma_param_estimate\(\)](#), [util_geometric_param_estimate\(\)](#), [util_hypergeometric_param_estimate\(\)](#), [util_logistic_param_estimate\(\)](#), [util_lognormal_param_estimate\(\)](#), [util_negative_binomial_param_estimate\(\)](#), [util_normal_param_estimate\(\)](#), [util_pareto_param_estimate\(\)](#), [util_poisson_param_estimate\(\)](#), [util_triangular_param_estimate\(\)](#), [util_uniform_param_estimate\(\)](#), [util_weibull_param_estimate\(\)](#)

Other Binomial: [tidy_binomial\(\)](#), [tidy_negative_binomial\(\)](#), [tidy_zero_truncated_binomial\(\)](#), [tidy_zero_truncated_negative_binomial\(\)](#), [util_binomial_stats_tbl\(\)](#), [util_negative_binomial_param_estimate\(\)](#)

Examples

```
library(dplyr)
library(ggplot2)

tb <- rbinom(50, 1, .1)
output <- util_binomial_param_estimate(tb)

output$parameter_tbl

output$combined_data_tbl |>
```

```
tidy_combined_autoplot()
```

util_binomial_stats_tbl

Distribution Statistics

Description

Returns distribution statistics in a tibble.

Usage

```
util_binomial_stats_tbl(.data)
```

Arguments

.data The data being passed from a `tidy_` distribution function.

Details

This function will take in a tibble and returns the statistics of the given type of `tidy_` distribution. It is required that data be passed from a `tidy_` distribution function.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Binomial: `tidy_binomial()`, `tidy_negative_binomial()`, `tidy_zero_truncated_binomial()`, `tidy_zero_truncated_negative_binomial()`, `util_binomial_param_estimate()`, `util_negative_binomial_param_estimate()`

Other Distribution Statistics: `util_bernoulli_stats_tbl()`, `util_beta_stats_tbl()`, `util_burr_stats_tbl()`, `util_cauchy_stats_tbl()`, `util_chisquare_stats_tbl()`, `util_exponential_stats_tbl()`, `util_f_stats_tbl()`, `util_gamma_stats_tbl()`, `util_geometric_stats_tbl()`, `util_hypergeometric_stats_tbl()`, `util_logistic_stats_tbl()`, `util_lognormal_stats_tbl()`, `util_negative_binomial_stats_tbl()`, `util_normal_stats_tbl()`, `util_pareto_stats_tbl()`, `util_poisson_stats_tbl()`, `util_t_stats_tbl()`, `util_triangular_stats_tbl()`, `util_uniform_stats_tbl()`, `util_weibull_stats_tbl()`

Examples

```
library(dplyr)

tidy_binomial() |>
  util_binomial_stats_tbl() |>
  glimpse()
```

util_burr_param_estimate
Estimate Burr Parameters

Description

This function will attempt to estimate the Burr prob parameter given some vector of values `.x`. The function will return a list output by default, and if the parameter `.auto_gen_empirical` is set to TRUE then the empirical data given to the parameter `.x` will be run through the `tidy_empirical()` function and combined with the estimated Burr data.

Usage

```
util_burr_param_estimate(.x, .auto_gen_empirical = TRUE)
```

Arguments

- `.x` The vector of data to be passed to the function. Must be non-negative integers.
- `.auto_gen_empirical` This is a boolean value of TRUE/FALSE with default set to TRUE. This will automatically create the `tidy_empirical()` output for the `.x` parameter and use the `tidy_combine_distributions()`. The user can then plot out the data using `$combined_data_tbl` from the function output.

Details

This function will see if the given vector `.x` is a numeric vector. It will attempt to estimate the prob parameter of a Burr distribution.

Value

A tibble/list

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Parameter Estimation: [util_bernoulli_param_estimate\(\)](#), [util_beta_param_estimate\(\)](#), [util_binomial_param_estimate\(\)](#), [util_cauchy_param_estimate\(\)](#), [util_exponential_param_estimate\(\)](#), [util_gamma_param_estimate\(\)](#), [util_geometric_param_estimate\(\)](#), [util_hypergeometric_param_estimate\(\)](#), [util_logistic_param_estimate\(\)](#), [util_lognormal_param_estimate\(\)](#), [util_negative_binomial_param_estimate\(\)](#), [util_normal_param_estimate\(\)](#), [util_pareto_param_estimate\(\)](#), [util_poisson_param_estimate\(\)](#), [util_triangular_param_estimate\(\)](#), [util_uniform_param_estimate\(\)](#), [util_weibull_param_estimate\(\)](#)

Other Burr: [tidy_burr\(\)](#), [tidy_inverse_burr\(\)](#), [util_burr_stats_tbl\(\)](#)

Examples

```
library(dplyr)
library(ggplot2)

tb <- tidy_burr(.shape1 = 1, .shape2 = 2, .rate = .3) |> pull(y)
output <- util_burr_param_estimate(tb)

output$parameter_tbl

output$combined_data_tbl |>
  tidy_combined_autoplot()
```

util_burr_stats_tbl *Distribution Statistics*

Description

Returns distribution statistics in a tibble.

Usage

```
util_burr_stats_tbl(.data)
```

Arguments

.data	The data being passed from a <code>tidy_</code> distribution function.
-------	--

Details

This function will take in a tibble and returns the statistics of the given type of `tidy_` distribution. It is required that data be passed from a `tidy_` distribution function.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Burr: [tidy_burr\(\)](#), [tidy_inverse_burr\(\)](#), [util_burr_param_estimate\(\)](#)

Other Distribution Statistics: [util_bernoulli_stats_tbl\(\)](#), [util_beta_stats_tbl\(\)](#), [util_binomial_stats_tbl\(\)](#), [util_cauchy_stats_tbl\(\)](#), [util_chisquare_stats_tbl\(\)](#), [util_exponential_stats_tbl\(\)](#), [util_f_stats_tbl\(\)](#), [util_gamma_stats_tbl\(\)](#), [util_geometric_stats_tbl\(\)](#), [util_hypergeometric_stats_tbl\(\)](#), [util_logistic_stats_tbl\(\)](#), [util_lognormal_stats_tbl\(\)](#), [util_negative_binomial_stats_tbl\(\)](#), [util_normal_stats_tbl\(\)](#), [util_pareto_stats_tbl\(\)](#), [util_poisson_stats_tbl\(\)](#), [util_t_stats_tbl\(\)](#), [util_triangular_stats_tbl\(\)](#), [util_uniform_stats_tbl\(\)](#), [util_weibull_stats_tbl\(\)](#)

Examples

```
library(dplyr)

tidy_burr() |>
  util_burr_stats_tbl() |>
  glimpse()
```

util_cauchy_param_estimate
Estimate Cauchy Parameters

Description

The function will return a list output by default, and if the parameter `.auto_gen_empirical` is set to TRUE then the empirical data given to the parameter `.x` will be run through the `tidy_empirical()` function and combined with the estimated cauchy data.

Usage

```
util_cauchy_param_estimate(.x, .auto_gen_empirical = TRUE)
```

Arguments

`.x` The vector of data to be passed to the function.

`.auto_gen_empirical`

This is a boolean value of TRUE/FALSE with default set to TRUE. This will automatically create the `tidy_empirical()` output for the `.x` parameter and use the `tidy_combine_distributions()`. The user can then plot out the data using `$combined_data_tbl` from the function output.

Details

This function will attempt to estimate the cauchy location and scale parameters given some vector of values.

Value

A tibble/list

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Parameter Estimation: [util_bernoulli_param_estimate\(\)](#), [util_beta_param_estimate\(\)](#), [util_binomial_param_estimate\(\)](#), [util_burr_param_estimate\(\)](#), [util_exponential_param_estimate\(\)](#), [util_gamma_param_estimate\(\)](#), [util_geometric_param_estimate\(\)](#), [util_hypergeometric_param_estimate\(\)](#), [util_logistic_param_estimate\(\)](#), [util_lognormal_param_estimate\(\)](#), [util_negative_binomial_param_estimate\(\)](#), [util_normal_param_estimate\(\)](#), [util_pareto_param_estimate\(\)](#), [util_poisson_param_estimate\(\)](#), [util_triangular_param_estimate\(\)](#), [util_uniform_param_estimate\(\)](#), [util_weibull_param_estimate\(\)](#)
Other Cauchy: [tidy_cauchy\(\)](#), [util_cauchy_stats_tbl\(\)](#)

Examples

```
library(dplyr)
library(ggplot2)

x <- tidy_cauchy(.location = 0, .scale = 1)$y
output <- util_cauchy_param_estimate(x)

output$parameter_tbl

output$combined_data_tbl |>
  tidy_combined_autoplot()
```

util_cauchy_stats_tbl *Distribution Statistics*

Description

Returns distribution statistics in a tibble.

Usage

```
util_cauchy_stats_tbl(.data)
```

Arguments

- .data The data being passed from a `tidy_` distribution function.

Details

This function will take in a tibble and returns the statistics of the given type of `tidy_` distribution. It is required that data be passed from a `tidy_` distribution function.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Cauchy: [tidy_cauchy\(\)](#), [util_cauchy_param_estimate\(\)](#)

Other Distribution Statistics: [util_bernoulli_stats_tbl\(\)](#), [util_beta_stats_tbl\(\)](#), [util_binomial_stats_tbl\(\)](#), [util_burr_stats_tbl\(\)](#), [util_chisquare_stats_tbl\(\)](#), [util_exponential_stats_tbl\(\)](#), [util_f_stats_tbl\(\)](#), [util_gamma_stats_tbl\(\)](#), [util_geometric_stats_tbl\(\)](#), [util_hypergeometric_stats_tbl\(\)](#), [util_logistic_stats_tbl\(\)](#), [util_lognormal_stats_tbl\(\)](#), [util_negative_binomial_stats_tbl\(\)](#), [util_normal_stats_tbl\(\)](#), [util_pareto_stats_tbl\(\)](#), [util_poisson_stats_tbl\(\)](#), [util_t_stats_tbl\(\)](#), [util_triangular_stats_tbl\(\)](#), [util_uniform_stats_tbl\(\)](#), [util_weibull_stats_tbl\(\)](#)

Examples

```
library(dplyr)

tidy_cauchy() |>
  util_cauchy_stats_tbl() |>
  glimpse()
```

util_chisquare_stats_tbl

Distribution Statistics

Description

Returns distribution statistics in a tibble.

Usage

```
util_chisquare_stats_tbl(.data)
```

Arguments

.data The data being passed from a tidy_ distribution function.

Details

This function will take in a tibble and returns the statistics of the given type of tidy_ distribution. It is required that data be passed from a tidy_ distribution function.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Chisquare: [tidy_chisquare\(\)](#)

Other Distribution Statistics: [util_bernoulli_stats_tbl\(\)](#), [util_beta_stats_tbl\(\)](#), [util_binomial_stats_tbl\(\)](#), [util_burr_stats_tbl\(\)](#), [util_cauchy_stats_tbl\(\)](#), [util_exponential_stats_tbl\(\)](#), [util_f_stats_tbl\(\)](#), [util_gamma_stats_tbl\(\)](#), [util_geometric_stats_tbl\(\)](#), [util_hypergeometric_stats_tbl\(\)](#), [util_logistic_stats_tbl\(\)](#), [util_lognormal_stats_tbl\(\)](#), [util_negative_binomial_stats_tbl\(\)](#), [util_normal_stats_tbl\(\)](#), [util_pareto_stats_tbl\(\)](#), [util_poisson_stats_tbl\(\)](#), [util_t_stats_tbl\(\)](#), [util_triangular_stats_tbl\(\)](#), [util_uniform_stats_tbl\(\)](#), [util_weibull_stats_tbl\(\)](#)

Examples

```
library(dplyr)

tidy_chisquare() |>
  util_chisquare_stats_tbl() |>
  glimpse()
```

util_exponential_param_estimate
Estimate Exponential Parameters

Description

This function will attempt to estimate the exponential rate parameter given some vector of values. The function will return a list output by default, and if the parameter .auto_gen_empirical is set to TRUE then the empirical data given to the parameter .x will be run through the tidy_empirical() function and combined with the estimated exponential data.

Usage

```
util_exponential_param_estimate(.x, .auto_gen_empirical = TRUE)
```

Arguments

- .x The vector of data to be passed to the function. Must be numeric.
- .auto_gen_empirical This is a boolean value of TRUE/FALSE with default set to TRUE. This will automatically create the `tidy_empirical()` output for the .x parameter and use the `tidy_combine_distributions()`. The user can then plot out the data using `$combined_data_tbl` from the function output.

Details

This function will see if the given vector .x is a numeric vector.

Value

A tibble/list

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Parameter Estimation: `util_bernoulli_param_estimate()`, `util_beta_param_estimate()`,
`util_binomial_param_estimate()`, `util_burr_param_estimate()`, `util_cauchy_param_estimate()`,
`util_gamma_param_estimate()`, `util_geometric_param_estimate()`, `util_hypergeometric_param_estimate()`,
`util_logistic_param_estimate()`, `util_lognormal_param_estimate()`, `util_negative_binomial_param_estimate()`,
`util_normal_param_estimate()`, `util_pareto_param_estimate()`, `util_poisson_param_estimate()`,
`util_triangular_param_estimate()`, `util_uniform_param_estimate()`, `util_weibull_param_estimate()`

Other Exponential: `tidy_exponential()`, `tidy_inverse_exponential()`, `util_exponential_stats_tbl()`

Examples

```
library(dplyr)
library(ggplot2)

te <- tidy_exponential(.rate = .1) |> pull(y)
output <- util_exponential_param_estimate(te)

output$parameter_tbl

output$combined_data_tbl |>
  tidy_combined_autoplot()
```

util_exponential_stats_tbl
Distribution Statistics

Description

Returns distribution statistics in a tibble.

Usage

```
util_exponential_stats_tbl(.data)
```

Arguments

.data The data being passed from a `tidy_` distribution function.

Details

This function will take in a tibble and returns the statistics of the given type of `tidy_` distribution.
It is required that data be passed from a `tidy_` distribution function.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Exponential: [tidy_exponential\(\)](#), [tidy_inverse_exponential\(\)](#), [util_exponential_param_estimate\(\)](#)
Other Distribution Statistics: [util_bernoulli_stats_tbl\(\)](#), [util_beta_stats_tbl\(\)](#), [util_binomial_stats_tbl\(\)](#),
[util_burr_stats_tbl\(\)](#), [util_cauchy_stats_tbl\(\)](#), [util_chisquare_stats_tbl\(\)](#), [util_f_stats_tbl\(\)](#),
[util_gamma_stats_tbl\(\)](#), [util_geometric_stats_tbl\(\)](#), [util_hypergeometric_stats_tbl\(\)](#),
[util_logistic_stats_tbl\(\)](#), [util_lognormal_stats_tbl\(\)](#), [util_negative_binomial_stats_tbl\(\)](#),
[util_normal_stats_tbl\(\)](#), [util_pareto_stats_tbl\(\)](#), [util_poisson_stats_tbl\(\)](#), [util_t_stats_tbl\(\)](#),
[util_triangular_stats_tbl\(\)](#), [util_uniform_stats_tbl\(\)](#), [util_weibull_stats_tbl\(\)](#)

Examples

```
library(dplyr)

tidy_exponential() |>
  util_exponential_stats_tbl() |>
  glimpse()
```

util_f_stats_tbl *Distribution Statistics*

Description

Returns distribution statistics in a tibble.

Usage

```
util_f_stats_tbl(.data)
```

Arguments

.data The data being passed from a `tidy_` distribution function.

Details

This function will take in a tibble and returns the statistics of the given type of `tidy_` distribution. It is required that data be passed from a `tidy_` distribution function.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other F Distribution: [tidy_f\(\)](#)

Other Distribution Statistics: [util_bernoulli_stats_tbl\(\)](#), [util_beta_stats_tbl\(\)](#), [util_binomial_stats_tbl\(\)](#), [util_burr_stats_tbl\(\)](#), [util_cauchy_stats_tbl\(\)](#), [util_chisquare_stats_tbl\(\)](#), [util_exponential_stats_tbl\(\)](#), [util_gamma_stats_tbl\(\)](#), [util_geometric_stats_tbl\(\)](#), [util_hypergeometric_stats_tbl\(\)](#), [util_logistic_stats_tbl\(\)](#), [util_lognormal_stats_tbl\(\)](#), [util_negative_binomial_stats_tbl\(\)](#), [util_normal_stats_tbl\(\)](#), [util_pareto_stats_tbl\(\)](#), [util_poisson_stats_tbl\(\)](#), [util_t_stats_tbl\(\)](#), [util_triangular_stats_tbl\(\)](#), [util_uniform_stats_tbl\(\)](#), [util_weibull_stats_tbl\(\)](#)

Examples

```
library(dplyr)

tidy_f() |>
  util_f_stats_tbl() |>
  glimpse()
```

util_gamma_param_estimate
Estimate Gamma Parameters

Description

This function will attempt to estimate the gamma shape and scale parameters given some vector of values. The function will return a list output by default, and if the parameter `.auto_gen_empirical` is set to TRUE then the empirical data given to the parameter `.x` will be run through the `tidy_empirical()` function and combined with the estimated gamma data.

Usage

```
util_gamma_param_estimate(.x, .auto_gen_empirical = TRUE)
```

Arguments

`.x` The vector of data to be passed to the function. Must be numeric.

`.auto_gen_empirical`

This is a boolean value of TRUE/FALSE with default set to TRUE. This will automatically create the `tidy_empirical()` output for the `.x` parameter and use the `tidy_combine_distributions()`. The user can then plot out the data using `$combined_data_tbl` from the function output.

Details

This function will see if the given vector `.x` is a numeric vector.

Value

A tibble/list

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Parameter Estimation: [util_bernoulli_param_estimate\(\)](#), [util_beta_param_estimate\(\)](#), [util_binomial_param_estimate\(\)](#), [util_burr_param_estimate\(\)](#), [util_cauchy_param_estimate\(\)](#), [util_exponential_param_estimate\(\)](#), [util_geometric_param_estimate\(\)](#), [util_hypergeometric_param_estimate\(\)](#), [util_logistic_param_estimate\(\)](#), [util_lognormal_param_estimate\(\)](#), [util_negative_binomial_param_estimate\(\)](#), [util_normal_param_estimate\(\)](#), [util_pareto_param_estimate\(\)](#), [util_poisson_param_estimate\(\)](#), [util_triangular_param_estimate\(\)](#), [util_uniform_param_estimate\(\)](#), [util_weibull_param_estimate\(\)](#)

Other Gamma: [tidy_gamma\(\)](#), [tidy_inverse_gamma\(\)](#), [util_gamma_stats_tbl\(\)](#)

Examples

```
library(dplyr)
library(ggplot2)

tg <- tidy_gamma(.shape = 1, .scale = .3) |> pull(y)
output <- util_gamma_param_estimate(tg)

output$parameter_tbl

output$combined_data_tbl |>
  tidy_combined_autoplot()
```

util_gamma_stats_tbl *Distribution Statistics*

Description

Returns distribution statistics in a tibble.

Usage

```
util_gamma_stats_tbl(.data)
```

Arguments

.data The data being passed from a `tidy_` distribution function.

Details

This function will take in a tibble and returns the statistics of the given type of `tidy_` distribution. It is required that data be passed from a `tidy_` distribution function.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Gamma: [tidy_gamma\(\)](#), [tidy_inverse_gamma\(\)](#), [util_gamma_param_estimate\(\)](#)

Other Distribution Statistics: [util_bernoulli_stats_tbl\(\)](#), [util_beta_stats_tbl\(\)](#), [util_binomial_stats_tbl\(\)](#), [util_burr_stats_tbl\(\)](#), [util_cauchy_stats_tbl\(\)](#), [util_chisquare_stats_tbl\(\)](#), [util_exponential_stats_tbl\(\)](#), [util_f_stats_tbl\(\)](#), [util_geometric_stats_tbl\(\)](#), [util_hypergeometric_stats_tbl\(\)](#), [util_logistic_stats_tbl\(\)](#), [util_lognormal_stats_tbl\(\)](#), [util_negative_binomial_stats_tbl\(\)](#), [util_normal_stats_tbl\(\)](#), [util_pareto_stats_tbl\(\)](#), [util_poisson_stats_tbl\(\)](#), [util_t_stats_tbl\(\)](#), [util_triangular_stats_tbl\(\)](#), [util_uniform_stats_tbl\(\)](#), [util_weibull_stats_tbl\(\)](#)

Examples

```
library(dplyr)

tidy_gamma() |>
  util_gamma_stats_tbl() |>
  glimpse()
```

util_geometric_param_estimate
Estimate Geometric Parameters

Description

This function will attempt to estimate the geometric prob parameter given some vector of values .x. The function will return a list output by default, and if the parameter .auto_gen_empirical is set to TRUE then the empirical data given to the parameter .x will be run through the `tidy_empirical()` function and combined with the estimated geometric data.

Usage

```
util_geometric_param_estimate(.x, .auto_gen_empirical = TRUE)
```

Arguments

- .x The vector of data to be passed to the function. Must be non-negative integers.
- .auto_gen_empirical This is a boolean value of TRUE/FALSE with default set to TRUE. This will automatically create the `tidy_empirical()` output for the .x parameter and use the `tidy_combine_distributions()`. The user can then plot out the data using \$combined_data_tbl from the function output.

Details

This function will see if the given vector .x is a numeric vector. It will attempt to estimate the prob parameter of a geometric distribution.

Value

A tibble/list

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Parameter Estimation: [util_bernoulli_param_estimate\(\)](#), [util_beta_param_estimate\(\)](#), [util_binomial_param_estimate\(\)](#), [util_burr_param_estimate\(\)](#), [util_cauchy_param_estimate\(\)](#), [util_exponential_param_estimate\(\)](#), [util_gamma_param_estimate\(\)](#), [util_hypergeometric_param_estimate\(\)](#), [util_logistic_param_estimate\(\)](#), [util_lognormal_param_estimate\(\)](#), [util_negative_binomial_param_estimate\(\)](#), [util_normal_param_estimate\(\)](#), [util_pareto_param_estimate\(\)](#), [util_poisson_param_estimate\(\)](#), [util_triangular_param_estimate\(\)](#), [util_uniform_param_estimate\(\)](#), [util_weibull_param_estimate\(\)](#)

Other Geometric: [tidy_geometric\(\)](#), [tidy_zero_truncated_geometric\(\)](#), [util_geometric_stats_tbl\(\)](#)

Examples

```
library(dplyr)
library(ggplot2)

tg <- tidy_geometric(.prob = .1) |> pull(y)
output <- util_geometric_param_estimate(tg)

output$parameter_tbl

output$combined_data_tbl |>
  tidy_combined_autoplot()
```

`util_geometric_stats_tbl`*Distribution Statistics***Description**

Returns distribution statistics in a tibble.

Usage

```
util_geometric_stats_tbl(.data)
```

Arguments

.data	The data being passed from a <code>tidy_</code> distribution function.
-------	--

Details

This function will take in a tibble and returns the statistics of the given type of `tidy_` distribution. It is required that data be passed from a `tidy_` distribution function.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Geometric: [tidy_geometric\(\)](#), [tidy_zero_truncated_geometric\(\)](#), [util_geometric_param_estimate\(\)](#)
Other Distribution Statistics: [util_bernoulli_stats_tbl\(\)](#), [util_beta_stats_tbl\(\)](#), [util_binomial_stats_tbl\(\)](#),
[util_burr_stats_tbl\(\)](#), [util_cauchy_stats_tbl\(\)](#), [util_chisquare_stats_tbl\(\)](#), [util_exponential_stats_tbl\(\)](#),
[util_f_stats_tbl\(\)](#), [util_gamma_stats_tbl\(\)](#), [util_hypergeometric_stats_tbl\(\)](#), [util_logistic_stats_tbl\(\)](#),
[util_lognormal_stats_tbl\(\)](#), [util_negative_binomial_stats_tbl\(\)](#), [util_normal_stats_tbl\(\)](#),
[util_pareto_stats_tbl\(\)](#), [util_poisson_stats_tbl\(\)](#), [util_t_stats_tbl\(\)](#), [util_triangular_stats_tbl\(\)](#),
[util_uniform_stats_tbl\(\)](#), [util_weibull_stats_tbl\(\)](#)

Examples

```
library(dplyr)

tidy_geometric() |>
  util_geometric_stats_tbl() |>
  glimpse()
```

util_hypergeometric_param_estimate
Estimate Hypergeometric Parameters

Description

This function will attempt to estimate the geometric prob parameter given some vector of values .x. Estimate m, the number of white balls in the urn, or m+n, the total number of balls in the urn, for a hypergeometric distribution.

Usage

```
util_hypergeometric_param_estimate(
  .x,
  .m = NULL,
  .total = NULL,
  .k,
  .auto_gen_empirical = TRUE
)
```

Arguments

.x	A non-negative integer indicating the number of white balls out of a sample of size .k drawn without replacement from the urn. You cannot have missing, undefined or infinite values.
.m	Non-negative integer indicating the number of white balls in the urn. You must supply .m or .total, but not both. You cannot have missing values.
.total	A positive integer indicating the total number of balls in the urn (i.e., m+n). You must supply .m or .total, but not both. You cannot have missing values.
.k	A positive integer indicating the number of balls drawn without replacement from the urn. You cannot have missing values.
.auto_gen_empirical	This is a boolean value of TRUE/FALSE with default set to TRUE. This will automatically create the <code>tidy_empirical()</code> output for the .x parameter and use the <code>tidy_combine_distributions()</code> . The user can then plot out the data using <code>\$combined_data_tbl</code> from the function output.

Details

This function will see if the given vector .x is a numeric integer. It will attempt to estimate the prob parameter of a geometric distribution. Missing (NA), undefined (NaN), and infinite (Inf, -Inf) values are not allowed. Let .x be an observation from a hypergeometric distribution with parameters .m = M, .n = N, and .k = K. In R nomenclature, .x represents the number of white balls drawn out of a sample of .k balls drawn without replacement from an urn containing .m white balls and .n black balls. The total number of balls in the urn is thus .m + .n. Denote the total number of balls by T = .m + .n

Value

A tibble/list

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Parameter Estimation: [util_bernoulli_param_estimate\(\)](#), [util_beta_param_estimate\(\)](#), [util_binomial_param_estimate\(\)](#), [util_burr_param_estimate\(\)](#), [util_cauchy_param_estimate\(\)](#), [util_exponential_param_estimate\(\)](#), [util_gamma_param_estimate\(\)](#), [util_geometric_param_estimate\(\)](#), [util_logistic_param_estimate\(\)](#), [util_lognormal_param_estimate\(\)](#), [util_negative_binomial_param_estimate\(\)](#), [util_normal_param_estimate\(\)](#), [util_pareto_param_estimate\(\)](#), [util_poisson_param_estimate\(\)](#), [util_triangular_param_estimate\(\)](#), [util_uniform_param_estimate\(\)](#), [util_weibull_param_estimate\(\)](#)

Other Hypergeometric: [tidy_hypergeometric\(\)](#), [util_hypergeometric_stats_tbl\(\)](#)

Examples

```
library(dplyr)
library(ggplot2)

th <- rhyper(10, 20, 30, 5)
output <- util_hypergeometric_param_estimate(th, .total = 50, .k = 5)

output$parameter_tbl

output$combined_data_tbl |>
  tidy_combined_autoplot()
```

util_hypergeometric_stats_tbl
Distribution Statistics

Description

Returns distribution statistics in a tibble.

Usage

```
util_hypergeometric_stats_tbl(.data)
```

Arguments

.data The data being passed from a `tidy_` distribution function.

Details

This function will take in a tibble and returns the statistics of the given type of `tidy_` distribution. It is required that data be passed from a `tidy_` distribution function.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Hypergeometric: [tidy_hypergeometric\(\)](#), [util_hypergeometric_param_estimate\(\)](#)

Other Distribution Statistics: [util_bernoulli_stats_tbl\(\)](#), [util_beta_stats_tbl\(\)](#), [util_binomial_stats_tbl\(\)](#), [util_burr_stats_tbl\(\)](#), [util_cauchy_stats_tbl\(\)](#), [util_chisquare_stats_tbl\(\)](#), [util_exponential_stats_tbl\(\)](#), [util_f_stats_tbl\(\)](#), [util_gamma_stats_tbl\(\)](#), [util_geometric_stats_tbl\(\)](#), [util_logistic_stats_tbl\(\)](#), [util_lognormal_stats_tbl\(\)](#), [util_negative_binomial_stats_tbl\(\)](#), [util_normal_stats_tbl\(\)](#), [util_pareto_stats_tbl\(\)](#), [util_poisson_stats_tbl\(\)](#), [util_t_stats_tbl\(\)](#), [util_triangular_stats_tbl\(\)](#), [util_uniform_stats_tbl\(\)](#), [util_weibull_stats_tbl\(\)](#)

Examples

```
library(dplyr)

tidy_hypergeometric() |>
  util_hypergeometric_stats_tbl() |>
  glimpse()
```

util_logistic_param_estimate

Estimate Logistic Parameters

Description

The function will return a list output by default, and if the parameter `.auto_gen_empirical` is set to TRUE then the empirical data given to the parameter `.x` will be run through the `tidy_empirical()` function and combined with the estimated logistic data.

Three different methods of shape parameters are supplied:

- MLE
- MME
- MMUE

Usage

```
util_logistic_param_estimate(.x, .auto_gen_empirical = TRUE)
```

Arguments

`.x` The vector of data to be passed to the function.

`.auto_gen_empirical`

This is a boolean value of TRUE/FALSE with default set to TRUE. This will automatically create the `tidy_empirical()` output for the `.x` parameter and use the `tidy_combine_distributions()`. The user can then plot out the data using `$combined_data_tbl` from the function output.

Details

This function will attempt to estimate the logistic location and scale parameters given some vector of values.

Value

A tibble/list

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Parameter Estimation: [util_bernoulli_param_estimate\(\)](#), [util_beta_param_estimate\(\)](#), [util_binomial_param_estimate\(\)](#), [util_burr_param_estimate\(\)](#), [util_cauchy_param_estimate\(\)](#), [util_exponential_param_estimate\(\)](#), [util_gamma_param_estimate\(\)](#), [util_geometric_param_estimate\(\)](#), [util_hypergeometric_param_estimate\(\)](#), [util_lognormal_param_estimate\(\)](#), [util_negative_binomial_param_estimate\(\)](#), [util_normal_param_estimate\(\)](#), [util_pareto_param_estimate\(\)](#), [util_poisson_param_estimate\(\)](#), [util_triangular_param_estimate\(\)](#), [util_uniform_param_estimate\(\)](#), [util_weibull_param_estimate\(\)](#)

Other Logistic: [tidy_logistic\(\)](#), [tidy_paralogistic\(\)](#), [util_logistic_stats_tbl\(\)](#)

Examples

```
library(dplyr)
library(ggplot2)

x <- mtcars$mpg
output <- util_logistic_param_estimate(x)

output$parameter_tbl

output$combined_data_tbl |>
  tidy_combined_autoplot()

t <- rlogis(50, 2.5, 1.4)
util_logistic_param_estimate(t)$parameter_tbl
```

util_logistic_stats_tbl

Distribution Statistics

Description

Returns distribution statistics in a tibble.

Usage

```
util_logistic_stats_tbl(.data)
```

Arguments

.data The data being passed from a `tidy_` distribution function.

Details

This function will take in a tibble and returns the statistics of the given type of `tidy_` distribution. It is required that data be passed from a `tidy_` distribution function.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Logistic: [tidy_logistic\(\)](#), [tidy_paralogistic\(\)](#), [util_logistic_param_estimate\(\)](#)

Other Distribution Statistics: [util_bernoulli_stats_tbl\(\)](#), [util_beta_stats_tbl\(\)](#), [util_binomial_stats_tbl\(\)](#), [util_burr_stats_tbl\(\)](#), [util_cauchy_stats_tbl\(\)](#), [util_chisquare_stats_tbl\(\)](#), [util_exponential_stats_tbl\(\)](#), [util_f_stats_tbl\(\)](#), [util_gamma_stats_tbl\(\)](#), [util_geometric_stats_tbl\(\)](#), [util_hypergeometric_stats_tbl\(\)](#), [util_lognormal_stats_tbl\(\)](#), [util_negative_binomial_stats_tbl\(\)](#), [util_normal_stats_tbl\(\)](#), [util_pareto_stats_tbl\(\)](#), [util_poisson_stats_tbl\(\)](#), [util_t_stats_tbl\(\)](#), [util_triangular_stats_tbl\(\)](#), [util_uniform_stats_tbl\(\)](#), [util_weibull_stats_tbl\(\)](#)

Examples

```
library(dplyr)

tidy_logistic() |>
  util_logistic_stats_tbl() |>
  glimpse()
```

Description

The function will return a list output by default, and if the parameter `.auto_gen_empirical` is set to TRUE then the empirical data given to the parameter `.x` will be run through the `tidy_empirical()` function and combined with the estimated lognormal data.

Three different methods of shape parameters are supplied:

- mme, see [EnvStats::elnorm\(\)](#)
- mle, see [EnvStats::elnorm\(\)](#)

Usage

```
util_lognormal_param_estimate(.x, .auto_gen_empirical = TRUE)
```

Arguments

<code>.x</code>	The vector of data to be passed to the function.
<code>.auto_gen_empirical</code>	This is a boolean value of TRUE/FALSE with default set to TRUE. This will automatically create the <code>tidy_empirical()</code> output for the <code>.x</code> parameter and use the <code>tidy_combine_distributions()</code> . The user can then plot out the data using <code>\$combined_data_tbl</code> from the function output.

Details

This function will attempt to estimate the lognormal meanlog and log sd parameters given some vector of values.

Value

A tibble/list

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Parameter Estimation: [util_bernoulli_param_estimate\(\)](#), [util_beta_param_estimate\(\)](#), [util_binomial_param_estimate\(\)](#), [util_burr_param_estimate\(\)](#), [util_cauchy_param_estimate\(\)](#), [util_exponential_param_estimate\(\)](#), [util_gamma_param_estimate\(\)](#), [util_geometric_param_estimate\(\)](#), [util_hypergeometric_param_estimate\(\)](#), [util_logistic_param_estimate\(\)](#), [util_negative_binomial_param_estimate\(\)](#), [util_normal_param_estimate\(\)](#), [util_pareto_param_estimate\(\)](#), [util_poisson_param_estimate\(\)](#), [util_triangular_param_estimate\(\)](#), [util_uniform_param_estimate\(\)](#), [util_weibull_param_estimate\(\)](#)

Other Lognormal: [tidy_lognormal\(\)](#), [util_lognormal_stats_tbl\(\)](#)

Examples

```
library(dplyr)
library(ggplot2)

x <- mtcars$mpg
output <- util_lognormal_param_estimate(x)

output$parameter_tbl

output$combined_data_tbl |>
  tidy_combined_autoplot()

tb <- tidy_lognormal(.meanlog = 2, .sdlog = 1) |> pull(y)
util_lognormal_param_estimate(tb)$parameter_tbl
```

util_lognormal_stats_tbl
Distribution Statistics

Description

Returns distribution statistics in a tibble.

Usage

```
util_lognormal_stats_tbl(.data)
```

Arguments

.data The data being passed from a `tidy_` distribution function.

Details

This function will take in a tibble and returns the statistics of the given type of `tidy_` distribution. It is required that data be passed from a `tidy_` distribution function.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Lognormal: [tidy_lognormal\(\)](#), [util_lognormal_param_estimate\(\)](#)

Other Distribution Statistics: [util_bernoulli_stats_tbl\(\)](#), [util_beta_stats_tbl\(\)](#), [util_binomial_stats_tbl\(\)](#), [util_burr_stats_tbl\(\)](#), [util_cauchy_stats_tbl\(\)](#), [util_chisquare_stats_tbl\(\)](#), [util_exponential_stats_tbl\(\)](#), [util_f_stats_tbl\(\)](#), [util_gamma_stats_tbl\(\)](#), [util_geometric_stats_tbl\(\)](#), [util_hypergeometric_stats_tbl\(\)](#), [util_logistic_stats_tbl\(\)](#), [util_negative_binomial_stats_tbl\(\)](#), [util_normal_stats_tbl\(\)](#), [util_pareto_stats_tbl\(\)](#), [util_poisson_stats_tbl\(\)](#), [util_t_stats_tbl\(\)](#), [util_triangular_stats_tbl\(\)](#), [util_uniform_stats_tbl\(\)](#), [util_weibull_stats_tbl\(\)](#)

Examples

```
library(dplyr)

tidy_lognormal() |>
  util_lognormal_stats_tbl() |>
  glimpse()
```

util_negative_binomial_param_estimate

Estimate Negative Binomial Parameters

Description

The function will return a list output by default, and if the parameter `.auto_gen_empirical` is set to TRUE then the empirical data given to the parameter `.x` will be run through the `tidy_empirical()` function and combined with the estimated negative binomial data.

Two different methods of shape parameters are supplied:

- MLE/MME
- MMUE

Usage

```
util_negative_binomial_param_estimate(.x, .size, .auto_gen_empirical = TRUE)
```

Arguments

<code>.x</code>	The vector of data to be passed to the function.
<code>.size</code>	The size parameter.
<code>.auto_gen_empirical</code>	This is a boolean value of TRUE/FALSE with default set to TRUE. This will automatically create the <code>tidy_empirical()</code> output for the <code>.x</code> parameter and use the <code>tidy_combine_distributions()</code> . The user can then plot out the data using <code>\$combined_data_tbl</code> from the function output.

Details

This function will attempt to estimate the negative binomial size and prob parameters given some vector of values.

Value

A tibble/list

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Parameter Estimation: [util_bernoulli_param_estimate\(\)](#), [util_beta_param_estimate\(\)](#), [util_binomial_param_estimate\(\)](#), [util_burr_param_estimate\(\)](#), [util_cauchy_param_estimate\(\)](#), [util_exponential_param_estimate\(\)](#), [util_gamma_param_estimate\(\)](#), [util_geometric_param_estimate\(\)](#), [util_hypergeometric_param_estimate\(\)](#), [util_logistic_param_estimate\(\)](#), [util_lognormal_param_estimate\(\)](#), [util_normal_param_estimate\(\)](#), [util_pareto_param_estimate\(\)](#), [util_poisson_param_estimate\(\)](#), [util_triangular_param_estimate\(\)](#), [util_uniform_param_estimate\(\)](#), [util_weibull_param_estimate\(\)](#)
 Other Binomial: [tidy_binomial\(\)](#), [tidy_negative_binomial\(\)](#), [tidy_zero_truncated_binomial\(\)](#), [tidy_zero_truncated_negative_binomial\(\)](#), [util_binomial_param_estimate\(\)](#), [util_binomial_stats_tbl\(\)](#)

Examples

```
library(dplyr)
library(ggplot2)

x <- as.integer(mtcars$mpg)
output <- util_negative_binomial_param_estimate(x, .size = 1)

output$parameter_tbl

output$combined_data_tbl |>
  tidy_combined_autoplot()

t <- rnbnom(50, 1, .1)
util_negative_binomial_param_estimate(t, .size = 1)$parameter_tbl
```

util_negative_binomial_stats_tbl
Distribution Statistics

Description

Returns distribution statistics in a tibble.

Usage

```
util_negative_binomial_stats_tbl(.data)
```

Arguments

.data The data being passed from a tidy_ distribution function.

Details

This function will take in a tibble and returns the statistics of the given type of tidy_ distribution. It is required that data be passed from a tidy_ distribution function.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Distribution Statistics: [util_bernoulli_stats_tbl\(\)](#), [util_beta_stats_tbl\(\)](#), [util_binomial_stats_tbl\(\)](#), [util_burr_stats_tbl\(\)](#), [util_cauchy_stats_tbl\(\)](#), [util_chisquare_stats_tbl\(\)](#), [util_exponential_stats_tbl\(\)](#), [util_f_stats_tbl\(\)](#), [util_gamma_stats_tbl\(\)](#), [util_geometric_stats_tbl\(\)](#), [util_hypergeometric_stats_tbl\(\)](#), [util_logistic_stats_tbl\(\)](#), [util_lognormal_stats_tbl\(\)](#), [util_normal_stats_tbl\(\)](#), [util_pareto_stats_tbl\(\)](#), [util_poisson_stats_tbl\(\)](#), [util_t_stats_tbl\(\)](#), [util_triangular_stats_tbl\(\)](#), [util_uniform_stats_tbl\(\)](#), [util_weibull_stats_tbl\(\)](#)

Examples

```
library(dplyr)

tidy_negative_binomial() |>
  util_negative_binomial_stats_tbl() |>
  glimpse()
```

Description

The function will return a list output by default, and if the parameter `.auto_gen_empirical` is set to TRUE then the empirical data given to the parameter `.x` will be run through the `tidy_empirical()` function and combined with the estimated normal data.

Three different methods of shape parameters are supplied:

- MLE/MME
- MVUE

Usage

```
util_normal_param_estimate(.x, .auto_gen_empirical = TRUE)
```

Arguments

<code>.x</code>	The vector of data to be passed to the function.
<code>.auto_gen_empirical</code>	This is a boolean value of TRUE/FALSE with default set to TRUE. This will automatically create the <code>tidy_empirical()</code> output for the <code>.x</code> parameter and use the <code>tidy_combine_distributions()</code> . The user can then plot out the data using <code>\$combined_data_tbl</code> from the function output.

Details

This function will attempt to estimate the normal gaussian mean and standard deviation parameters given some vector of values.

Value

A tibble/list

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Parameter Estimation: [util_bernoulli_param_estimate\(\)](#), [util_beta_param_estimate\(\)](#), [util_binomial_param_estimate\(\)](#), [util_burr_param_estimate\(\)](#), [util_cauchy_param_estimate\(\)](#), [util_exponential_param_estimate\(\)](#), [util_gamma_param_estimate\(\)](#), [util_geometric_param_estimate\(\)](#), [util_hypergeometric_param_estimate\(\)](#), [util_logistic_param_estimate\(\)](#), [util_lognormal_param_estimate\(\)](#), [util_negative_binomial_param_estimate\(\)](#), [util_pareto_param_estimate\(\)](#), [util_poisson_param_estimate\(\)](#), [util_triangular_param_estimate\(\)](#), [util_uniform_param_estimate\(\)](#), [util_weibull_param_estimate\(\)](#)

Other Gaussian: [tidy_inverse_normal\(\)](#), [tidy_normal\(\)](#), [util_normal_stats_tbl\(\)](#)

Examples

```
library(dplyr)
library(ggplot2)

x <- mtcars$mpg
output <- util_normal_param_estimate(x)

output$parameter_tbl

output$combined_data_tbl |>
  tidy_combined_autoplot()

t <- rnorm(50, 0, 1)
util_normal_param_estimate(t)$parameter_tbl
```

`util_normal_stats_tbl` *Distribution Statistics*

Description

Returns distribution statistics in a tibble.

Usage

```
util_normal_stats_tbl(.data)
```

Arguments

.data The data being passed from a `tidy_` distribution function.

Details

This function will take in a tibble and returns the statistics of the given type of `tidy_` distribution. It is required that data be passed from a `tidy_` distribution function.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Gaussian: `tidy_inverse_normal()`, `tidy_normal()`, `util_normal_param_estimate()`

Other Distribution Statistics: `util_bernoulli_stats_tbl()`, `util_beta_stats_tbl()`, `util_binomial_stats_tbl()`, `util_burr_stats_tbl()`, `util_cauchy_stats_tbl()`, `util_chisquare_stats_tbl()`, `util_exponential_stats_tbl()`, `util_f_stats_tbl()`, `util_gamma_stats_tbl()`, `util_geometric_stats_tbl()`, `util_hypergeometric_stats_tbl()`, `util_logistic_stats_tbl()`, `util_lognormal_stats_tbl()`, `util_negative_binomial_stats_tbl()`, `util_pareto_stats_tbl()`, `util_poisson_stats_tbl()`, `util_t_stats_tbl()`, `util_triangular_stats_tbl()`, `util_uniform_stats_tbl()`, `util_weibull_stats_tbl()`

Examples

```
library(dplyr)

tidy_normal() |>
  util_normal_stats_tbl() |>
  glimpse()
```

`util_pareto_param_estimate`

Estimate Pareto Parameters

Description

The function will return a list output by default, and if the parameter `.auto_gen_empirical` is set to TRUE then the empirical data given to the parameter `.x` will be run through the `tidy_empirical()` function and combined with the estimated pareto data.

Two different methods of shape parameters are supplied:

- LSE
- MLE

Usage

```
util_pareto_param_estimate(.x, .auto_gen_empirical = TRUE)
```

Arguments

`.x` The vector of data to be passed to the function.

`.auto_gen_empirical`

This is a boolean value of TRUE/FALSE with default set to TRUE. This will automatically create the `tidy_empirical()` output for the `.x` parameter and use the `tidy_combine_distributions()`. The user can then plot out the data using `$combined_data_tbl` from the function output.

Details

This function will attempt to estimate the pareto shape and scale parameters given some vector of values.

Value

A tibble/list

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Parameter Estimation: [util_bernoulli_param_estimate\(\)](#), [util_beta_param_estimate\(\)](#), [util_binomial_param_estimate\(\)](#), [util_burr_param_estimate\(\)](#), [util_cauchy_param_estimate\(\)](#), [util_exponential_param_estimate\(\)](#), [util_gamma_param_estimate\(\)](#), [util_geometric_param_estimate\(\)](#), [util_hypergeometric_param_estimate\(\)](#), [util_logistic_param_estimate\(\)](#), [util_lognormal_param_estimate\(\)](#), [util_negative_binomial_param_estimate\(\)](#), [util_normal_param_estimate\(\)](#), [util_poisson_param_estimate\(\)](#), [util_triangular_param_estimate\(\)](#), [util_uniform_param_estimate\(\)](#), [util_weibull_param_estimate\(\)](#)

Other Pareto: [tidy_generalized_pareto\(\)](#), [tidy_inverse_pareto\(\)](#), [tidy_pareto1\(\)](#), [tidy_pareto\(\)](#), [util_pareto_stats_tbl\(\)](#)

Examples

```
library(dplyr)
library(ggplot2)

x <- mtcars$mpg
output <- util_pareto_param_estimate(x)

output$parameter_tbl

output$combined_data_tbl |>
  tidy_combined_autoplot()

t <- tidy_pareto(50, 1, 1) |> pull(y)
util_pareto_param_estimate(t)$parameter_tbl
```

util_pareto_stats_tbl *Distribution Statistics*

Description

Returns distribution statistics in a tibble.

Usage

```
util_pareto_stats_tbl(.data)
```

Arguments

.data The data being passed from a `tidy_` distribution function.

Details

This function will take in a tibble and returns the statistics of the given type of `tidy_` distribution.
It is required that data be passed from a `tidy_` distribution function.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Pareto: [tidy_generalized_pareto\(\)](#), [tidy_inverse_pareto\(\)](#), [tidy_pareto1\(\)](#), [tidy_pareto\(\)](#), [util_pareto_param_estimate\(\)](#)

Other Distribution Statistics: [util_bernoulli_stats_tbl\(\)](#), [util_beta_stats_tbl\(\)](#), [util_binomial_stats_tbl\(\)](#), [util_burr_stats_tbl\(\)](#), [util_cauchy_stats_tbl\(\)](#), [util_chisquare_stats_tbl\(\)](#), [util_exponential_stats_tbl\(\)](#), [util_f_stats_tbl\(\)](#), [util_gamma_stats_tbl\(\)](#), [util_geometric_stats_tbl\(\)](#), [util_hypergeometric_stats_tbl\(\)](#), [util_logistic_stats_tbl\(\)](#), [util_lognormal_stats_tbl\(\)](#), [util_negative_binomial_stats_tbl\(\)](#), [util_normal_stats_tbl\(\)](#), [util_poisson_stats_tbl\(\)](#), [util_t_stats_tbl\(\)](#), [util_triangular_stats_tbl\(\)](#), [util_uniform_stats_tbl\(\)](#), [util_weibull_stats_tbl\(\)](#)

Examples

```
library(dplyr)

tidy_pareto() |>
  util_pareto_stats_tbl() |>
  glimpse()
```

util_poisson_param_estimate
Estimate Poisson Parameters

Description

The function will return a list output by default, and if the parameter `.auto_gen_empirical` is set to TRUE then the empirical data given to the parameter `.x` will be run through the `tidy_empirical()` function and combined with the estimated poisson data.

Usage

```
util_poisson_param_estimate(.x, .auto_gen_empirical = TRUE)
```

Arguments

`.x` The vector of data to be passed to the function.

`.auto_gen_empirical`

This is a boolean value of TRUE/FALSE with default set to TRUE. This will automatically create the `tidy_empirical()` output for the `.x` parameter and use the `tidy_combine_distributions()`. The user can then plot out the data using `$combined_data_tbl` from the function output.

Details

This function will attempt to estimate the pareto lambda parameter given some vector of values.

Value

A tibble/list

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Parameter Estimation: [util_bernoulli_param_estimate\(\)](#), [util_beta_param_estimate\(\)](#),
[util_binomial_param_estimate\(\)](#), [util_burr_param_estimate\(\)](#), [util_cauchy_param_estimate\(\)](#),
[util_exponential_param_estimate\(\)](#), [util_gamma_param_estimate\(\)](#), [util_geometric_param_estimate\(\)](#),
[util_hypergeometric_param_estimate\(\)](#), [util_logistic_param_estimate\(\)](#), [util_lognormal_param_estimate\(\)](#),
[util_negative_binomial_param_estimate\(\)](#), [util_normal_param_estimate\(\)](#), [util_pareto_param_estimate\(\)](#),
[util_triangular_param_estimate\(\)](#), [util_uniform_param_estimate\(\)](#), [util_weibull_param_estimate\(\)](#)

Other Poisson: [tidy_poisson\(\)](#), [tidy_zero_truncated_poisson\(\)](#), [util_poisson_stats_tbl\(\)](#)

Examples

```
library(dplyr)
library(ggplot2)

x <- as.integer(mtcars$mpg)
output <- util_poisson_param_estimate(x)

output$parameter_tbl

output$combined_data_tbl |>
  tidy_combined_autoplot()

t <- rpois(50, 5)
util_poisson_param_estimate(t)$parameter_tbl
```

util_poisson_stats_tbl

Distribution Statistics

Description

Returns distribution statistics in a tibble.

Usage

```
util_poisson_stats_tbl(.data)
```

Arguments

.data The data being passed from a `tidy_` distribution function.

Details

This function will take in a tibble and returns the statistics of the given type of `tidy_` distribution. It is required that data be passed from a `tidy_` distribution function.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Poisson: [tidy_poisson\(\)](#), [tidy_zero_truncated_poisson\(\)](#), [util_poisson_param_estimate\(\)](#)
 Other Distribution Statistics: [util_bernoulli_stats_tbl\(\)](#), [util_beta_stats_tbl\(\)](#), [util_binomial_stats_tbl\(\)](#),
[util_burr_stats_tbl\(\)](#), [util_cauchy_stats_tbl\(\)](#), [util_chisquare_stats_tbl\(\)](#), [util_exponential_stats_tbl\(\)](#),
[util_f_stats_tbl\(\)](#), [util_gamma_stats_tbl\(\)](#), [util_geometric_stats_tbl\(\)](#), [util_hypergeometric_stats_tbl\(\)](#),
[util_logistic_stats_tbl\(\)](#), [util_lognormal_stats_tbl\(\)](#), [util_negative_binomial_stats_tbl\(\)](#),
[util_normal_stats_tbl\(\)](#), [util_pareto_stats_tbl\(\)](#), [util_t_stats_tbl\(\)](#), [util_triangular_stats_tbl\(\)](#),
[util_uniform_stats_tbl\(\)](#), [util_weibull_stats_tbl\(\)](#)

Examples

```
library(dplyr)

tidy_poisson() |>
  util_poisson_stats_tbl() |>
  glimpse()
```

util_triangular_param_estimate

Estimate Triangular Parameters

Description

This function will attempt to estimate the triangular min, mode, and max parameters given some vector of values.

The function will return a list output by default, and if the parameter `.auto_gen_empirical` is set to TRUE then the empirical data given to the parameter `.x` will be run through the `tidy_empirical()` function and combined with the estimated beta data.

Usage

```
util_triangular_param_estimate(.x, .auto_gen_empirical = TRUE)
```

Arguments

- `.x` The vector of data to be passed to the function. Must be numeric, and all values must be $0 \leq x \leq 1$
- `.auto_gen_empirical` This is a boolean value of TRUE/FALSE with default set to TRUE. This will automatically create the `tidy_empirical()` output for the `.x` parameter and use the `tidy_combine_distributions()`. The user can then plot out the data using `$combined_data_tbl` from the function output.

Details

This function will attempt to estimate the triangular min, mode, and max parameters given some vector of values.

Value

A tibble/list

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Parameter Estimation: [util_bernoulli_param_estimate\(\)](#), [util_beta_param_estimate\(\)](#), [util_binomial_param_estimate\(\)](#), [util_burr_param_estimate\(\)](#), [util_cauchy_param_estimate\(\)](#), [util_exponential_param_estimate\(\)](#), [util_gamma_param_estimate\(\)](#), [util_geometric_param_estimate\(\)](#), [util_hypergeometric_param_estimate\(\)](#), [util_logistic_param_estimate\(\)](#), [util_lognormal_param_estimate\(\)](#), [util_negative_binomial_param_estimate\(\)](#), [util_normal_param_estimate\(\)](#), [util_pareto_param_estimate\(\)](#), [util_poisson_param_estimate\(\)](#), [util_uniform_param_estimate\(\)](#), [util_weibull_param_estimate\(\)](#)

Other Triangular: [tidy_triangular\(\)](#), [util_triangular_stats_tbl\(\)](#)

Examples

```
library(dplyr)
library(ggplot2)

x <- mtcars$mpg
output <- util_triangular_param_estimate(x)

output$parameter_tbl

output$combined_data_tbl |>
  tidy_combined_autoplot()

params <- tidy_triangular()$y |>
  util_triangular_param_estimate()
params$parameter_tbl
```

util_triangular_stats_tbl
Distribution Statistics

Description

Returns distribution statistics in a tibble.

Usage

`util_triangular_stats_tbl(.data)`

Arguments

- .data The data being passed from a tidy_ distribution function.

Details

This function will take in a tibble and returns the statistics of the given type of tidy_ distribution. It is required that data be passed from a tidy_ distribution function.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Triangular: [tidy_triangular\(\)](#), [util_triangular_param_estimate\(\)](#)

Other Distribution Statistics: [util_bernoulli_stats_tbl\(\)](#), [util_beta_stats_tbl\(\)](#), [util_binomial_stats_tbl\(\)](#), [util_burr_stats_tbl\(\)](#), [util_cauchy_stats_tbl\(\)](#), [util_chisquare_stats_tbl\(\)](#), [util_exponential_stats_tbl\(\)](#), [util_f_stats_tbl\(\)](#), [util_gamma_stats_tbl\(\)](#), [util_geometric_stats_tbl\(\)](#), [util_hypergeometric_stats_tbl\(\)](#), [util_logistic_stats_tbl\(\)](#), [util_lognormal_stats_tbl\(\)](#), [util_negative_binomial_stats_tbl\(\)](#), [util_normal_stats_tbl\(\)](#), [util_pareto_stats_tbl\(\)](#), [util_poisson_stats_tbl\(\)](#), [util_t_stats_tbl\(\)](#), [util_uniform_stats_tbl\(\)](#), [util_weibull_stats_tbl\(\)](#)

Examples

```
library(dplyr)

tidy_triangular() |>
  util_triangular_stats_tbl() |>
  glimpse()
```

util_t_stats_tbl *Distribution Statistics*

Description

Returns distribution statistics in a tibble.

Usage

```
util_t_stats_tbl(.data)
```

Arguments

- .data The data being passed from a tidy_ distribution function.

Details

This function will take in a tibble and returns the statistics of the given type of tidy_ distribution. It is required that data be passed from a tidy_ distribution function.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other T Distribution: [tidy_t\(\)](#)

Other Distribution Statistics: [util_bernoulli_stats_tbl\(\)](#), [util_beta_stats_tbl\(\)](#), [util_binomial_stats_tbl\(\)](#), [util_burr_stats_tbl\(\)](#), [util_cauchy_stats_tbl\(\)](#), [util_chisquare_stats_tbl\(\)](#), [util_exponential_stats_tbl\(\)](#), [util_f_stats_tbl\(\)](#), [util_gamma_stats_tbl\(\)](#), [util_geometric_stats_tbl\(\)](#), [util_hypergeometric_stats_tbl\(\)](#), [util_logistic_stats_tbl\(\)](#), [util_lognormal_stats_tbl\(\)](#), [util_negative_binomial_stats_tbl\(\)](#), [util_normal_stats_tbl\(\)](#), [util_pareto_stats_tbl\(\)](#), [util_poisson_stats_tbl\(\)](#), [util_triangular_stats_tbl\(\)](#), [util_uniform_stats_tbl\(\)](#), [util_weibull_stats_tbl\(\)](#)

Examples

```
library(dplyr)

tidy_t() |>
  util_t_stats_tbl() |>
  glimpse()
```

util_uniform_param_estimate *Estimate Uniform Parameters*

Description

The function will return a list output by default, and if the parameter `.auto_gen_empirical` is set to TRUE then the empirical data given to the parameter `.x` will be run through the `tidy_empirical()` function and combined with the estimated uniform data.

Usage

```
util_uniform_param_estimate(.x, .auto_gen_empirical = TRUE)
```

Arguments

- .x The vector of data to be passed to the function.
- .auto_gen_empirical This is a boolean value of TRUE/FALSE with default set to TRUE. This will automatically create the tidy_empirical() output for the .x parameter and use the tidy_combine_distributions(). The user can then plot out the data using \$combined_data_tbl from the function output.

Details

This function will attempt to estimate the uniform min and max parameters given some vector of values.

Value

A tibble/list

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Parameter Estimation: [util_bernoulli_param_estimate\(\)](#), [util_beta_param_estimate\(\)](#), [util_binomial_param_estimate\(\)](#), [util_burr_param_estimate\(\)](#), [util_cauchy_param_estimate\(\)](#), [util_exponential_param_estimate\(\)](#), [util_gamma_param_estimate\(\)](#), [util_geometric_param_estimate\(\)](#), [util_hypergeometric_param_estimate\(\)](#), [util_logistic_param_estimate\(\)](#), [util_lognormal_param_estimate\(\)](#), [util_negative_binomial_param_estimate\(\)](#), [util_normal_param_estimate\(\)](#), [util_pareto_param_estimate\(\)](#), [util_poisson_param_estimate\(\)](#), [util_triangular_param_estimate\(\)](#), [util_weibull_param_estimate\(\)](#)

Other Uniform: [tidy_uniform\(\)](#), [util_uniform_stats_tbl\(\)](#)

Examples

```
library(dplyr)
library(ggplot2)

x <- tidy_uniform(.min = 1, .max = 3)$y
output <- util_uniform_param_estimate(x)

output$parameter_tbl

output$combined_data_tbl |>
  tidy_combined_autoplot()
```

util_uniform_stats_tbl*Distribution Statistics*

Description

Returns distribution statistics in a tibble.

Usage

```
util_uniform_stats_tbl(.data)
```

Arguments

.data The data being passed from a `tidy_` distribution function.

Details

This function will take in a tibble and returns the statistics of the given type of `tidy_` distribution. It is required that data be passed from a `tidy_` distribution function.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Uniform: [tidy_uniform\(\)](#), [util_uniform_param_estimate\(\)](#)

Other Distribution Statistics: [util_bernoulli_stats_tbl\(\)](#), [util_beta_stats_tbl\(\)](#), [util_binomial_stats_tbl\(\)](#), [util_burr_stats_tbl\(\)](#), [util_cauchy_stats_tbl\(\)](#), [util_chisquare_stats_tbl\(\)](#), [util_exponential_stats_tbl\(\)](#), [util_f_stats_tbl\(\)](#), [util_gamma_stats_tbl\(\)](#), [util_geometric_stats_tbl\(\)](#), [util_hypergeometric_stats_tbl\(\)](#), [util_logistic_stats_tbl\(\)](#), [util_lognormal_stats_tbl\(\)](#), [util_negative_binomial_stats_tbl\(\)](#), [util_normal_stats_tbl\(\)](#), [util_pareto_stats_tbl\(\)](#), [util_poisson_stats_tbl\(\)](#), [util_t_stats_tbl\(\)](#), [util_triangular_stats_tbl\(\)](#), [util_weibull_stats_tbl\(\)](#)

Examples

```
library(dplyr)

tidy_uniform() |>
  util_uniform_stats_tbl() |>
  glimpse()
```

util_weibull_param_estimate
Estimate Weibull Parameters

Description

The function will return a list output by default, and if the parameter `.auto_gen_empirical` is set to TRUE then the empirical data given to the parameter `.x` will be run through the `tidy_empirical()` function and combined with the estimated weibull data.

Usage

```
util_weibull_param_estimate(.x, .auto_gen_empirical = TRUE)
```

Arguments

`.x` The vector of data to be passed to the function.

`.auto_gen_empirical`

This is a boolean value of TRUE/FALSE with default set to TRUE. This will automatically create the `tidy_empirical()` output for the `.x` parameter and use the `tidy_combine_distributions()`. The user can then plot out the data using `$combined_data_tbl` from the function output.

Details

This function will attempt to estimate the weibull shape and scale parameters given some vector of values.

Value

A tibble/list

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Parameter Estimation: [util_bernoulli_param_estimate\(\)](#), [util_beta_param_estimate\(\)](#), [util_binomial_param_estimate\(\)](#), [util_burr_param_estimate\(\)](#), [util_cauchy_param_estimate\(\)](#), [util_exponential_param_estimate\(\)](#), [util_gamma_param_estimate\(\)](#), [util_geometric_param_estimate\(\)](#), [util_hypergeometric_param_estimate\(\)](#), [util_logistic_param_estimate\(\)](#), [util_lognormal_param_estimate\(\)](#), [util_negative_binomial_param_estimate\(\)](#), [util_normal_param_estimate\(\)](#), [util_pareto_param_estimate\(\)](#), [util_poisson_param_estimate\(\)](#), [util_triangular_param_estimate\(\)](#), [util_uniform_param_estimate\(\)](#)

Other Weibull: [tidy_inverse_weibull\(\)](#), [tidy_weibull\(\)](#), [util_weibull_stats_tbl\(\)](#)

Examples

```
library(dplyr)
library(ggplot2)

x <- tidy_weibull(.shape = 1, .scale = 2)$y
output <- util_weibull_param_estimate(x)

output$parameter_tbl

output$combined_data_tbl %>%
  tidy_combined_autoplot()
```

util_weibull_stats_tbl

Distribution Statistics

Description

Returns distribution statistics in a tibble.

Usage

```
util_weibull_stats_tbl(.data)
```

Arguments

.data The data being passed from a `tidy_` distribution function.

Details

This function will take in a tibble and returns the statistics of the given type of `tidy_` distribution. It is required that data be passed from a `tidy_` distribution function.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Weibull: [tidy_inverse_weibull\(\)](#), [tidy_weibull\(\)](#), [util_weibull_param_estimate\(\)](#)

Other Distribution Statistics: [util_bernoulli_stats_tbl\(\)](#), [util_beta_stats_tbl\(\)](#), [util_binomial_stats_tbl\(\)](#), [util_burr_stats_tbl\(\)](#), [util_cauchy_stats_tbl\(\)](#), [util_chisquare_stats_tbl\(\)](#), [util_exponential_stats_tbl\(\)](#), [util_f_stats_tbl\(\)](#), [util_gamma_stats_tbl\(\)](#), [util_geometric_stats_tbl\(\)](#), [util_hypergeometric_stats_tbl\(\)](#), [util_logistic_stats_tbl\(\)](#), [util_lognormal_stats_tbl\(\)](#), [util_negative_binomial_stats_tbl\(\)](#), [util_normal_stats_tbl\(\)](#), [util_pareto_stats_tbl\(\)](#), [util_poisson_stats_tbl\(\)](#), [util_t_stats_tbl\(\)](#), [util_triangular_stats_tbl\(\)](#), [util_uniform_stats_tbl\(\)](#)

Examples

```
library(dplyr)

tidy_weibull() |>
  util_weibull_stats_tbl() |>
  glimpse()
```

Index

- * **Augment Function**
 - bootstrap_density_augment, 4
 - bootstrap_p_augment, 5
 - bootstrap_q_augment, 7
- * **Autoplot**
 - bootstrap_stat_plot, 9
 - tidy_autoplot, 24
 - tidy_combined_autoplot, 35
 - tidy_four_autoplot, 46
 - tidy_multi_dist_autoplot, 69
 - tidy_random_walk_autoplot, 82
- * **Bernoulli**
 - tidy_bernoulli, 25
 - util_bernoulli_param_estimate, 101
 - util_bernoulli_stats_tbl, 102
- * **Beta**
 - tidy_beta, 27
 - tidy_generalized_beta, 49
 - util_beta_param_estimate, 103
 - util_beta_stats_tbl, 104
- * **Binomial**
 - util_negative_binomial_stats_tbl, 130
- * **Binomial**
 - tidy_binomial, 28
 - tidy_negative_binomial, 72
 - tidy_zero_truncated_binomial, 94
 - tidy_zero_truncated_negative_binomial, 97
 - util_binomial_param_estimate, 105
 - util_binomial_stats_tbl, 107
 - util_negative_binomial_param_estimate, 129
- * **Bootstrap**
 - bootstrap_density_augment, 4
 - bootstrap_p_augment, 5
 - bootstrap_p_vec, 6
 - bootstrap_q_augment, 7
 - bootstrap_q_vec, 8
- bootstrap_stat_plot, 9
- bootstrap_unnest_tbl, 10
- tidy_bootstrap, 30
- * **Burr**
 - tidy_burr, 31
 - tidy_inverse_burr, 55
 - util_burr_param_estimate, 108
 - util_burr_stats_tbl, 109
- * **Cauchy**
 - tidy_cauchy, 32
 - util_cauchy_param_estimate, 110
 - util_cauchy_stats_tbl, 111
- * **Chisquare**
 - tidy_chisquare, 34
 - util_chisquare_stats_tbl, 112
- * **Continuous Distribution**
 - tidy_beta, 27
 - tidy_burr, 31
 - tidy_cauchy, 32
 - tidy_chisquare, 34
 - tidy_exponential, 43
 - tidy_f, 44
 - tidy_gamma, 47
 - tidy_generalized_beta, 49
 - tidy_generalized_pareto, 50
 - tidy_geometric, 52
 - tidy_inverse_burr, 55
 - tidy_inverse_exponential, 57
 - tidy_inverse_gamma, 58
 - tidy_inverse_normal, 60
 - tidy_inverse_pareto, 61
 - tidy_inverse_weibull, 63
 - tidy_logistic, 65
 - tidy_lognormal, 67
 - tidy_normal, 74
 - tidy_paralogistic, 75
 - tidy_pareto, 77
 - tidy_pareto1, 78
 - tidy_t, 88

- tidy_triangular, 90
- tidy_uniform, 91
- tidy_weibull, 92
- tidy_zero_truncated_geometric, 95
- * **Discrete Distribution**
 - tidy_bernoulli, 25
 - tidy_binomial, 28
 - tidy_hypergeometric, 53
 - tidy_negative_binomial, 72
 - tidy_poisson, 80
 - tidy_zero_truncated_binomial, 94
 - tidy_zero_truncated_negative_binomial, 97
 - tidy_zero_truncated_poisson, 98
- * **Distribution Statistics**
 - util_bernoulli_stats_tbl, 102
 - util_beta_stats_tbl, 104
 - util_binomial_stats_tbl, 107
 - util_burr_stats_tbl, 109
 - util_cauchy_stats_tbl, 111
 - util_chisquare_stats_tbl, 112
 - util_exponential_stats_tbl, 115
 - util_f_stats_tbl, 116
 - util_gamma_stats_tbl, 118
 - util_geometric_stats_tbl, 120
 - util_hypergeometric_stats_tbl, 123
 - util_logistic_stats_tbl, 125
 - util_lognormal_stats_tbl, 128
 - util_negative_binomial_stats_tbl, 130
 - util_normal_stats_tbl, 133
 - util_pareto_stats_tbl, 135
 - util_poisson_stats_tbl, 138
 - util_t_stats_tbl, 141
 - util_triangular_stats_tbl, 140
 - util_uniform_stats_tbl, 144
 - util_weibull_stats_tbl, 146
- * **Empirical**
 - tidy_distribution_comparison, 38
- * **Exponential**
 - tidy_exponential, 43
 - tidy_inverse_exponential, 57
 - util_exponential_param_estimate, 113
 - util_exponential_stats_tbl, 115
- * **F Distribution**
 - tidy_f, 44
 - util_f_stats_tbl, 116
- * **Gamma**
 - tidy_gamma, 47
 - tidy_inverse_gamma, 58
 - util_gamma_param_estimate, 117
 - util_gamma_stats_tbl, 118
- * **Gaussian**
 - tidy_inverse_normal, 60
 - tidy_normal, 74
 - util_normal_param_estimate, 131
 - util_normal_stats_tbl, 133
- * **Geometric**
 - tidy_geometric, 52
 - tidy_zero_truncated_geometric, 95
 - util_geometric_param_estimate, 119
 - util_geometric_stats_tbl, 120
- * **Helper**
 - dist_type_extractor, 22
- * **Hypergeometric**
 - tidy_hypergeometric, 53
 - util_hypergeometric_param_estimate, 121
 - util_hypergeometric_stats_tbl, 123
- * **Inverse Distribution**
 - tidy_inverse_burr, 55
 - tidy_inverse_exponential, 57
 - tidy_inverse_gamma, 58
 - tidy_inverse_normal, 60
 - tidy_inverse_pareto, 61
 - tidy_inverse_weibull, 63
- * **Logistic**
 - tidy_logistic, 65
 - tidy_paralogistic, 75
 - util_logistic_param_estimate, 124
 - util_logistic_stats_tbl, 125
- * **Lognormal**
 - tidy_lognormal, 67
 - util_lognormal_param_estimate, 126
 - util_lognormal_stats_tbl, 128
- * **Mixture Data**
 - tidy_mixture_density, 68
- * **Multiple Distribution**
 - tidy_combine_distributions, 37
 - tidy_multi_single_dist, 71
- * **Negative Binomial**
 - util_negative_binomial_stats_tbl, 130
- * **Negative Distribution**
 - tidy_negative_binomial, 72

- * **Parameter Estimation**
 - `util_bernoulli_param_estimate`, 101
 - `util_beta_param_estimate`, 103
 - `util_binomial_param_estimate`, 105
 - `util_burr_param_estimate`, 108
 - `util_cauchy_param_estimate`, 110
 - `util_exponential_param_estimate`, 113
 - `util_gamma_param_estimate`, 117
 - `util_geometric_param_estimate`, 119
 - `util_hypergeometric_param_estimate`, 121
 - `util_logistic_param_estimate`, 124
 - `util_lognormal_param_estimate`, 126
 - `util_negative_binomial_param_estimate`, 129
 - `util_normal_param_estimate`, 131
 - `util_pareto_param_estimate`, 134
 - `util_poisson_param_estimate`, 137
 - `util_triangular_param_estimate`, 139
 - `util_uniform_param_estimate`, 142
 - `util_weibull_param_estimate`, 145
- * **Pareto**
 - `tidy_generalized_pareto`, 50
 - `tidy_inverse_pareto`, 61
 - `tidy_pareto`, 77
 - `tidy_pareto1`, 78
 - `util_pareto_param_estimate`, 134
 - `util_pareto_stats_tbl`, 135
- * **Poisson**
 - `tidy_poisson`, 80
 - `tidy_zero_truncated_poisson`, 98
 - `util_poisson_param_estimate`, 137
 - `util_poisson_stats_tbl`, 138
- * **Statistic**
 - `ci_hi`, 13
 - `ci_lo`, 14
 - `tidy_kurtosis_vec`, 64
 - `tidy_range_statistic`, 84
 - `tidy_skewness_vec`, 86
 - `tidy_stat_tbl`, 87
- * **Summary Statistics**
 - `tidy_distribution_summary_tbl`, 40
- * **T Distribution**
 - `tidy_t`, 88
 - `util_t_stats_tbl`, 141
- * **Table Data**
 - `tidy_distribution_summary_tbl`, 40
- * **Triangular**
 - `tidy_triangular`, 90
 - `util_triangular_param_estimate`, 139
 - `util_triangular_stats_tbl`, 140
- * **Uniform**
 - `tidy_uniform`, 91
 - `util_uniform_param_estimate`, 142
 - `util_uniform_stats_tbl`, 144
- * **Utility**
 - `convert_to_ts`, 18
- * **Vector Function**
 - `bootstrap_p_vec`, 6
 - `bootstrap_q_vec`, 8
 - `cgmean`, 11
 - `chmean`, 12
 - `ckurtosis`, 15
 - `cmean`, 16
 - `cmedian`, 17
 - `csd`, 19
 - `cskewness`, 20
 - `cvar`, 21
 - `tidy_kurtosis_vec`, 64
 - `tidy_scale_zero_one_vec`, 85
 - `tidy_skewness_vec`, 86
- * **Visualization**
 - `triangle_plot`, 100
- * **Weibull**
 - `tidy_inverse_weibull`, 63
 - `tidy_weibull`, 92
 - `util_weibull_param_estimate`, 145
 - `util_weibull_stats_tbl`, 146
- * **Zero Truncated Distribution**
 - `tidy_zero_truncated_binomial`, 94
 - `tidy_zero_truncated_geometric`, 95
 - `tidy_zero_truncated_poisson`, 98
- * **Zero Truncated Negative Distribution**
 - `tidy_zero_truncated_negative_binomial`, 97
 - `actuar::rburr()`, 32
 - `actuar::rgenpareto()`, 51
 - `actuar::rinvburr()`, 56
 - `actuar::rinvexp()`, 57
 - `actuar::rinvgamma()`, 59
 - `actuar::rinvpareto()`, 62
 - `actuar::rinvweibull()`, 64
 - `actuar::rparalogis()`, 76

actuar::rpareto(), 77
actuar::rpareto1(), 79
actuar::rztbinom(), 94
actuar::rztgeom(), 96
actuar::rzttnbinom(), 97
actuar::rztpois(), 99

bootstrap_density_augment, 4, 6–8, 10, 11, 30
bootstrap_p_augment, 5, 5, 7, 8, 10, 11, 30
bootstrap_p_vec, 5, 6, 6, 7, 8, 10–13, 15–17, 20, 21, 30, 65, 85, 86
bootstrap_q_augment, 5–7, 7, 8, 10, 11, 30
bootstrap_q_vec, 5–7, 8, 10–13, 15–17, 20, 21, 30, 65, 85, 86
bootstrap_stat_plot, 5–8, 9, 11, 25, 30, 37, 47, 71, 83
bootstrap_unnest_tbl, 5–8, 10, 10, 30

cgmean, 7, 8, 11, 13, 15–17, 20, 21, 65, 85, 86
chmean, 7, 8, 12, 12, 15–17, 20, 21, 65, 85, 86
ci_hi, 13, 14, 65, 84, 86, 88
ci_lo, 13, 14, 65, 84, 86, 88
ckurtosis, 7, 8, 12, 13, 15, 16, 17, 20, 21, 65, 85, 86
cmean, 7, 8, 12, 13, 15, 16, 17, 20, 21, 65, 85, 86
cmedian, 7, 8, 12, 13, 15, 16, 17, 20, 21, 65, 85, 86
color_blind, 18
convert_to_ts, 18
csd, 7, 8, 12, 13, 15–17, 19, 21, 65, 85, 86
cskewness, 7, 8, 12, 13, 15–17, 20, 20, 21, 65, 85, 86
cvar, 7, 8, 12, 13, 15–17, 20, 21, 21, 65, 85, 86

dist_type_extractor, 22
dplyr::cummean(), 16
dplyr::group_by(), 40
dplyr::select(), 40

EnvStats::ebeta(), 103
EnvStats::elnorm(), 127

rinvgauss(), 61
rlang::enquo(), 5, 7

stats::density(), 26–28, 31, 33, 34, 43, 44, 47, 49, 51, 52, 54, 55, 57, 58, 60, 61, 63, 65, 67, 73–75, 77, 78, 80, 89, 91, 92, 94, 95, 97, 98

stats::rbeta(), 27, 50
stats::rbinom(), 29
stats::rcauchy(), 33
stats::rchisq(), 35
stats::rexp(), 43
stats::rf(), 45
stats::rgamma(), 48
stats::rgeom(), 53
stats::rhyper(), 54
stats::rlnorm(), 67
stats::rlogis(), 66
stats::rnbinom(), 73
stats::rnorm(), 74
stats::rpois(), 80
stats::rt(), 89
stats::runif(), 92
stats::rweibull(), 93

td_scale_color_colorblind, 23
td_scale_fill_colorblind, 23
tidy_autoplot, 10, 24, 37, 47, 71, 83
tidy_bernoulli, 25, 29, 55, 73, 81, 95, 98, 99, 101, 103
tidy_beta, 27, 32, 33, 35, 44, 45, 48, 50, 52, 53, 56, 58, 59, 61, 62, 64, 66, 68, 75, 76, 78, 79, 89, 91–93, 96, 104, 105
tidy_binomial, 26, 28, 55, 73, 81, 95, 98, 99, 106, 107, 130
tidy_bootstrap, 5–8, 10, 11, 30
tidy_burr, 28, 31, 33, 35, 44, 45, 48, 50, 52, 53, 56, 58, 59, 61, 62, 64, 66, 68, 75, 76, 78, 79, 89, 91–93, 96, 109, 110
tidy_cauchy, 28, 32, 32, 35, 44, 45, 48, 50, 52, 53, 56, 58, 59, 61, 62, 64, 66, 68, 75, 76, 78, 79, 89, 91–93, 96, 111, 112
tidy_chisquare, 28, 32, 33, 34, 44, 45, 48, 50, 52, 53, 56, 58, 59, 61, 62, 64, 66, 68, 75, 76, 78, 79, 89, 91–93, 96, 113
tidy_combine_distributions, 37, 72
tidy_combined_autoplot, 10, 25, 35, 47, 71, 83
tidy_distribution_comparison, 38
tidy_distribution_summary_tbl, 40
tidy_empirical, 42
tidy_exponential, 28, 32, 33, 35, 43, 45, 48, 50, 52, 53, 56, 58, 59, 61, 62, 64, 66,

- 68, 75, 76, 78, 79, 89, 91–93, 96, 114, 115
- `tidy_f`, 28, 32, 33, 35, 44, 44, 48, 50, 52, 53, 56, 58, 59, 61, 62, 64, 66, 68, 75, 76, 78, 79, 89, 91–93, 96, 116
- `tidy_four_autoplot`, 10, 25, 37, 46, 71, 83
- `tidy_gamma`, 28, 32, 33, 35, 44, 45, 47, 50, 52, 53, 56, 58, 59, 61, 62, 64, 66, 68, 75, 76, 78, 79, 89, 91–93, 96, 117, 118
- `tidy_generalized_beta`, 28, 32, 33, 35, 44, 45, 48, 49, 52, 53, 56, 58, 59, 61, 62, 64, 66, 68, 75, 76, 78, 79, 89, 91–93, 96, 104, 105
- `tidy_generalized_pareto`, 28, 32, 33, 35, 44, 45, 48, 50, 52, 53, 56, 58, 59, 61, 62, 64, 66, 68, 75, 76, 78, 79, 89, 91–93, 96, 135, 136
- `tidy_geometric`, 28, 32, 33, 35, 44, 45, 48, 50, 52, 53, 56, 58, 59, 61, 62, 64, 66, 68, 75, 76, 78, 79, 89, 91–93, 96, 120, 121
- `tidy_hypergeometric`, 26, 29, 53, 73, 81, 95, 98, 99, 122, 124
- `tidy_inverse_burr`, 28, 32, 33, 35, 44, 45, 48, 50, 52, 53, 55, 58, 59, 61, 62, 64, 66, 68, 75, 76, 78, 79, 89, 91–93, 96, 109, 110
- `tidy_inverse_exponential`, 28, 32, 33, 35, 44, 45, 48, 50, 52, 53, 56, 57, 59, 61, 62, 64, 66, 68, 75, 76, 78, 79, 89, 91–93, 96, 114, 115
- `tidy_inverse_gamma`, 28, 32, 33, 35, 44, 45, 48, 50, 52, 53, 56, 58, 59, 61, 62, 64, 66, 68, 75, 76, 78, 79, 89, 91–93, 96, 117, 118
- `tidy_inverse_normal`, 28, 32, 33, 35, 44, 45, 48, 50, 52, 53, 56, 58, 59, 60, 62, 64, 66, 68, 75, 76, 78, 79, 89, 91–93, 96, 132, 134
- `tidy_inverse_pareto`, 28, 32, 33, 35, 44, 45, 48, 50, 52, 53, 56, 58, 59, 61, 61, 64, 66, 68, 75, 76, 78, 79, 89, 91–93, 96, 135, 136
- `tidy_inverse_weibull`, 28, 32, 33, 35, 44, 45, 48, 50, 52, 53, 56, 58, 59, 61, 62, 63, 66, 68, 75, 76, 78, 79, 89, 91–93, 96, 145, 147
- `tidy_kurtosis_vec`, 7, 8, 12–17, 20, 21, 64, 84–86, 88
- `tidy_logistic`, 28, 32, 33, 35, 44, 45, 48, 50, 52, 53, 56, 58, 59, 61, 62, 64, 65, 68, 75, 76, 78, 79, 89, 91–93, 96, 125, 126
- `tidy_lognormal`, 28, 32, 33, 35, 44, 45, 48, 50, 52, 53, 56, 58, 59, 61, 62, 64, 66, 67, 75, 76, 78, 79, 89, 91–93, 96, 127, 129
- `tidy_mixture_density`, 68
- `tidy_multi_dist_autoplot`, 10, 25, 37, 47, 69, 83
- `tidy_multi_single_dist`, 38, 71
- `tidy_negative_binomial`, 26, 29, 55, 72, 81, 95, 98, 99, 106, 107, 130
- `tidy_normal`, 28, 32, 33, 35, 44, 45, 48, 50, 52, 53, 56, 58, 59, 61, 62, 64, 66, 68, 74, 76, 78, 79, 89, 91–93, 96, 132, 134
- `tidy_paralogistic`, 28, 32, 34, 35, 44, 45, 48, 50, 52, 53, 56, 58, 59, 61, 62, 64, 66, 68, 75, 76, 78, 79, 89, 91–93, 96, 125, 126
- `tidy_pareto`, 28, 32, 34, 35, 44, 45, 48, 50, 52, 53, 56, 58, 59, 61, 62, 64, 66, 68, 75, 76, 77, 79, 89, 91–93, 96, 135, 136
- `tidy_pareto1`, 28, 32, 34, 35, 44, 45, 48, 50, 52, 53, 56, 58, 59, 61, 62, 64, 66, 68, 75, 76, 78, 79, 89, 91–93, 96, 135, 136
- `tidy_poisson`, 26, 29, 55, 73, 80, 95, 98, 99, 137, 139
- `tidy_random_walk`, 81
- `tidy_random_walk_autoplot`, 10, 25, 37, 47, 71, 82
- `tidy_range_statistic`, 13, 14, 65, 84, 86, 88
- `tidy_scale_zero_one_vec`, 7, 8, 12, 13, 15–17, 20, 21, 65, 85, 86
- `tidy_skewness_vec`, 7, 8, 12–17, 20, 21, 65, 84, 85, 86, 88
- `tidy_stat_tbl`, 13, 14, 65, 84, 86, 87
- `tidy_t`, 28, 32, 34, 35, 44, 45, 48, 50, 52, 53, 56, 58, 59, 61, 62, 64, 66, 68, 75, 76, 78, 79, 88, 91–93, 96, 142
- `tidy_triangular`, 28, 32, 34, 35, 44, 45, 48, 50, 52, 53, 56, 58, 59, 61, 62, 64, 66, 68, 75, 76, 78, 79, 89, 90, 92, 93, 96,

- 140, 141
tidy_uniform, 28, 32, 34, 35, 44, 45, 48, 50,
 52, 53, 56, 58, 59, 61, 62, 64, 66, 68,
 75, 76, 78, 79, 89, 91, 91, 93, 96,
 143, 144
tidy_weibull, 28, 32, 34, 35, 44, 45, 48, 50,
 52, 53, 56, 58, 59, 61, 62, 64, 66, 68,
 75, 76, 78, 79, 89, 91, 92, 92, 96,
 145, 147
tidy_zero_truncated_binomial, 26, 29, 55,
 73, 81, 94, 96, 98, 99, 106, 107, 130
tidy_zero_truncated_geometric, 28, 32,
 34, 35, 44, 45, 48, 50, 52, 53, 56, 58,
 59, 61, 62, 64, 66, 68, 75, 76, 78, 79,
 89, 91–93, 95, 95, 99, 120, 121
tidy_zero_truncated_negative_binomial,
 26, 29, 55, 73, 81, 95, 97, 99, 106,
 107, 130
tidy_zero_truncated_poisson, 26, 29, 55,
 73, 81, 95, 96, 98, 98, 137, 139
triangle_plot, 100

util_bernoulli_param_estimate, 26, 101,
 103, 104, 106, 109, 111, 114, 117,
 120, 122, 125, 127, 130, 132, 135,
 137, 140, 143, 145
util_bernoulli_stats_tbl, 26, 101, 102,
 105, 107, 110, 112, 113, 115, 116,
 118, 121, 124, 126, 129, 131, 134,
 136, 139, 141, 142, 144, 147
util_beta_param_estimate, 28, 50, 101,
 103, 105, 106, 109, 111, 114, 117,
 120, 122, 125, 127, 130, 132, 135,
 137, 140, 143, 145
util_beta_stats_tbl, 28, 50, 103, 104, 104,
 107, 110, 112, 113, 115, 116, 118,
 121, 124, 126, 129, 131, 134, 136,
 139, 141, 142, 144, 147
util_binomial_param_estimate, 29, 73, 95,
 98, 101, 104, 105, 107, 109, 111,
 114, 117, 120, 122, 125, 127, 130,
 132, 135, 137, 140, 143, 145
util_binomial_stats_tbl, 29, 73, 95, 98,
 103, 105, 106, 107, 110, 112, 113,
 115, 116, 118, 121, 124, 126,
 129–131, 134, 136, 139, 141, 142,
 144, 147
util_burr_param_estimate, 32, 56, 101,
 104, 106, 108, 110, 111, 114, 117,
 120, 122, 125, 127, 130, 132, 135,
 137, 140, 143, 145
util_cauchy_param_estimate, 34, 101, 104,
 106, 109, 110, 112, 114, 117, 120,
 122, 125, 127, 130, 132, 135, 137,
 140, 143, 145
util_cauchy_stats_tbl, 34, 103, 105, 107,
 110, 111, 111, 113, 115, 116, 118,
 121, 124, 126, 129, 131, 134, 136,
 139, 141, 142, 144, 147
util_chisquare_params_tbl, 35, 103, 105,
 107, 110, 112, 112, 115, 116, 118,
 121, 124, 126, 129, 131, 134, 136,
 139, 141, 142, 144, 147
util_exponential_param_estimate, 44, 58,
 101, 104, 106, 109, 111, 113, 115,
 117, 120, 122, 125, 127, 130, 132,
 135, 137, 140, 143, 145
util_exponential_stats_tbl, 44, 58, 103,
 105, 107, 110, 112–114, 115, 116,
 118, 121, 124, 126, 129, 131, 134,
 136, 139, 141, 142, 144, 147
util_f_stats_tbl, 45, 103, 105, 107, 110,
 112, 113, 115, 116, 118, 121, 124,
 126, 129, 131, 134, 136, 139, 141,
 142, 144, 147
util_gamma_param_estimate, 48, 59, 101,
 104, 106, 109, 111, 114, 117, 118,
 120, 122, 125, 127, 130, 132, 135,
 137, 140, 143, 145
util_gamma_stats_tbl, 48, 59, 103, 105,
 107, 110, 112, 113, 115–117, 118,
 121, 124, 126, 129, 131, 134, 136,
 139, 141, 142, 144, 147
util_geometric_param_estimate, 53, 96,
 101, 104, 106, 109, 111, 114, 117,
 119, 121, 122, 125, 127, 130, 132,
 135, 137, 140, 143, 145
util_geometric_stats_tbl, 53, 96, 103,
 105, 107, 110, 112, 113, 115, 116,
 118, 120, 120, 124, 126, 129, 131,
 134, 136, 139, 141, 142, 144, 147
util_hypergeometric_param_estimate, 55,
 101, 104, 106, 109, 111, 114, 117,

120, 121, 124, 125, 127, 130, 132,
 135, 137, 140, 143, 145
 util_hypergeometric_stats_tbl, 55, 103,
 105, 107, 110, 112, 113, 115, 116,
 118, 121, 122, 123, 126, 129, 131,
 134, 136, 139, 141, 142, 144, 147
 util_logistic_param_estimate, 66, 76,
 101, 104, 106, 109, 111, 114, 117,
 120, 122, 124, 126, 127, 130, 132,
 135, 137, 140, 143, 145
 util_logistic_stats_tbl, 66, 76, 103, 105,
 107, 110, 112, 113, 115, 116, 118,
 121, 124, 125, 125, 129, 131, 134,
 136, 139, 141, 142, 144, 147
 util_lognormal_param_estimate, 68, 101,
 104, 106, 109, 111, 114, 117, 120,
 122, 125, 126, 129, 130, 132, 135,
 137, 140, 143, 145
 util_lognormal_stats_tbl, 68, 103, 105,
 107, 110, 112, 113, 115, 116, 118,
 121, 124, 126, 127, 128, 131, 134,
 136, 139, 141, 142, 144, 147
 util_negative_binomial_param_estimate,
 29, 73, 95, 98, 101, 104, 106, 107,
 109, 111, 114, 117, 120, 122, 125,
 127, 129, 132, 135, 137, 140, 143,
 145
 util_negative_binomial_stats_tbl, 103,
 105, 107, 110, 112, 113, 115, 116,
 118, 121, 124, 126, 129, 130, 134,
 136, 139, 141, 142, 144, 147
 util_normal_param_estimate, 61, 75, 101,
 104, 106, 109, 111, 114, 117, 120,
 122, 125, 127, 130, 131, 134, 135,
 137, 140, 143, 145
 util_normal_stats_tbl, 61, 75, 103, 105,
 107, 110, 112, 113, 115, 116, 118,
 121, 124, 126, 129, 131, 132, 133,
 136, 139, 141, 142, 144, 147
 util_pareto_param_estimate, 52, 62, 78,
 79, 101, 104, 106, 109, 111, 114,
 117, 120, 122, 125, 127, 130, 132,
 134, 136, 137, 140, 143, 145
 util_pareto_stats_tbl, 52, 62, 78, 79, 103,
 105, 107, 110, 112, 113, 115, 116,
 118, 121, 124, 126, 129, 131, 134,
 135, 139, 141, 142, 144, 147
 util_poisson_param_estimate, 81, 99, 101,
 104, 106, 109, 111, 114, 117, 120,
 122, 125, 127, 130, 132, 135, 137,
 139, 140, 143, 145
 util_poisson_stats_tbl, 81, 99, 103, 105,
 107, 110, 112, 113, 115, 116, 118,
 121, 124, 126, 129, 131, 134, 136,
 137, 138, 141, 142, 144, 147
 util_t_stats_tbl, 89, 103, 105, 107, 110,
 112, 113, 115, 116, 118, 121, 124,
 126, 129, 131, 134, 136, 139, 141,
 141, 144, 147
 util_triangular_param_estimate, 91, 101,
 104, 106, 109, 111, 114, 117, 120,
 122, 125, 127, 130, 132, 135, 137,
 139, 141, 143, 145
 util_triangular_stats_tbl, 91, 103, 105,
 107, 110, 112, 113, 115, 116, 118,
 121, 124, 126, 129, 131, 134, 136,
 139, 140, 140, 142, 144, 147
 util_uniform_param_estimate, 92, 101,
 104, 106, 109, 111, 114, 117, 120,
 122, 125, 127, 130, 132, 135, 137,
 140, 142, 144, 145
 util_uniform_stats_tbl, 92, 103, 105, 107,
 110, 112, 113, 115, 116, 118, 121,
 124, 126, 129, 131, 134, 136, 139,
 141–143, 144, 147
 util_weibull_param_estimate, 64, 93, 101,
 104, 106, 109, 111, 114, 117, 120,
 122, 125, 127, 130, 132, 135, 137,
 140, 143, 145, 147
 util_weibull_stats_tbl, 64, 93, 103, 105,
 107, 110, 112, 113, 115, 116, 118,
 121, 124, 126, 129, 131, 134, 136,
 139, 141, 142, 144, 145, 146