

Package ‘nlist’

September 1, 2021

Title Lists of Numeric Atomic Objects

Version 0.3.3

Description Create and manipulate numeric list ('nlist') objects. An 'nlist' is an S3 list of uniquely named numeric objects. An numeric object is an integer or double vector, matrix or array. An 'nlists' object is a S3 class list of 'nlist' objects with the same names, dimensionalities and typeofs. Numeric list objects are of interest because they are the raw data inputs for analytic engines such as 'JAGS', 'STAN' and 'TMB'. Numeric lists objects, which are useful for storing multiple realizations of simulated data sets, can be converted to coda::mcmc and coda::mcmc.list objects.

License MIT + file LICENSE

URL <https://github.com/poissonconsulting/nlist>

BugReports <https://github.com/poissonconsulting/nlist/issues>

Depends R (>= 3.4)

Imports abind,

chk,
coda,
extras,
generics,
lifecycle,
purrr,
stats,
term,
tibble,
universals

Suggests covr,

rlang,
testthat

RdMacros lifecycle

Config/testthat/edition 3

Encoding UTF-8

Language en-US

Roxygen list(markdown = TRUE)

RoxygenNote 7.1.1

R topics documented:

aggregate.nlist	3
aggregate.nlists	4
as_mcmc	4
as_mcmc_list	5
as_nlist	6
as_nlists	8
as_term.mcmc	9
as_term.nlist	9
as_term.nlists	10
as_term_frame	10
as_term_frame.nlist	11
as_term_frame.nlists	11
bind_iterations.mcmc	12
bind_iterations.mcmc.list	13
chk_nlist	13
collapse_chains.mcmc	14
collapse_chains.mcmc.list	15
collapse_chains.nlist	15
collapse_chains.nlists	16
complete_terms.mcmc	17
estimates.nlist	17
estimates.nlists	18
fill_all.nlist	19
fill_all.nlists	20
fill_na.nlist	21
fill_na.nlists	22
is_numeric	23
nchains.mcmc	24
nchains.mcmc.list	24
nchains.nlist	25
nchains.nlists	25
niters.mcmc	26
niters.mcmc.list	27
niters.nlist	27
niters.nlists	28
nlist	28
nlists	29
npdims.mcmc.list	30
npdims.nlist	30
npdims.nlists	31
nsims.nlist	32
nsims.nlists	32
nterms.mcmc	33
nterms.mcmc.list	34
nterms.nlist	34
nterms.nlists	35
pars.mcmc	35
pars.mcmc.list	36
pars.nlist	37
pars.nlists	37

pdims.mcmc	38
pdims.mcmc.list	38
pdims.nlist	39
pdims.nlists	40
relist_nlist	40
set_pars.mcmc	41
set_pars.mcmc.list	42
set_pars.nlist	42
set_pars.nlists	43
split_chains.nlists	44
subset.mcmc	44
subset.mcmc.list	45
subset.nlist	46
subset.nlists	47
thin.default	48
tidy.mcmc	48
tidy.mcmc.list	49
tidy.nlists	49
unlist.nlist	50
unlist_nlist	51
vld_nlist	51

Index	53
--------------	-----------

aggregate.nlist	<i>Aggregate nlist</i>
-----------------	------------------------

Description

Aggregates an `nlist_object()` into a named list of numeric scalars.

Usage

```
## S3 method for class 'nlist'
aggregate(x, fun = mean, ...)
```

Arguments

x	An nlist object.
fun	A function that given a numeric vector returns a numeric scalar.
...	Additional arguments passed to fun.

Value

An named list of numeric scalars

See Also

Other aggregate: [aggregate.nlists\(\)](#)

Examples

```
aggregate(nlist(x = 1:9))
aggregate(nlist(y = 3:5, zz = matrix(1:9, 3)), fun = function(x) x[1])
```

aggregate.nlists	<i>Aggregate nlists</i>
------------------	-------------------------

Description

Aggregates an `nlists_object()` into a `nlist_object()` or `by_chain = TRUE` an `nlists_object()` with `nchains` `nlist_object()`s.

Usage

```
## S3 method for class 'nlists'
aggregate(x, fun = mean, ..., by_chain = FALSE)
```

Arguments

<code>x</code>	An object.
<code>fun</code>	A function that given a numeric vector returns a numeric scalar.
<code>...</code>	Unused.
<code>by_chain</code>	A flag specifying whether to aggregate by chains.

Value

An `nlist` object if `by_chain = FALSE` otherwise an `nlists` object.

See Also

Other aggregate: [aggregate.nlist\(\)](#)

Examples

```
aggregate(nlists(nlist(x = 1:3), nlist(x = 2:4)))
```

as_mcmc	<i>Coerce to mcmc Object</i>
---------	------------------------------

Description

Coerce an R object to an `mcmc` object.

Usage

```
as_mcmc(x, ...)  
  
## S3 method for class 'mcmc.list'  
as_mcmc(x, ...)  
  
## S3 method for class 'nlist'  
as_mcmc(x, ...)  
  
## S3 method for class 'nlists'  
as_mcmc(x, ...)
```

Arguments

x	An object.
...	Unused.

Value

An mcmc object.

Methods (by class)

- `mcmc.list`: Coerce an `mcmc.list` object to an mcmc object.
- `nlist`: Coerce an `nlist` object to an mcmc object.
- `nlists`: Coerce an `nlists` object to an mcmc object.

See Also

[coda::as.mcmc\(\)](#)
Other mcmc: [as_mcmc_list\(\)](#)

Examples

```
as_mcmc(as_mcmc_list(nlists(nlist(x = 2), nlist(x = 3))))  
as_mcmc(nlist(x = matrix(1:6, 2)))  
as_mcmc(nlists(  
  nlist(x = matrix(1:6, 2)),  
  nlist(x = matrix(3:8, 2))  
))
```

as_mcmc_list

Coerce to an mcmc.list Object

Description

Coerce an R object to an `mcmc.list` object.

Usage

```
as_mcmc_list(x, ...)  
  
## S3 method for class 'mcmc'  
as_mcmc_list(x, ...)  
  
## S3 method for class 'nlist'  
as_mcmc_list(x, ...)  
  
## S3 method for class 'nlists'  
as_mcmc_list(x, ...)
```

Arguments

x	An object.
...	Unused.

Value

An mcmc.list object.

Methods (by class)

- mcmc: Coerce an mcmc object to an mcmc.list object.
- nlist: Coerce an nlist object to an mcmc.list object.
- nlists: Coerce an nlists object to an mcmc.list object.

See Also

Other mcmc: [as_mcmc\(\)](#)

Examples

```
as_mcmc_list(nlist(x = matrix(1:6, 2)))  
  
as_mcmc_list(nlists(  
  nlist(x = matrix(1:6, 2)),  
  nlist(x = matrix(3:8, 2))  
))
```

as_nlist

Coerce to nlist

Description

Coerce an R object to an [nlist_object\(\)](#).

Usage

```
as_nlist(x, ...)  
  
as.nlist(x, ...)  
  
## S3 method for class 'numeric'  
as_nlist(x, ...)  
  
## S3 method for class 'list'  
as_nlist(x, ...)  
  
## S3 method for class 'data.frame'  
as_nlist(x, ...)  
  
## S3 method for class 'mcmc'  
as_nlist(x, ...)  
  
## S3 method for class 'mcmc.list'  
as_nlist(x, ...)  
  
as.nlists(x, ...)
```

Arguments

x	An object.
...	Unused.

Value

An nlist object.

Methods (by class)

- `numeric`: Coerce named numeric vector to nlist
- `list`: Coerce list to nlist
- `data.frame`: Coerce data.frame to nlist
- `mcmc`: Coerce mcmc (with one iteration) to nlist
- `mcmc.list`: Coerce mcmc.list (with one iteration) to nlist

See Also

Other coerce: [as_nlists\(\)](#)

Examples

```
as_nlist(list(x = 1:4))  
as_nlist(c(`a[2]` = 3, `a[1]` = 2))
```

`as_nlists`*Coerce to nlists*

Description

Coerce an R object to an `nlists_object()`.

Usage

```
as_nlists(x, ...)  
  
## S3 method for class 'list'  
as_nlists(x, ...)  
  
## S3 method for class 'mcmc'  
as_nlists(x, ...)  
  
## S3 method for class 'mcmc.list'  
as_nlists(x, ...)  
  
## S3 method for class 'nlist'  
as_nlists(x, ...)
```

Arguments

<code>x</code>	An object.
<code>...</code>	Unused.

Value

An nlists object.

Methods (by class)

- `list`: Coerce list to nlists
- `mcmc`: Coerce mcmc to nlists
- `mcmc.list`: Coerce mcmc.list to nlists
- `nlist`: Coerce nlist to nlists

See Also

Other coerce: `as_nlist()`

Examples

```
as_nlists(list(nlist(x = c(1, 5)), nlist(x = c(2, 3)), nlist(x = c(3, 2))))
```

as_term.mcmc	<i>Coerce to a Term Vector</i>
--------------	--------------------------------

Description

Coerce to a Term Vector

Usage

```
## S3 method for class 'mcmc'  
as_term(x, ...)
```

Arguments

x	An object.
...	Unused.

See Also

Other coerce term: [as_term.nlists\(\)](#), [as_term.nlist\(\)](#), [as_term_frame.nlists\(\)](#), [as_term_frame.nlist\(\)](#), [as_term_frame\(\)](#)

Examples

```
as_term(as_mcmc(nlist(x = matrix(1:4, ncol = 2))))
```

as_term.nlist	<i>Coerce to a Term Vector</i>
---------------	--------------------------------

Description

Coerce to a Term Vector

Usage

```
## S3 method for class 'nlist'  
as_term(x, ...)
```

Arguments

x	An object.
...	Unused.

See Also

Other coerce term: [as_term.mcmc\(\)](#), [as_term.nlists\(\)](#), [as_term_frame.nlists\(\)](#), [as_term_frame.nlist\(\)](#), [as_term_frame\(\)](#)

Examples

```
as_term(nlist(x = matrix(1:4, ncol = 2)))
```

as_term.nlists *Coerce to a Term Vector*

Description

Coerce to a Term Vector

Usage

```
## S3 method for class 'nlists'
as_term(x, ...)
```

Arguments

x	An object.
...	Unused.

See Also

Other coerce term: [as_term.mcmc\(\)](#), [as_term.nlist\(\)](#), [as_term_frame.nlists\(\)](#), [as_term_frame.nlist\(\)](#), [as_term_frame\(\)](#)

Examples

```
as_term(nlists(nlist(x = matrix(1:4, ncol = 2))))
```

as_term_frame *Coerce to a Term Frame*

Description

A term frame is a tibble with the first column a term vector called and a numeric column called value and in the case of an nlists object an integer vector called samples. It includes the original nlist or nlists object.

Usage

```
as_term_frame(x, ...)
```

Arguments

x	An object.
...	Unused.

Value

An term_frame object.

See Also

Other coerce term: [as_term.mcmc\(\)](#), [as_term.nlists\(\)](#), [as_term.nlist\(\)](#), [as_term_frame.nlists\(\)](#), [as_term_frame.nlist\(\)](#)

as_term_frame.nlist *Coerce nlist Object to Data Frame*

Description

Coerces an nlist object to a data.frame with an term column and a value column.

Usage

```
## S3 method for class 'nlist'  
as_term_frame(x, ...)
```

Arguments

x	An nlist object.
...	Unused.

Value

A data.frame.

See Also

Other coerce term: [as_term.mcmc\(\)](#), [as_term.nlists\(\)](#), [as_term.nlist\(\)](#), [as_term_frame.nlists\(\)](#), [as_term_frame\(\)](#)

Examples

```
as_term_frame(nlist(x = 1, y = 4:6))
```

as_term_frame.nlists *Coerce nlists Object to Data Frame*

Description

Coerces an nlists object to a data.frame with a term, sample and value column.

Usage

```
## S3 method for class 'nlists'  
as_term_frame(x, ...)
```

Arguments

x	An nlists object.
...	Unused.

Value

A data.frame.

See Also

Other coerce term: [as_term.mcmc\(\)](#), [as_term.nlists\(\)](#), [as_term.nlist\(\)](#), [as_term_frame.nlist\(\)](#), [as_term_frame\(\)](#)

Examples

```
as_term_frame(nlists(
  nlist(x = 1, y = 4:6),
  nlist(x = 3, y = 1:3)
))
```

bind_iterations.mcmc *Bind Iterations*

Description

Combines two MCMC objects (with the same parameters and chains) by iterations.

Usage

```
## S3 method for class 'mcmc'
bind_iterations(x, x2, ...)
```

Arguments

x	An object.
x2	A second object.
...	Other arguments passed to methods.

Value

The combined object.

See Also

Other MCMC manipulations: [bind_chains\(\)](#), [collapse_chains\(\)](#), [estimates\(\)](#), [split_chains\(\)](#)

Examples

```
bind_iterations(as_mcmc(nlist(x = 1)), as_mcmc(nlist(x = 3)))
```

```
bind_iterations.mcmc.list
```

Bind Iterations

Description

Combines two MCMC objects (with the same parameters and chains) by iterations.

Usage

```
## S3 method for class 'mcmc.list'
bind_iterations(x, x2, ...)
```

Arguments

x	An object.
x2	A second object.
...	Other arguments passed to methods.

Value

The combined object.

See Also

Other MCMC manipulations: [bind_chains\(\)](#), [collapse_chains\(\)](#), [estimates\(\)](#), [split_chains\(\)](#)

Examples

```
bind_iterations(as_mcmc_list(nlist(x = 1)), as_mcmc_list(nlist(x = 3)))
```

```
chk_nlist
```

Check nlist Object or nlists Object

Description

chk_nlist checks if an [nlist-object\(\)](#).

Usage

```
chk_nlist(x, x_name = NULL)

chk_nlists(x, x_name = NULL)
```

Arguments

x	The object to check.
x_name	A string of the name of object x or NULL.

Value

NULL, invisibly. Called for the side effect of throwing an error if the condition is not met.

Functions

- `chk_nlists`: Check nlists Object
`chk_nlists` checks if an [nlists-object\(\)](#).

Examples

```
# chk_nlist
chk_nlist(nlist(x = 1))
try(chk_nlist(list(x = 1)))

# chk_nlists
chk_nlists(nlists(nlist(x = 1)))
```

collapse_chains.mcmc *Collapse Chains*

Description

Collapses an MCMC object's chains into a single chain.

Usage

```
## S3 method for class 'mcmc'
collapse_chains(x, ...)
```

Arguments

`x` An object.
`...` Other arguments passed to methods.

Details

As mcmc objects can only have 1 chain the object is unchanged.

Value

The modified object with one chain.

See Also

Other collapse: [collapse_chains.nlists\(\)](#), [collapse_chains.nlist\(\)](#)

Examples

```
collapse_chains(as_mcmc(nlist(x = 2)))
```

collapse_chains.mcmc.list
Collapse Chains

Description

Collapses an MCMC object's chains into a single chain.

Usage

```
## S3 method for class 'mcmc.list'  
collapse_chains(x, ...)
```

Arguments

x An object.
... Other arguments passed to methods.

Value

The modified object with one chain.

See Also

Other MCMC manipulations: [bind_chains\(\)](#), [bind_iterations\(\)](#), [estimates\(\)](#), [split_chains\(\)](#)

collapse_chains.nlist *Collapse Chains*

Description

Collapses an MCMC object's chains into a single chain.

Usage

```
## S3 method for class 'nlist'  
collapse_chains(x, ...)
```

Arguments

x An object.
... Other arguments passed to methods.

Details

As nlist objects can only have 1 chain the object is unchanged.

Value

The modified object with one chain.

See Also

Other collapse: [collapse_chains.mcmc\(\)](#), [collapse_chains.nlists\(\)](#)

Examples

```
collapse_chains(nlist(x = 2))
```

collapse_chains.nlists

Collapse Chains

Description

Collapses an MCMC object's chains into a single chain.

Usage

```
## S3 method for class 'nlists'  
collapse_chains(x, ...)
```

Arguments

x	An object.
...	Other arguments passed to methods.

Value

The modified object with one chain.

See Also

Other collapse: [collapse_chains.mcmc\(\)](#), [collapse_chains.nlist\(\)](#)

Examples

```
collapse_chains(nlist(x = 2))
```

complete_terms.mcmc *Complete Terms*

Description

Adds any absent elements to an mcmc object.

Usage

```
## S3 method for class 'mcmc'
complete_terms(x, silent = FALSE, ...)
```

Arguments

x	An mcmc object.
silent	A flag specifying whether to suppress warning messages.
...	Unused.

Details

The terms are repaired before being completed. Missing or invalid or inconsistent terms are dropped with a warning.

Value

The repaired and complete mcmc object.

Examples

```
mcmc <- as_mcmc(nlist(beta = matrix(1:4, nrow = 2)))
mcmc <- mcmc[, -4, drop = FALSE]
complete_terms(mcmc)
```

estimates.nlist *Estimates*

Description

Calculates the estimates for an MCMC object.

Usage

```
## S3 method for class 'nlist'
estimates(x, fun = median, ...)
```

Arguments

x	An object.
fun	A function that given a numeric vector returns a numeric scalar.
...	Additional arguments passed to fun.

Value

A list of uniquely named numeric objects.

See Also

Other MCMC manipulations: [bind_chains\(\)](#), [bind_iterations\(\)](#), [collapse_chains\(\)](#), [split_chains\(\)](#)

Examples

```
estimates(nlist(x = 1:9))
estimates(nlist(y = 3:5, zz = matrix(1:9, 3)))
```

estimates.nlists	<i>Estimates</i>
------------------	------------------

Description

Calculates the estimates for an MCMC object.

Usage

```
## S3 method for class 'nlists'
estimates(x, fun = median, ...)
```

Arguments

x	An object.
fun	A function that given a numeric vector returns a numeric scalar.
...	Additional arguments passed to fun.

Value

A list of uniquely named numeric objects.

See Also

Other MCMC manipulations: [bind_chains\(\)](#), [bind_iterations\(\)](#), [collapse_chains\(\)](#), [split_chains\(\)](#)

Examples

```
estimates(nlists(nlist(x = 1:3), nlist(x = 2:4)), fun = mean)
```

fill_all.nlist	<i>Fill All Values</i>
----------------	------------------------

Description

Fills all of an object's (missing and non-missing) values while preserving the object's dimensionality and class.

Usage

```
## S3 method for class 'nlist'  
fill_all(x, value = 0L, nas = TRUE, ...)
```

Arguments

x	An object.
value	A scalar of the value to replace values with.
nas	A flag specifying whether to also fill missing values.
...	Other arguments passed to methods.

Details

It should only be defined for objects with values of consistent class ie not standard data.frames.

Value

The modified object.

Methods (by class)

- logical: Fill All for logical Objects
- integer: Fill All for integer Objects
- numeric: Fill All for numeric Objects
- character: Fill All for character Objects

See Also

Other fill: [fill_na\(\)](#)

Examples

```
fill_all(nlist(x = c(2, NA), y = matrix(c(1:3, NA), nrow = 2)))  
fill_all(nlist(x = c(2, NA), y = matrix(c(1:3, NA), nrow = 2)), nas = FALSE)
```

fill_all.nlists	<i>Fill All Values</i>
-----------------	------------------------

Description

Fills all of an object's (missing and non-missing) values while preserving the object's dimensionality and class.

Usage

```
## S3 method for class 'nlists'
fill_all(x, value = 0L, nas = TRUE, ...)
```

Arguments

x	An object.
value	A scalar of the value to replace values with.
nas	A flag specifying whether to also fill missing values.
...	Other arguments passed to methods.

Details

It should only be defined for objects with values of consistent class ie not standard data.frames.

Value

The modified object.

Methods (by class)

- logical: Fill All for logical Objects
- integer: Fill All for integer Objects
- numeric: Fill All for numeric Objects
- character: Fill All for character Objects

See Also

Other fill: [fill_na\(\)](#)

Examples

```
fill_all(nlists(nlist(x = c(2, NA)), nlist(x = c(NA_real_, NA))))
fill_all(nlists(nlist(x = c(2, NA)), nlist(x = c(NA_real_, NA))), nas = FALSE)
```

fill_na.nlist	<i>Fill Missing Values</i>
---------------	----------------------------

Description

Fills all of an object's missing values while preserving the object's dimensionality and class.

Usage

```
## S3 method for class 'nlist'  
fill_na(x, value = 0L, ...)
```

Arguments

x	An object.
value	A scalar of the value to replace values with.
...	Other arguments passed to methods.

Details

It should only be defined for objects with values of consistent class ie not standard data.frames.

Value

The modified object.

Methods (by class)

- logical: Fill Missing Values for logical Objects
- integer: Fill Missing Values for integer Objects
- numeric: Fill Missing Values for numeric Objects
- character: Fill Missing Values for character Objects

See Also

Other fill: [fill_all\(\)](#)

Examples

```
fill_na(nlist(x = c(2, NA), y = matrix(c(1:3, NA), nrow = 2)))  
fill_na(nlists(nlist(x = c(2, NA)), nlist(x = c(NA_real_, NA))))
```

fill_na.nlists	<i>Fill Missing Values</i>
----------------	----------------------------

Description

Fills all of an object's missing values while preserving the object's dimensionality and class.

Usage

```
## S3 method for class 'nlists'  
fill_na(x, value = 0L, ...)
```

Arguments

x	An object.
value	A scalar of the value to replace values with.
...	Other arguments passed to methods.

Details

It should only be defined for objects with values of consistent class ie not standard data.frames.

Value

The modified object.

Methods (by class)

- logical: Fill Missing Values for logical Objects
- integer: Fill Missing Values for integer Objects
- numeric: Fill Missing Values for numeric Objects
- character: Fill Missing Values for character Objects

See Also

Other fill: [fill_all\(\)](#)

Examples

```
fill_na(nlist(x = c(2, NA), y = matrix(c(1:3, NA), nrow = 2)))
```

is_numeric	<i>Is numeric, nlist or nlists</i>
------------	------------------------------------

Description

Ask whether x is a numeric object, `nlist_object()` or `nlists_object()`.

Usage

```
is_numeric(x)
is_nlist(x)
is_nlists(x)
```

Arguments

x An object.

Value

A flag indicating whether x is a numeric object or inherits from S3 class nlist or nlists.

Functions

- `is_nlist`: Is nlist
- `is_nlists`: Is nlists

Examples

```
# is_numeric
is_numeric(list(x = 1))
is_numeric(1)

# is_nlist
is_nlist(1)
is_nlist(list(x = 1))
is_nlist(nlist(x = 1))

# is_nlists
is_nlists(nlist(x = 1))
is_nlists(nlists(nlist(x = 2), nlist(x = 3.5)))
```

nchains.mcmc *Number of Chains*

Description

Gets the number of chains of an MCMC object.

Usage

```
## S3 method for class 'mcmc'  
nchains(x, ...)
```

Arguments

x An object.
... Other arguments passed to methods.

Value

An integer scalar of the number of chains.

See Also

Other MCMC dimensions: [niters\(\)](#), [npars\(\)](#), [nsams\(\)](#), [nsims\(\)](#), [nterms\(\)](#)

nchains.mcmc.list *Number of Chains*

Description

Gets the number of chains of an MCMC object.

Usage

```
## S3 method for class 'mcmc.list'  
nchains(x, ...)
```

Arguments

x An object.
... Other arguments passed to methods.

Value

An integer scalar of the number of chains.

See Also

Other MCMC dimensions: [niters\(\)](#), [npars\(\)](#), [nsams\(\)](#), [nsims\(\)](#), [nterms\(\)](#)

nchains.nlist	<i>Number of Terms</i>
---------------	------------------------

Description

Gets the number of terms of an MCMC object.

Usage

```
## S3 method for class 'nlist'  
nchains(x, ...)
```

Arguments

x	An object.
...	Other arguments passed to methods.

Details

Always 1L.

Value

A integer scalar of the number of terms.

See Also

Other MCMC dimensions: [nchains\(\)](#), [niters\(\)](#), [npars\(\)](#), [nsams\(\)](#), [nsims\(\)](#)

Examples

```
nchains(nlist(x = 1:2))
```

nchains.nlists	<i>Number of Terms</i>
----------------	------------------------

Description

Gets the number of terms of an MCMC object.

Usage

```
## S3 method for class 'nlists'  
nchains(x, ...)
```

Arguments

x	An object.
...	Other arguments passed to methods.

Value

A integer scalar of the number of terms.

See Also

Other MCMC dimensions: [nchains\(\)](#), [niters\(\)](#), [npars\(\)](#), [nsams\(\)](#), [nsims\(\)](#)

Examples

```
nchains(nlists(nlist(x = c(2, 9)), nlist(x = c(1, 7))))
nchains(split_chains(nlists(nlist(x = c(2, 9)), nlist(x = c(1, 7))))))
```

`niters.mcmc`

Number of Iterations

Description

Gets the number of iterations (in a chain) of an MCMC object.

Usage

```
## S3 method for class 'mcmc'
niters(x, ...)
```

Arguments

`x` An object.

`...` Other arguments passed to methods.

Value

An integer scalar of the number of iterations.

See Also

Other MCMC dimensions: [nchains\(\)](#), [npars\(\)](#), [nsams\(\)](#), [nsims\(\)](#), [nterms\(\)](#)

niters.mcmc.list	<i>Number of Iterations</i>
------------------	-----------------------------

Description

Gets the number of iterations (in a chain) of an MCMC object.

Usage

```
## S3 method for class 'mcmc.list'  
niters(x, ...)
```

Arguments

x	An object.
...	Other arguments passed to methods.

Value

An integer scalar of the number of iterations.

See Also

Other MCMC dimensions: [nchains\(\)](#), [npars\(\)](#), [nsams\(\)](#), [nsims\(\)](#), [nterms\(\)](#)

niters.nlist	<i>Number of Iterations</i>
--------------	-----------------------------

Description

Gets the number of iterations (in a chain) of an MCMC object.

Usage

```
## S3 method for class 'nlist'  
niters(x, ...)
```

Arguments

x	An object.
...	Other arguments passed to methods.

Details

Always 1.

Value

An integer scalar of the number of iterations.

See Also

Other MCMC dimensions: [nchains\(\)](#), [npars\(\)](#), [nsams\(\)](#), [nsims\(\)](#), [nterms\(\)](#)

Examples

```
niters(nlist(x = 1:2))
```

niters.nlists	<i>Number of Iterations</i>
---------------	-----------------------------

Description

Gets the number of iterations (in a chain) of an MCMC object.

Usage

```
## S3 method for class 'nlists'
niters(x, ...)
```

Arguments

x	An object.
...	Other arguments passed to methods.

Value

An integer scalar of the number of iterations.

See Also

Other MCMC dimensions: [nchains\(\)](#), [npars\(\)](#), [nsams\(\)](#), [nsims\(\)](#), [nterms\(\)](#)

Examples

```
niters(nlists(nlist(x = c(2, 9)), nlist(x = c(1, 7))))
```

nlist	<i>Create nlist Object</i>
-------	----------------------------

Description

Creates a [nlist_object\(\)](#) from one of more uniquely named numeric arguments.

Usage

```
nlist(...)
```

Arguments

...	Uniquely named numeric objects.
-----	---------------------------------

Details

An nlist object is an S3 class list of uniquely named numeric elements.

nlist objects are the raw data inputs for analytic engines such as JAGS, STAN and TMB.

Value

An nlist object.

See Also

[nlists\(\)](#)

Examples

```
nlist()  
nlist(x = 1)  
nlist(y = 1:4, zz = matrix(1:9, 3))
```

nlists	<i>Create nlists Object</i>
--------	-----------------------------

Description

Creates an [nlists_object\(\)](#) from one or more [nlist_object\(\)](#)s.

Usage

```
nlists(...)
```

Arguments

... nlist objects.

Details

An nlists object is a S3 class list of [nlist_object\(\)](#) elements with the same names, dimensionalities and typeofs.

nlists objects are useful for storing individual realizations of a simulated data set.

Value

An nlists object.

See Also

[nlist\(\)](#)

Examples

```
nlists()  
nlists(nlist())  
nlists(nlist(x = 1))  
nlists(nlist(x = 1), nlist(x = -3))
```

npdims.mcmc.list *Number of Parameter Dimensions*

Description

Gets the number of the dimensions of each parameter of an object.

The default methods returns the length of each element of `pdims()` as an integer vector.

Usage

```
## S3 method for class 'mcmc.list'  
npdims(x, ...)
```

Arguments

x An object.
... Other arguments passed to methods.

Value

A named integer vector of the number of dimensions of each parameter.

See Also

Other dimensions: `dims()`, `ndims()`, `pdims()`

npdims.nlist *Number of Parameter Dimensions*

Description

Gets the number of the dimensions of each parameter of an object.

The default methods returns the length of each element of `pdims()` as an integer vector.

Usage

```
## S3 method for class 'nlist'  
npdims(x, ...)
```

Arguments

x An object.
... Other arguments passed to methods.

Value

A named integer vector of the number of dimensions of each parameter.

See Also

Other dimensions: [dims\(\)](#), [ndims\(\)](#), [pdims\(\)](#)

Examples

```
npdims(nlist(x = 1:3))
npdims(nlist(y = 3, zz = matrix(2:5, 2)))
```

npdims.nlists	<i>Number of Parameter Dimensions</i>
---------------	---------------------------------------

Description

Gets the number of the dimensions of each parameter of an object.

The default methods returns the length of each element of [pdims\(\)](#) as an integer vector.

Usage

```
## S3 method for class 'nlists'
npdims(x, ...)
```

Arguments

x	An object.
...	Other arguments passed to methods.

Value

A named integer vector of the number of dimensions of each parameter.

See Also

Other dimensions: [dims\(\)](#), [ndims\(\)](#), [pdims\(\)](#)

Examples

```
npdims(nlists(nlist(x = 1:3)))
npdims(nlists(
  nlist(y = 3, zz = matrix(2:5, 2)),
  nlist(y = 5, zz = matrix(1:4, 2))
))
```

 nsims.nlist

Number of Simulations

Description

Gets the number of simulations (iterations * chains) of an MCMC object.

The default methods returns the product of [nchains\(\)](#) and [niters\(\)](#).

Usage

```
## S3 method for class 'nlist'
nsims(x, ...)
```

Arguments

x An object.
 ... Other arguments passed to methods.

Details

Always 1L.

Value

An integer scalar of the number of simulations.

See Also

Other MCMC dimensions: [nchains\(\)](#), [niters\(\)](#), [npars\(\)](#), [nsams\(\)](#), [nterms\(\)](#)

Examples

```
nsims(nlist(x = 1:2))
```

 nsims.nlists

Number of Simulations

Description

Gets the number of simulations (iterations * chains) of an MCMC object.

The default methods returns the product of [nchains\(\)](#) and [niters\(\)](#).

Usage

```
## S3 method for class 'nlists'
nsims(x, ...)
```


Arguments

x An object.
 ... Other arguments passed to methods.

Value

An integer scalar of the number of simulations.

See Also

Other MCMC dimensions: [nchains\(\)](#), [niters\(\)](#), [npars\(\)](#), [nsams\(\)](#), [nterms\(\)](#)

Examples

```
nsims(nlists(nlist(x = c(2, 9)), nlist(x = c(1, 7))))
nsims(split_chains(nlists(nlist(x = c(2, 9)), nlist(x = c(1, 7))))))
```

nterms.mcmc

Number of Terms

Description

Gets the number of terms of an MCMC object.

Usage

```
## S3 method for class 'mcmc'
nterms(x, ...)
```

Arguments

x An object.
 ... Other arguments passed to methods.

Value

A integer scalar of the number of terms.

See Also

Other MCMC dimensions: [nchains\(\)](#), [niters\(\)](#), [npars\(\)](#), [nsams\(\)](#), [nsims\(\)](#)

nterms.mcmc.list	<i>Number of Terms</i>
------------------	------------------------

Description

Gets the number of terms of an MCMC object.

Usage

```
## S3 method for class 'mcmc.list'  
nterms(x, ...)
```

Arguments

x	An object.
...	Other arguments passed to methods.

Value

A integer scalar of the number of terms.

See Also

Other MCMC dimensions: [nchains\(\)](#), [niters\(\)](#), [npars\(\)](#), [nsams\(\)](#), [nsims\(\)](#)

nterms.nlist	<i>Number of Terms</i>
--------------	------------------------

Description

Gets the number of terms of an MCMC object.

Usage

```
## S3 method for class 'nlist'  
nterms(x, ...)
```

Arguments

x	An object.
...	Other arguments passed to methods.

Value

A integer scalar of the number of terms.

See Also

Other MCMC dimensions: [nchains\(\)](#), [niters\(\)](#), [npars\(\)](#), [nsams\(\)](#), [nsims\(\)](#)

Examples

```
nterms(nlist(x = 2))
nterms(nlist(x = NA_real_))
nterms(nlist(x = 3, zz = matrix(2:5, 2)))
```

nterms.nlists	<i>Number of Terms</i>
---------------	------------------------

Description

Gets the number of terms of an MCMC object.

Usage

```
## S3 method for class 'nlists'
nterms(x, ...)
```

Arguments

x An object.
 ... Other arguments passed to methods.

Value

A integer scalar of the number of terms.

See Also

Other MCMC dimensions: [nchains\(\)](#), [niters\(\)](#), [npars\(\)](#), [nsams\(\)](#), [nsims\(\)](#)

Examples

```
nterms(nlists(nlist(x = 1:3)))
nterms(nlists(
  nlist(y = 3, zz = matrix(2:5, 2)),
  nlist(y = 5, zz = matrix(1:4, 2))
))
```

pars.mcmc	<i>Parameter Names</i>
-----------	------------------------

Description

Gets the parameter names.

Usage

```
## S3 method for class 'mcmc'
pars(x, scalar = NULL, terms = FALSE, ...)
```

Arguments

x	An object.
scalar	A logical scalar specifying whether to include all parameters (NULL), only scalars (TRUE) or all parameters except scalars (FALSE).
terms	A flag specifying whether to return the parameter name for each term element.
...	Other arguments passed to methods.

Value

A character vector of the names of the parameters.

See Also

Other parameters: [npars\(\)](#), [set_pars\(\)](#)

`pars.mcmc.list`

Parameter Names

Description

Gets the parameter names.

Usage

```
## S3 method for class 'mcmc.list'
pars(x, scalar = NULL, terms = FALSE, ...)
```

Arguments

x	An object.
scalar	A logical scalar specifying whether to include all parameters (NULL), only scalars (TRUE) or all parameters except scalars (FALSE).
terms	A flag specifying whether to return the parameter name for each term element.
...	Other arguments passed to methods.

Value

A character vector of the names of the parameters.

See Also

Other parameters: [npars\(\)](#), [set_pars\(\)](#)

pars.nlist *Parameter Names*

Description

Gets the parameter names.

Usage

```
## S3 method for class 'nlist'
pars(x, scalar = NULL, terms = FALSE, ...)
```

Arguments

x	An object.
scalar	A logical scalar specifying whether to include all parameters (NULL), only scalars (TRUE) or all parameters except scalars (FALSE).
terms	A flag specifying whether to return the parameter name for each term element.
...	Other arguments passed to methods.

Value

A character vector of the names of the parameters.

See Also

Other parameters: [npars\(\)](#), [set_pars\(\)](#)

Examples

```
pars(nlist(zz = 1, y = 3:6))
```

pars.nlists *Parameter Names*

Description

Gets the parameter names.

Usage

```
## S3 method for class 'nlists'
pars(x, scalar = NULL, terms = FALSE, ...)
```

Arguments

x	An object.
scalar	A logical scalar specifying whether to include all parameters (NULL), only scalars (TRUE) or all parameters except scalars (FALSE).
terms	A flag specifying whether to return the parameter name for each term element.
...	Other arguments passed to methods.

Value

A character vector of the names of the parameters.

See Also

Other parameters: [npars\(\)](#), [set_pars\(\)](#)

Examples

```
pars(nlists(nlist(zz = 1, y = 3:6), nlist(zz = 4, y = 13:16)))
```

pdims.mcmc

Parameter Dimensions

Description

Gets the dimensions of each parameter of an object.

Usage

```
## S3 method for class 'mcmc'
pdims(x, ...)
```

Arguments

`x` An object.
`...` Other arguments passed to methods.

Value

A named list of integer vectors of the dimensions of each parameter.

See Also

Other dimensions: [dims\(\)](#), [ndims\(\)](#), [npdims\(\)](#)

pdims.mcmc.list

Parameter Dimensions

Description

Gets the dimensions of each parameter of an object.

Usage

```
## S3 method for class 'mcmc.list'
pdims(x, ...)
```

Arguments

x An object.
... Other arguments passed to methods.

Value

A named list of integer vectors of the dimensions of each parameter.

See Also

Other dimensions: [dims\(\)](#), [ndims\(\)](#), [npdims\(\)](#)

pdims.nlist

Parameter Dimensions

Description

Gets the dimensions of each parameter of an object.

Usage

```
## S3 method for class 'nlist'  
pdims(x, ...)
```

Arguments

x An object.
... Other arguments passed to methods.

Value

A named list of integer vectors of the dimensions of each parameter.

See Also

Other dimensions: [dims\(\)](#), [ndims\(\)](#), [npdims\(\)](#)

Examples

```
pdims(nlist(x = 1:3))  
pdims(nlist(y = 3, zz = matrix(2:5, 2)))
```

pdims.nlists *Parameter Dimensions*

Description

Gets the dimensions of each parameter of an object.

Usage

```
## S3 method for class 'nlists'
pdims(x, ...)
```

Arguments

x An object.
 ... Other arguments passed to methods.

Value

A named list of integer vectors of the dimensions of each parameter.

See Also

Other dimensions: [dims\(\)](#), [ndims\(\)](#), [npdims\(\)](#)

Examples

```
pdims(nlists(nlist(x = 1:3)))
pdims(nlists(
  nlist(y = 3, zz = matrix(2:5, 2)),
  nlist(y = 5, zz = matrix(1:4, 2))
))
```

relist_nlist *Relists an unlist nlist Object*

Description

Relists an nlist object that has been unlisted to a named numeric vector. Ensures absent terms are included and preserves integer class.

Usage

```
relist_nlist(flesh, skeleton)
```

Arguments

flesh An atomic vector
 skeleton An nlist object.

Value

A numeric vector of the values in `x`.

See Also

[as_nlist.numeric\(\)](#) and [unlist_nlist\(\)](#)

Examples

```
relist_nlist(c(`a[2]` = 5), nlist(a = 1:3))
```

set_pars.mcmc

Set Parameters

Description

Sets an object's parameter names.

The assignment version `pars<-()` forwards to `set_pars()`.

Usage

```
## S3 method for class 'mcmc'  
set_pars(x, value, ...)
```

Arguments

<code>x</code>	An object.
<code>value</code>	A character vector of the new parameter names.
<code>...</code>	Other arguments passed to methods.

Details

`value` must be a unique character vector of the same length as the object's parameters.

Value

The modified object.

See Also

Other parameters: [npars\(\)](#), [pars\(\)](#)

set_pars.mcmc.list *Set Parameters*

Description

Sets an object's parameter names.

The assignment version pars<-() forwards to set_pars().

Usage

```
## S3 method for class 'mcmc.list'
set_pars(x, value, ...)
```

Arguments

x	An object.
value	A character vector of the new parameter names.
...	Other arguments passed to methods.

Details

value must be a unique character vector of the same length as the object's parameters.

Value

The modified object.

See Also

Other parameters: [npars\(\)](#), [pars\(\)](#)

set_pars.nlist *Set Parameter Names*

Description

Sets an object's parameter names.

The assignment version pars<-() forwards to set_pars().

Usage

```
## S3 method for class 'nlist'
set_pars(x, value, ...)
```

Arguments

x	An object.
value	A character vector of the new parameter names.
...	Other arguments passed to methods.

Details

value must be a unique character vector of the same length as the object's parameters.

Value

The modified object.

See Also

Other parameters: [npars\(\)](#), [pars\(\)](#)

Examples

```
nlist <- nlist(x = 1, y = 3:4)
pars(nlist) <- c("a", "b")
nlist
set_pars(nlist, c("z", "c1"))
```

set_pars.nlists	<i>Set Parameter Names</i>
-----------------	----------------------------

Description

Sets an object's parameter names.

The assignment version `pars<-()` forwards to `set_pars()`.

Usage

```
## S3 method for class 'nlists'
set_pars(x, value, ...)
```

Arguments

x	An object.
value	A character vector of the new parameter names.
...	Other arguments passed to methods.

Details

value must be a unique character vector of the same length as the object's parameters.

Value

The modified object.

See Also

Other parameters: [npars\(\)](#), [pars\(\)](#)

Examples

```
nlists <- nlists(nlist(x = 2), nlist(x = 3))
pars(nlists) <- "a"
nlists
set_pars(nlists, "zz")
```

split_chains.nlists *Split Chains*

Description

Splits each of an MCMC object's chains in half to double the number of chains and halve the number of iterations.

Usage

```
## S3 method for class 'nlists'
split_chains(x, ...)
```

Arguments

x An object.
 ... Other arguments passed to methods.

Value

The modified object.

See Also

Other MCMC manipulations: [bind_chains\(\)](#), [bind_iterations\(\)](#), [collapse_chains\(\)](#), [estimates\(\)](#)

Examples

```
nlists <- nlists(nlist(x = c(2, 9)), nlist(x = c(1, 7)))
nchains(nlists)
nchains(split_chains(nlists))
```

subset.mcmc *Subset mcmc Object*

Description

Subsets an mcmc object by its parameters and/or iterations.

Usage

```
## S3 method for class 'mcmc'
subset(x, iters = NULL, pars = NULL, iterations = NULL, parameters = NULL, ...)
```

Arguments

x	An mcmc object.
iters	An integer vector of iterations.
pars	A character vector of parameter names.
iterations	An integer vector (or NULL) of the iterations to subset by.
parameters	A character vector (or NULL) of the parameters to subset by.
...	Unused.

Details

Future versions should allow it to be reordered by its parameters.

Value

An mcmc object.

Examples

```
mcmc <- as_mcmc(nlist(beta = 1:2, theta = 1))
subset(mcmc, pars = "beta")
subset(mcmc, iters = c(1L,1L))
```

subset.mcmc.list	<i>Subset mcmc.list Object</i>
------------------	--------------------------------

Description

Subsets an mcmc.list object by its chains, parameters and/or iterations.

Usage

```
## S3 method for class 'mcmc.list'
subset(
  x,
  chains = NULL,
  iters = NULL,
  pars = NULL,
  iterations = NULL,
  parameters = NULL,
  ...
)
```

Arguments

x	An mcmc.list object.
chains	An integer vector of chains.
iters	An integer vector of iterations.
pars	A character vector of parameter names.
iterations	An integer vector (or NULL) of the iterations to subset by.
parameters	A character vector (or NULL) of the parameters to subset by.
...	Unused.

Details

Future versions should allow it to be reordered by its parameters.

Value

An mcmc.list object.

Examples

```
mcmc.list <- as_mcmc_list(nlists(nlist(beta = 1:2, theta = 1),
                                nlist(beta = 3:4, theta = -1)))
subset(mcmc.list, pars = "beta")
subset(mcmc.list, iters = c(1L,1L))
```

subset.nlist

Subset nlist Object

Description

Subsets an nlist object by its parameters.

Usage

```
## S3 method for class 'nlist'
subset(x, pars = NULL, ...)
```

Arguments

x	An nlist object.
pars	A character vector of parameter names.
...	Unused.

Details

It can also be used to reorder the parameters.

Value

An nlist object.

Examples

```
nlist <- nlist(a = 1, y = 3, x = 1:4)
subset(nlist)
subset(nlist, "a")
subset(nlist, c("x", "a"))
```

subset.nlists	<i>Subset nlists Object</i>
---------------	-----------------------------

Description

Subsets an nlists object by its parameters, chains and iterations.

Usage

```
## S3 method for class 'nlists'  
subset(x, chains = NULL, iters = NULL, pars = NULL, ...)
```

Arguments

x	An nlists object.
chains	An integer vector of chains.
iters	An integer vector of iterations.
pars	A character vector of parameter names.
...	Unused.

Details

It can also be used to reorder the parameters as well as duplicate chains and iterations.

Value

An nlists object.

Examples

```
nlists <- nlists(  
  nlist(a = 1, y = 3, x = 1:4),  
  nlist(a = 2, y = 4, x = 4:1),  
  nlist(a = 3, y = 6, x = 5:2)  
)  
subset(nlists)  
subset(nlists, pars = "a")  
subset(nlists, pars = c("x", "a"))  
subset(nlists, iters = 1L)  
subset(nlists, iters = c(2L, 2L))
```

thin.default	<i>Thin MCMC Object</i>
--------------	-------------------------

Description

Thins an MCMC object's iterations.

Usage

```
## Default S3 method:
thin(x, nthin = 1L, ...)
```

Arguments

x	An object.
nthin	A positive integer of the thinning rate.
...	Unused.

Value

The thinned MCMC object.

Examples

```
thin(nlists(nlist(x = 1), nlist(x = 2), nlist(x = 3), nlist(x = 4)), nthin = 2)
```

tidy.mcmc	<i>Turn an object into a tidy tibble</i>
-----------	--

Description

Turn an object into a tidy tibble

Usage

```
## S3 method for class 'mcmc'
tidy(x, simplify = FALSE, ...)
```

Arguments

x	An object.
simplify	A flag specifying whether to drop sd and zscore columns.
...	Unused.

Value

A `tibble::tibble()` with information about model components.

Methods

No methods found in currently loaded packages.

tidy.mcmc.list	<i>Turn an object into a tidy tibble</i>
----------------	--

Description

Turn an object into a tidy tibble

Usage

```
## S3 method for class 'mcmc.list'  
tidy(x, simplify = FALSE, ...)
```

Arguments

x	An object.
simplify	A flag specifying whether to drop sd and zscore columns.
...	Unused.

Value

A `tibble::tibble()` with information about model components.

Methods

No methods found in currently loaded packages.

tidy.nlists	<i>Turn an object into a tidy tibble</i>
-------------	--

Description

Turn an object into a tidy tibble

Usage

```
## S3 method for class 'nlists'  
tidy(x, simplify = FALSE, ...)
```

Arguments

x	An object.
simplify	A flag specifying whether to drop sd and zscore columns.
...	Unused.

Value

A `tibble::tibble()` with information about model components.

Methods

No methods found in currently loaded packages.

Examples

```
tidy(nlists(
  nlist(x = 1, y = 4:6),
  nlist(x = 3, y = 7:9)
), simplify = TRUE)
```

unlist.nlist	<i>Flatten nlist Object</i>
--------------	-----------------------------

Description

Flatten nlist Object

Usage

```
## S3 method for class 'nlist'
unlist(x, recursive = TRUE, use.names = TRUE)
```

Arguments

x	An nlist object.
recursive	Ignored.
use.names	A flag specifying whether to preserve names.

Value

A named numeric vector of the values in x.

See Also

[unlist_nlist\(\)](#)

Examples

```
unlist(nlist(y = 2, x = matrix(4:7, ncol = 2)))
```

unlist_nlist	<i>Flatten nlist Object</i>
--------------	-----------------------------

Description

Simplifies an nlist object to an named numeric vector where the names are the terms.

Usage

```
unlist_nlist(x)
```

Arguments

x An nlist object.

Value

A named numeric vector of the values in x.

See Also

[as_nlist.numeric\(\)](#) and [relist_nlist\(\)](#)

Examples

```
unlist_nlist(nlist(y = 2, x = matrix(4:7, ncol = 2)))
```

vld_nlist	<i>Validate nlist Object or nlists Object</i>
-----------	---

Description

Validate nlist Object or nlists Object

Usage

```
vld_nlist(x)
```

```
vld_nlists(x)
```

Arguments

x The object to check.

Value

A flag indicating whether the object was validated.

Functions

- vld_nlists: Validate nlists Object

Examples

```
# vld_nlist
vld_nlist(nlist(x = 1))
try(vld_nlist(list(x = 1)))

# vld_nlists
vld_nlists(nlists(nlist(x = 1)))
vld_nlists(1)
```

Index

- * **aggregate**
 - aggregate.nlist, 3
 - aggregate.nlists, 4
- * **coerce term**
 - as_term.mcmc, 9
 - as_term.nlist, 9
 - as_term.nlists, 10
 - as_term_frame, 10
 - as_term_frame.nlist, 11
 - as_term_frame.nlists, 11
- * **coerce**
 - as_nlist, 6
 - as_nlists, 8
- * **collapse**
 - collapse_chains.mcmc, 14
 - collapse_chains.nlist, 15
 - collapse_chains.nlists, 16
- * **mcmc**
 - as_mcmc, 4
 - as_mcmc_list, 5
- aggregate.nlist, 3, 4
- aggregate.nlists, 3, 4
- as.nlist(as_nlist), 6
- as.nlists(as_nlist), 6
- as_mcmc, 4, 6
- as_mcmc_list, 5, 5
- as_nlist, 6, 8
- as_nlist.numeric(), 41, 51
- as_nlists, 7, 8
- as_term.mcmc, 9, 9, 10–12
- as_term.nlist, 9, 9, 10–12
- as_term.nlists, 9, 10, 10, 11, 12
- as_term_frame, 9, 10, 10, 11, 12
- as_term_frame.nlist, 9, 10, 11, 12
- as_term_frame.nlists, 9–11, 11
- bind_chains, 12, 13, 15, 18, 44
- bind_iterations, 15, 18, 44
- bind_iterations.mcmc, 12
- bind_iterations.mcmc.list, 13
- chk_nlist, 13
- chk_nlists(chk_nlist), 13
- coda::as.mcmc(), 5
- collapse_chains, 12, 13, 18, 44
- collapse_chains.mcmc, 14, 16
- collapse_chains.mcmc.list, 15
- collapse_chains.nlist, 14, 15, 16
- collapse_chains.nlists, 14, 16, 16
- complete_terms.mcmc, 17
- dims, 30, 31, 38–40
- estimates, 12, 13, 15, 44
- estimates.nlist, 17
- estimates.nlists, 18
- fill_all, 21, 22
- fill_all.nlist, 19
- fill_all.nlists, 20
- fill_na, 19, 20
- fill_na.nlist, 21
- fill_na.nlists, 22
- is_nlist(is_numeric), 23
- is_nlists(is_numeric), 23
- is_numeric, 23
- nchains, 25–28, 32–35
- nchains(), 32
- nchains.mcmc, 24
- nchains.mcmc.list, 24
- nchains.nlist, 25
- nchains.nlists, 25
- ndims, 30, 31, 38–40
- niters, 24–26, 32–35
- niters(), 32
- niters.mcmc, 26
- niters.mcmc.list, 27
- niters.nlist, 27
- niters.nlists, 28
- nlist, 28
- nlist(), 29
- nlist-object(nlist), 28
- nlist_object(nlist), 28
- nlist_object(), 3, 4, 6, 23, 28, 29
- nlists, 29
- nlists(), 29

`nlists-object(nlists)`, 29
`nlists_object(nlists)`, 29
`nlists_object()`, 4, 8, 23, 29
`npars`, 24–28, 32–38, 41–43
`npdims`, 38–40
`npdims.mcmc.list`, 30
`npdims.nlist`, 30
`npdims.nlists`, 31
`nsams`, 24–28, 32–35
`nsims`, 24–28, 33–35
`nsims.nlist`, 32
`nsims.nlists`, 32
`nterms`, 24, 26–28, 32, 33
`nterms.mcmc`, 33
`nterms.mcmc.list`, 34
`nterms.nlist`, 34
`nterms.nlists`, 35

`pars`, 41–43
`pars.mcmc`, 35
`pars.mcmc.list`, 36
`pars.nlist`, 37
`pars.nlists`, 37
`pdims`, 30, 31
`pdims()`, 30, 31
`pdims.mcmc`, 38
`pdims.mcmc.list`, 38
`pdims.nlist`, 39
`pdims.nlists`, 40

`relist_nlist`, 40
`relist_nlist()`, 51

`set_pars`, 36–38
`set_pars.mcmc`, 41
`set_pars.mcmc.list`, 42
`set_pars.nlist`, 42
`set_pars.nlists`, 43
`split_chains`, 12, 13, 15, 18
`split_chains.nlists`, 44
`subset.mcmc`, 44
`subset.mcmc.list`, 45
`subset.nlist`, 46
`subset.nlists`, 47

`thin.default`, 48
`tibble::tibble()`, 48, 49
`tidy.mcmc`, 48
`tidy.mcmc.list`, 49
`tidy.nlists`, 49

`unlist.nlist`, 50
`unlist_nlist`, 51
`unlist_nlist()`, 41, 50
`vld_nlist`, 51
`vld_nlists(vld_nlist)`, 51