

Package ‘datamods’

February 8, 2024

Title Modules to Import and Manipulate Data in 'Shiny'

Version 1.4.4

Description 'Shiny' modules to import data into an application or 'addin' from various sources, and to manipulate them after that.

License GPL-3

URL <https://github.com/dreamRs/datamods>

BugReports <https://github.com/dreamRs/datamods/issues>

Encoding UTF-8

RoxygenNote 7.3.1

Imports data.table, htmltools, htmlwidgets, phosphoricons, reactable, readxl, rio, rlang, shiny ($\geq 1.5.0$), shinyWidgets ($\geq 0.7.3$), tibble, tools, shinybusy, writexl

Suggests bslib, jsonlite, knitr, MASS, rmarkdown, testthat, validate

VignetteBuilder knitr

Depends R (≥ 2.10)

LazyData true

NeedsCompilation no

Author Victor Perrier [aut, cre, cph],
Fanny Meyer [aut],
Samra Goumri [aut],
Zauad Shahreer Abeer [aut],
Eduard Szöcs [ctb]

Maintainer Victor Perrier <victor.perrier@dreamrs.fr>

Repository CRAN

Date/Publication 2024-02-08 06:10:02 UTC

R topics documented:

demo_edit	2
edit-data	3
filter-data	6
get_data_packages	10
i18n	11
import-copypaste	12
import-file	14
import-globalenv	16
import-goolesheets	19
import-modal	20
import-url	23
list_pkg_data	25
module-sample	25
select-group	27
show_data	29
update-variables	30
validation_ui	32
Index	36

demo_edit	<i>Customer Credit Card Information</i>
-----------	---

Description

A subset of fake customer credit card information inspired by the {charlatan} package.

Usage

```
demo_edit
```

Format

demo_edit:

A data frame with 20 rows and 6 columns:

name Customer name

job Customer job

credit_card_provider Credit card provider

credit_card_security_code Credit card security code

date_obtained Date of obtaining the credit card

contactless_card Contactless card

Source

<https://CRAN.R-project.org/package=charlatan>

`edit-data`*Shiny module to interactively edit a data.frame*

Description

The module generates different options to edit a `data.frame`: adding, deleting and modifying rows, exporting data (csv and excel), choosing editable columns, choosing mandatory columns. This module returns the edited table with the user modifications.

Usage

```
edit_data_ui(id)

edit_data_server(
  id,
  data_r = reactive(NULL),
  add = TRUE,
  update = TRUE,
  delete = TRUE,
  download_csv = TRUE,
  download_excel = TRUE,
  file_name_export = "data",
  var_edit = NULL,
  var_mandatory = NULL,
  var_labels = NULL,
  add_default_values = list(),
  n_column = 1,
  return_class = c("data.frame", "data.table", "tbl_df", "raw"),
  reactable_options = NULL,
  modal_size = c("m", "s", "l", "xl"),
  modal_easy_close = TRUE,
  callback_add = NULL,
  callback_update = NULL,
  callback_delete = NULL,
  only_callback = FALSE,
  use_notify = TRUE
)
```

Arguments

<code>id</code>	Module ID
<code>data_r</code>	<code>data_r</code> reactive function containing a <code>data.frame</code> to use in the module.
<code>add</code>	boolean, if TRUE, allows you to add a row in the table via a button at the top right.
<code>update</code>	boolean, if TRUE, allows you to modify a row of the table via a button located in the table on the row you want to edit.

<code>delete</code>	boolean, if TRUE, allows a row to be deleted from the table via a button in the table.
<code>download_csv</code>	if TRUE, allows to export the table in csv format via a download button.
<code>download_excel</code>	if TRUE, allows to export the table in excel format via a download button.
<code>file_name_export</code>	character that allows you to choose the export name of the downloaded file.
<code>var_edit</code>	vector of character which allows to choose the names of the editable columns.
<code>var_mandatory</code>	vector of character which allows to choose obligatory fields to fill.
<code>var_labels</code>	named list, where names are colnames and values are labels to be used in edit modal.
<code>add_default_values</code>	Default values to use for input control when adding new data, e.g. <code>list(my_var_text = "Default text to display")</code> .
<code>n_column</code>	Number of column in the edit modal window, must be a number that divide 12 since it use Bootstrap grid system with <code>shiny::column()</code> .
<code>return_class</code>	Class of returned data: <code>data.frame</code> , <code>data.table</code> , <code>tbl_df</code> (tibble) or <code>raw</code> .
<code>reactable_options</code>	Options passed to <code>reactable::reactable()</code> .
<code>modal_size</code>	character which allows to choose the size of the modalDialog. One of "s" for small, "m" (the default) for medium, "l" for large, or "xl" for extra large.
<code>modal_easy_close</code>	boolean If TRUE, modalDialog can be dismissed by clicking outside the dialog box, or by pressing the Escape key. If FALSE (the default), modalDialog can't be dismissed in those ways; instead it must be dismissed by clicking on a modalButton(), or from a call to <code>removeModal()</code> on the server.
<code>callback_add</code> , <code>callback_update</code> , <code>callback_delete</code>	<p>Functions to be executed just before an action (add, update or delete) is performed on the data. Functions used must be like <code>function(data, row) {...}</code> where :</p> <ul style="list-style-type: none"> • data will be the data in the table at the moment the function is called • row will contain either a new row of data (add), an updated row (update) or the row that will be deleted (delete). <p>If the return value of a callback function is not truthy (see <code>shiny::isTruthy()</code>) then the action is cancelled.</p>
<code>only_callback</code>	Only use callbacks, don't alter data within the module.
<code>use_notify</code>	Display information or not to user through <code>shinybusy::notify()</code> .

Value

the edited data. frame in reactable format with the user modifications

Examples

```

library(shiny)
library(datamods)
library(bslib)
library(reactable)

ui <- fluidPage(
  theme = bs_theme(
    version = 5
  ),
  tags$h2(i18n("Edit data"), align = "center"),
  edit_data_ui(id = "id"),
  verbatimTextOutput("result")
)

server <- function(input, output, session) {

  edited_r <- edit_data_server(
    id = "id",
    data_r = reactive(demo_edit),
    add = TRUE,
    update = TRUE,
    delete = TRUE,
    download_csv = TRUE,
    download_excel = TRUE,
    file_name_export = "datas",
    # var_edit = c("name", "job", "credit_card_provider", "credit_card_security_code"),
    var_mandatory = c("name", "job"),
    var_labels = list(
      name = "Name",
      credit_card_security_code = "Credit card security code",
      date_obtained = "Date obtained",
      contactless_card = "Contactless Card",
      credit_card_provider = "Credit card provider"
    ),
    add_default_values = list(
      name = "Please enter your name here",
      date_obtained = Sys.Date()
    ),
    n_column = 2,
    modal_size = "1",
    modal_easy_close = TRUE,
    reactable_options = list(
      defaultColDef = colDef(filterable = TRUE),
      selection = "single",
      columns = list(
        name = colDef(name = "Name", style = list(fontWeight = "bold")),
        credit_card_security_code = colDef(name = "Credit card security code"),
        date_obtained = colDef(name = "Date obtained", format = colFormat(date = TRUE)),
        contactless_card = colDef(
          name = "Contactless Card",

```

```

    cell = function(value) {
      # Render as an X mark or check mark
      if (value == FALSE) "\u274c No" else "\u2714\u270f Yes"
    },
  credit_card_provider = colDef(
    name = "Credit card provider",
    style = function(value) {
      if (value == "Mastercard") {
        color <- "#e06631"
      } else if (value == "VISA 16 digit") {
        color <- "#0c13cf"
      } else if (value == "American Express") {
        color <- "#4d8be8"
      } else if (value == "JCB 16 digit") {
        color <- "#23c45e"
      } else {
        color <- "#777"
      }
      list(color = color, fontWeight = "bold")
    }
  ),
  bordered = TRUE,
  compact = TRUE,
  searchable = TRUE,
  highlight = TRUE
)
)

output$result <- renderPrint({
  str(edited_r())
})

}

if (interactive())
  shinyApp(ui, server)

```

 filter-data

Shiny module to interactively filter a data.frame

Description

Module generate inputs to filter data.frame according column's type. Code to reproduce the filter is returned as an expression with filtered data.

Usage

```
filter_data_ui(id, show_nrow = TRUE, max_height = NULL)
```

```

filter_data_server(
  id,
  data = reactive(NULL),
  vars = reactive(NULL),
  name = reactive("data"),
  defaults = reactive(NULL),
  drop_ids = getOption("datamods.filter.drop_ids", default = TRUE),
  widget_char = c("virtualSelect", "select", "picker"),
  widget_num = c("slider", "range"),
  widget_date = c("slider", "range"),
  label_na = "NA",
  value_na = TRUE
)

```

Arguments

<code>id</code>	Module id. See <code>shiny::moduleServer()</code> .
<code>show_nrow</code>	Show number of filtered rows and total.
<code>max_height</code>	Maximum height for filters panel, useful if you have many variables to filter and limited space.
<code>data</code>	<code>shiny::reactive()</code> function returning a data.frame to filter.
<code>vars</code>	<code>shiny::reactive()</code> function returning a character vector of variables for which to add a filter. If a named list, names are used as labels.
<code>name</code>	<code>shiny::reactive()</code> function returning a character string representing data name, only used for code generated.
<code>defaults</code>	<code>shiny::reactive()</code> function returning a named list of variable:value pairs which will be used to set the filters.
<code>drop_ids</code>	Drop columns containing more than 90% of unique values, or than 50 distinct values. Use FALSE to disable or use <code>list(p = 0.9, n = 50)</code> to customize threshold values.
<code>widget_char</code>	Widget to use for character variables: <code>shinyWidgets::pickerInput()</code> or <code>shiny::selectInput()</code> (default).
<code>widget_num</code>	Widget to use for numeric variables: <code>shinyWidgets::numericRangeInput()</code> or <code>shiny::sliderInput()</code> (default).
<code>widget_date</code>	Widget to use for date/time variables: <code>shiny::dateRangeInput()</code> or <code>shiny::sliderInput()</code> (default).
<code>label_na</code>	Label for missing value widget.
<code>value_na</code>	Default value for all NA's filters.

Value

- UI: HTML tags that can be included in shiny's UI
- Server: a list with four slots:
 - **filtered**: a reactive function returning the data filtered.
 - **code**: a reactive function returning the dplyr pipeline to filter data.

- **expr**: a reactive function returning an expression to filter data.
- **values**: a reactive function returning a named list of variables and filter values.

Examples

```

library(shiny)
library(shinyWidgets)
library(datamods)
library(MASS)

# Add some NAs to mpg
mtcars_na <- mtcars
mtcars_na[] <- lapply(
  X = mtcars_na,
  FUN = function(x) {
    x[sample.int(n = length(x), size = sample(5:10, 1))] <- NA
    x
  }
)

datetime <- data.frame(
  date = seq(Sys.Date(), by = "day", length.out = 300),
  datetime = seq(Sys.time(), by = "hour", length.out = 300),
  num = sample.int(1e5, 300)
)

one_column_numeric <- data.frame(
  var1 = rnorm(100)
)

ui <- fluidPage(
  tags$h2("Filter data.frame"),
  actionButton("saveFilterButton", "Save Filter Values"),
  actionButton("loadFilterButton", "Load Filter Values"),
  radioButtons(
    inputId = "dataset",
    label = "Data:",
    choices = c(
      "iris",
      "mtcars",
      "mtcars_na",
      "Cars93",
      "datetime",
      "one_column_numeric"
    )
  ),
  inline = TRUE
),

fluidRow(
  column(
    width = 3,
    filter_data_ui("filtering", max_height = "500px")
  )
),

```



```

column(
  width = 9,
  progressBar(
    id = "pbar", value = 100,
    total = 100, display_pct = TRUE
  ),
  reactable::reactableOutput(outputId = "table"),
  tags$b("Code dplyr:"),
  verbatimTextOutput(outputId = "code_dplyr"),
  tags$b("Expression:"),
  verbatimTextOutput(outputId = "code"),
  tags$b("Filtered data:"),
  verbatimTextOutput(outputId = "res_str")
)
)
)

server <- function(input, output, session) {
  savedFilterValues <- reactiveVal()
  data <- reactive({
    get(input$dataset)
  })

  vars <- reactive({
    if (identical(input$dataset, "mtcars")) {
      setNames(as.list(names(mtcars)[1:5]), c(
        "Miles/(US) gallon",
        "Number of cylinders",
        "Displacement (cu.in.)",
        "Gross horsepower",
        "Rear axle ratio"
      ))
    } else {
      NULL
    }
  })

  observeEvent(input$saveFilterButton,{
    savedFilterValues <<- res_filter$values()
  },ignoreInit = T)

  defaults <- reactive({
    input$loadFilterButton
    savedFilterValues
  })

  res_filter <- filter_data_server(
    id = "filtering",
    data = data,
    name = reactive(input$dataset),
    vars = vars,
    defaults = defaults,
    widget_num = "slider",

```

```
    widget_date = "slider",
    label_na = "Missing"
  )

  observeEvent(res_filter$filtered(), {
    updateProgressBar(
      session = session, id = "pbar",
      value = nrow(res_filter$filtered()), total = nrow(data())
    )
  })

  output$table <- reactable::renderReactable({
    reactable::reactable(res_filter$filtered())
  })

  output$code_dplyr <- renderPrint({
    res_filter$code()
  })
  output$code <- renderPrint({
    res_filter$expr()
  })

  output$res_str <- renderPrint({
    str(res_filter$filtered())
  })
}

if (interactive())
  shinyApp(ui, server)
```

get_data_packages *Get packages containing datasets*

Description

Get packages containing datasets

Usage

```
get_data_packages()
```

Value

a character vector of packages names

Examples

```
if (interactive()) {  
  get_data_packages()  
}
```

i18n

Internationalization

Description

Simple mechanism to translate labels in a Shiny application.

Usage

```
i18n(x, translations = i18n_translations())  
  
i18n_translations(package = packageName(parent.frame(2)))  
  
set_i18n(value, packages = c("datamods", "esquisse"))
```

Arguments

x	Label to translate.
translations	Either a list or a data.frame with translations.
package	Name of the package where the function is called, use NULL outside a package. It will retrieve option "i18n.<PACKAGE>" (or "i18n" if no package) to returns appropriate labels.
value	Value to set for translation. Can be: <ul style="list-style-type: none">• single character to use a supported language ("fr", "mk", "al", "pt" for esquisse and datamods packages).• a list with labels as names and translations as values.• a data.frame with 2 column: label & translation.• path to a CSV file with same structure as for data.frame above.
packages	Name of packages for which to set i18n, default to esquisse and datamods

Value

i18n() returns a character, i18n_translations() returns a list or a data.frame.

Examples

```

library(datamods)

# Use with an objet
my.translations <- list(
  "Hello" = "Bonjour"
)
i18n("Hello", my.translations)

# Use with options()
options("i18n" = list(
  "Hello" = "Bonjour"
))
i18n("Hello")

# With a package
options("datamods.i18n" = "fr")
i18n("Browse...", translations = i18n_translations("datamods"))
# If you call i18n() from within a function of your package
# you don't need second argument, e.g.:
# i18n("Browse...")

```

import-copypaste

Import data with copy & paste

Description

Let the user copy data from Excel or text file then paste it into a text area to import it.

Usage

```

import_copypaste_ui(id, title = TRUE, name_field = TRUE)

import_copypaste_server(
  id,
  btn_show_data = TRUE,
  show_data_in = c("popup", "modal"),
  trigger_return = c("button", "change"),
  return_class = c("data.frame", "data.table", "tbl_df", "raw"),
  reset = reactive(NULL),
  fread_args = list()
)

```

Arguments

<code>id</code>	Module's ID.
<code>title</code>	Module's title, if TRUE use the default title, use NULL for no title or a shiny.tag for a custom one.

<code>name_field</code>	Show or not a field to add a name to data (that is returned server-side).
<code>btn_show_data</code>	Display or not a button to display data in a modal window if import is successful.
<code>show_data_in</code>	Where to display data: in a "popup" or in a "modal" window.
<code>trigger_return</code>	When to update selected data: "button" (when user click on button) or "change" (each time user select a dataset in the list).
<code>return_class</code>	Class of returned data: <code>data.frame</code> , <code>data.table</code> , <code>tbl_df</code> (tibble) or <code>raw</code> .
<code>reset</code>	A reactive function that when triggered resets the data.
<code>fread_args</code>	list of additional arguments to pass to <code>data.table::fread()</code> when reading data.

Value

- UI: HTML tags that can be included in shiny's UI
- Server: a list with three slots:
 - **status**: a reactive function returning the status: NULL, error or success.
 - **name**: a reactive function returning the name of the imported data as character.
 - **data**: a reactive function returning the imported data. frame.

Examples

```
library(shiny)
library(datamods)

ui <- fluidPage(
  tags$h3("Import data with copy & paste"),
  fluidRow(
    column(
      width = 4,
      import_copypaste_ui("myid")
    ),
    column(
      width = 8,
      tags$b("Import status:"),
      verbatimTextOutput(outputId = "status"),
      tags$b("Name:"),
      verbatimTextOutput(outputId = "name"),
      tags$b("Data:"),
      verbatimTextOutput(outputId = "data")
    )
  )
)

server <- function(input, output, session) {

  imported <- import_copypaste_server("myid")

  output$status <- renderPrint({
    imported$status()
  })
}
```

```

    })
    output$name <- renderPrint({
      imported$name()
    })
    output$data <- renderPrint({
      imported$data()
    })
  }

  if (interactive())
    shinyApp(ui, server)

```

import-file

Import data from a file

Description

Let user upload a file and import data

Usage

```

import_file_ui(
  id,
  title = TRUE,
  preview_data = TRUE,
  file_extensions = c(".csv", ".txt", ".xls", ".xlsx", ".rds", ".fst", ".sas7bdat",
    ".sav")
)

import_file_server(
  id,
  btn_show_data = TRUE,
  show_data_in = c("popup", "modal"),
  trigger_return = c("button", "change"),
  return_class = c("data.frame", "data.table", "tbl_df", "raw"),
  reset = reactive(NULL),
  read_fns = list()
)

```

Arguments

<code>id</code>	Module's ID.
<code>title</code>	Module's title, if TRUE use the default title, use NULL for no title or a shiny.tag for a custom one.
<code>preview_data</code>	Show or not a preview of the data under the file input.
<code>file_extensions</code>	File extensions accepted by <code>shiny::fileInput()</code> , can also be MIME type.

btn_show_data	Display or not a button to display data in a modal window if import is successful.
show_data_in	Where to display data: in a "popup" or in a "modal" window.
trigger_return	When to update selected data: "button" (when user click on button) or "change" (each time user select a dataset in the list).
return_class	Class of returned data: <code>data.frame</code> , <code>data.table</code> , <code>tbl_df</code> (tibble) or <code>raw</code> .
reset	A reactive function that when triggered resets the data.
read_fns	Named list with custom function(s) to read data: <ul style="list-style-type: none"> • the name must be the extension of the files to which the function will be applied • the value must be a function that can have 5 arguments (you can ignore some of them, but you have to use the same names), passed by user through the interface: <ul style="list-style-type: none"> – <code>file</code>: path to the file – <code>sheet</code>: for Excel files, sheet to read – <code>skip</code>: number of row to skip – <code>dec</code>: decimal separator – <code>encoding</code>: file encoding – <code>na.strings</code>: character(s) to interpret as missing values.

Value

- UI: HTML tags that can be included in shiny's UI
- Server: a list with three slots:
 - **status**: a reactive function returning the status: `NULL`, `error` or `success`.
 - **name**: a reactive function returning the name of the imported data as character.
 - **data**: a reactive function returning the imported `data.frame`.

Examples

```
library(shiny)
library(datamods)

ui <- fluidPage(
  tags$h3("Import data from a file"),
  fluidRow(
    column(
      width = 4,
      import_file_ui(
        id = "myid",
        file_extensions = c(".csv", ".txt", ".xls", ".xlsx", ".json")
      )
    ),
    column(
      width = 8,
```

```

      tags$b("Import status:"),
      verbatimTextOutput(outputId = "status"),
      tags$b("Name:"),
      verbatimTextOutput(outputId = "name"),
      tags$b("Data:"),
      verbatimTextOutput(outputId = "data")
    )
  )
)

server <- function(input, output, session) {

  imported <- import_file_server(
    id = "myid",
    # Custom functions to read data
    read_fns = list(
      xls = function(file, sheet, skip, encoding) {
        readxl::read_xls(path = file, sheet = sheet, skip = skip)
      },
      json = function(file) {
        jsonlite::read_json(file, simplifyVector = TRUE)
      }
    ),
    show_data_in = "modal"
  )

  output$status <- renderPrint({
    imported$status()
  })
  output$name <- renderPrint({
    imported$name()
  })
  output$data <- renderPrint({
    imported$data()
  })
}

if (interactive())
  shinyApp(ui, server)

```

Description

Let the user select a dataset from its own environment or from a package's environment.

Usage

```
import_globalenv_ui(
  id,
  globalenv = TRUE,
  packages = get_data_packages(),
  title = TRUE
)

import_globalenv_server(
  id,
  btn_show_data = TRUE,
  show_data_in = c("popup", "modal"),
  trigger_return = c("button", "change"),
  return_class = c("data.frame", "data.table", "tbl_df", "raw"),
  reset = reactive(NULL)
)
```

Arguments

<code>id</code>	Module's ID.
<code>globalenv</code>	Search for data in Global environment.
<code>packages</code>	Name of packages in which to search data.
<code>title</code>	Module's title, if TRUE use the default title, use NULL for no title or a shiny.tag for a custom one.
<code>btn_show_data</code>	Display or not a button to display data in a modal window if import is successful.
<code>show_data_in</code>	Where to display data: in a "popup" or in a "modal" window.
<code>trigger_return</code>	When to update selected data: "button" (when user click on button) or "change" (each time user select a dataset in the list).
<code>return_class</code>	Class of returned data: data.frame, data.table, tbl_df (tibble) or raw.
<code>reset</code>	A reactive function that when triggered resets the data.

Value

- UI: HTML tags that can be included in shiny's UI
- Server: a list with three slots:
 - **status**: a reactive function returning the status: NULL, error or success.
 - **name**: a reactive function returning the name of the imported data as character.
 - **data**: a reactive function returning the imported data.frame.

Examples

```
if (interactive()) {
  library(shiny)
  library(datamods)

  # Create some data.frames
```

```
my_df <- data.frame(
  variable1 = sample(letters, 20, TRUE),
  variable2 = sample(1:100, 20, TRUE)
)

results_analysis <- data.frame(
  id = sample(letters, 20, TRUE),
  measure = sample(1:100, 20, TRUE),
  response = sample(1:100, 20, TRUE)
)

# Application

ui <- fluidPage(
  fluidRow(
    column(
      width = 4,
      import_globalenv_ui("myid")
    ),
    column(
      width = 8,
      tags$b("Import status:"),
      verbatimTextOutput(outputId = "status"),
      tags$b("Name:"),
      verbatimTextOutput(outputId = "name"),
      tags$b("Data:"),
      verbatimTextOutput(outputId = "data")
    )
  )
)

server <- function(input, output, session) {

  imported <- import_globalenv_server("myid")

  output$status <- renderPrint({
    imported$status()
  })
  output$name <- renderPrint({
    imported$name()
  })
  output$data <- renderPrint({
    imported$data()
  })

}

shinyApp(ui, server)
}
```

import-googlesheets *Import data from Google sheet*

Description

Let user paste link to a Google sheet then import the data.

Usage

```
import_googlesheets_ui(id, title = TRUE)

import_googlesheets_server(
  id,
  btn_show_data = TRUE,
  show_data_in = c("popup", "modal"),
  trigger_return = c("button", "change"),
  return_class = c("data.frame", "data.table", "tbl_df", "raw"),
  reset = reactive(NULL)
)
```

Arguments

<code>id</code>	Module's ID.
<code>title</code>	Module's title, if TRUE use the default title, use NULL for no title or a shiny.tag for a custom one.
<code>btn_show_data</code>	Display or not a button to display data in a modal window if import is successful.
<code>show_data_in</code>	Where to display data: in a "popup" or in a "modal" window.
<code>trigger_return</code>	When to update selected data: "button" (when user click on button) or "change" (each time user select a dataset in the list).
<code>return_class</code>	Class of returned data: data.frame, data.table, tbl_df (tibble) or raw.
<code>reset</code>	A reactive function that when triggered resets the data.

Value

- UI: HTML tags that can be included in shiny's UI
- Server: a list with three slots:
 - **status**: a reactive function returning the status: NULL, error or success.
 - **name**: a reactive function returning the name of the imported data as character.
 - **data**: a reactive function returning the imported data.frame.

Examples

```
library(shiny)
library(datamods)

ui <- fluidPage(
  tags$h3("Import data from Googlesheets"),
  fluidRow(
    column(
      width = 4,
      import_googlesheets_ui("myid")
    ),
    column(
      width = 8,
      tags$b("Import status:"),
      verbatimTextOutput(outputId = "status"),
      tags$b("Name:"),
      verbatimTextOutput(outputId = "name"),
      tags$b("Data:"),
      verbatimTextOutput(outputId = "data")
    )
  )
)

server <- function(input, output, session) {

  imported <- import_googlesheets_server("myid")

  output$status <- renderPrint({
    imported$status()
  })
  output$name <- renderPrint({
    imported$name()
  })
  output$data <- renderPrint({
    imported$data()
  })

}

if (interactive())
  shinyApp(ui, server)
```

Description

Wrap all import modules into one, can be displayed inline or in a modal window..

Usage

```

import_ui(
  id,
  from = c("env", "file", "copypaste", "googlesheets", "url"),
  file_extensions = c(".csv", ".txt", ".xls", ".xlsx", ".rds", ".fst", ".sas7bdat",
    ".sav")
)

import_server(
  id,
  validation_opts = NULL,
  allowed_status = c("OK", "Failed", "Error"),
  return_class = c("data.frame", "data.table", "tbl_df", "raw"),
  read_fns = list()
)

import_modal(
  id,
  from,
  title = "Import data",
  size = "l",
  file_extensions = c(".csv", ".txt", ".xls", ".xlsx", ".rds", ".fst", ".sas7bdat",
    ".sav")
)

```

Arguments

<code>id</code>	Module's id
<code>from</code>	The <code>import_ui</code> & server to use, i.e. the method. There are 5 options to choose from. ("env", "file", "copypaste", "googlesheets", "url")
<code>file_extensions</code>	File extensions accepted by <code>shiny::fileInput()</code> , can also be MIME type.
<code>validation_opts</code>	list of arguments passed to <code>[validation_server()]</code> .
<code>allowed_status</code>	Vector of statuses allowed to confirm dataset imported, if you want that all validation rules are successful before importing data use <code>allowed_status = "OK"</code> .
<code>return_class</code>	Class of returned data: <code>data.frame</code> , <code>data.table</code> , <code>tbl_df</code> (tibble) or <code>raw</code> .
<code>read_fns</code>	Named list with custom function(s) to read data: <ul style="list-style-type: none"> • the name must be the extension of the files to which the function will be applied • the value must be a function that can have 5 arguments (you can ignore some of them, but you have to use the same names), passed by user through the interface: <ul style="list-style-type: none"> – <code>file</code>: path to the file – <code>sheet</code>: for Excel files, sheet to read – <code>skip</code>: number of row to skip

- `dec`: decimal separator
- `encoding`: file encoding
- `na.strings`: character(s) to interpret as missing values.

`title` Modal window title.

`size` Modal window size, default to "l" (large).

Value

- UI: HTML tags that can be included in shiny's UI
- Server: a list with three slots:
 - **status**: a reactive function returning the status: NULL, error or success.
 - **name**: a reactive function returning the name of the imported data as character.
 - **data**: a reactive function returning the imported data . frame.

Examples

```
library(shiny)
library(datamods)

ui <- fluidPage(
  # Try with different Bootstrap version
  # theme = bslib::bs_theme(version = 4),
  fluidRow(
    column(
      width = 4,
      checkboxGroupInput(
        inputId = "from",
        label = "From",
        choices = c("env", "file", "copypaste", "googlesheets", "url"),
        selected = c("file", "copypaste")
      ),
      actionButton("launch_modal", "Launch modal window")
    ),
    column(
      width = 8,
      tags$b("Imported data:"),
      verbatimTextOutput(outputId = "name"),
      verbatimTextOutput(outputId = "data")
    )
  )
)

server <- function(input, output, session) {

  observeEvent(input$launch_modal, {
    req(input$from)
    import_modal(
      id = "myid",
      from = input$from,
```

```

        title = "Import data to be used in application"
      )
    })

imported <- import_server("myid", return_class = "tbl_df")

output$name <- renderPrint({
  req(imported$name())
  imported$name()
})

output$data <- renderPrint({
  req(imported$data())
  imported$data()
})
}

if (interactive())
  shinyApp(ui, server)

```

import-url

Import data from a URL

Description

Let user paste link to a JSON then import the data.

Usage

```

import_url_ui(id, title = TRUE)

import_url_server(
  id,
  btn_show_data = TRUE,
  show_data_in = c("popup", "modal"),
  trigger_return = c("button", "change"),
  return_class = c("data.frame", "data.table", "tbl_df", "raw"),
  reset = reactive(NULL)
)

```

Arguments

id	Module's ID.
title	Module's title, if TRUE use the default title, use NULL for no title or a shiny.tag for a custom one.
btn_show_data	Display or not a button to display data in a modal window if import is successful.
show_data_in	Where to display data: in a "popup" or in a "modal" window.

trigger_return	When to update selected data: "button" (when user click on button) or "change" (each time user select a dataset in the list).
return_class	Class of returned data: data.frame, data.table, tbl_df (tibble) or raw.
reset	A reactive function that when triggered resets the data.

Value

- UI: HTML tags that can be included in shiny's UI
- Server: a list with three slots:
 - **status**: a reactive function returning the status: NULL, error or success.
 - **name**: a reactive function returning the name of the imported data as character.
 - **data**: a reactive function returning the imported data.frame.

Examples

```
library(shiny)
library(datamods)

ui <- fluidPage(
  tags$h3("Import data from URL"),
  fluidRow(
    column(
      width = 4,
      import_url_ui("myid")
    ),
    column(
      width = 8,
      tags$b("Import status:"),
      verbatimTextOutput(outputId = "status"),
      tags$b("Name:"),
      verbatimTextOutput(outputId = "name"),
      tags$b("Data:"),
      verbatimTextOutput(outputId = "data")
    )
  )
)

server <- function(input, output, session) {

  imported <- import_url_server(
    "myid",
    btn_show_data = FALSE,
    return_class = "raw"
  )

  output$status <- renderPrint({
    imported$status()
  })
  output$name <- renderPrint({
```



```
    imported$name()
  })
  output$data <- renderPrint({
    imported$data()
  })
}

if (interactive())
  shinyApp(ui, server)
```

list_pkg_data	<i>List dataset contained in a package</i>
---------------	--

Description

List dataset contained in a package

Usage

```
list_pkg_data(pkg)
```

Arguments

pkg Name of the package, must be installed.

Value

a character vector or NULL.

Examples

```
list_pkg_data("ggplot2")
```

module-sample	<i>Shiny module to interactively sample a data.frame</i>
---------------	--

Description

Allow to take a sample of data.frame for a given number or proportion of rows to keep.

Usage

```
sample_ui(id)

sample_server(id, data_r = reactive(NULL))
```

Arguments

`id` Module id. See `shiny::moduleServer()`.
`data_r` reactive containing a `data.frame` to use in the module.

Value

- UI: HTML tags that can be included in shiny's UI
- Server: a reactive function with the sampled data.

Examples

```
library(shiny)
library(reactable)

##### ui.R #####

ui <- fluidPage(
  titlePanel("Sampling"),
  fluidRow(
    column(
      width = 4,
      sample_ui("myID")
    ),
    column(
      width = 8,
      reactableOutput("table")
    )
  )
)

##### server.R #####

server <- function(input, output, session) {
  result_sample <- sample_server("myID", reactive(iris))

  output$table <- renderReactable({
    table_sample <- reactable(
      data = result_sample(),
      defaultColDef = colDef(
        align = "center"
      ),
      borderless = TRUE,
      highlight = TRUE,
      striped = TRUE
    )
  })
  return(table_sample)
}
```

```

    })
  }

  if (interactive())
    shinyApp(ui, server)

```

 select-group

Select Group Input Module

Description

Group of mutually dependent select menus for filtering `data.frame`'s columns (like in Excel).

Usage

```

select_group_ui(
  id,
  params,
  label = NULL,
  btn_reset_label = "Reset filters",
  inline = TRUE,
  vs_args = list()
)

select_group_server(id, data_r, vars_r)

```

Arguments

<code>id</code>	Module's id.
<code>params</code>	A list of parameters passed to each <code>shinyWidgets::virtualSelectInput()</code> , you can use : <ul style="list-style-type: none"> • <code>inputId</code>: mandatory, must correspond to variable name. • <code>label</code>: Display label for the control. • <code>placeholder</code>: Text to show when no options selected.
<code>label</code>	Character, global label on top of all labels.
<code>btn_reset_label</code>	Character, reset button label. If <code>NULL</code> no button is added.
<code>inline</code>	If <code>TRUE</code> (the default), select menus are horizontally positioned, otherwise vertically.
<code>vs_args</code>	Arguments passed to all <code>shinyWidgets::virtualSelectInput()</code> created.
<code>data_r</code>	Either a <code>data.frame()</code> or a <code>shiny::reactive()</code> function returning a <code>data.frame</code> (do not use parentheses).
<code>vars_r</code>	character, columns to use to create filters, must correspond to variables listed in <code>params</code> . Can be a <code>shiny::reactive()</code> function, but values must be included in the initial ones (in <code>params</code>).

Value

A `shiny::reactive()` function containing data filtered with an attribute inputs containing a named list of selected inputs.

Examples

```
# Default -----

library(shiny)
library(datamods)
library(shinyWidgets)

ui <- fluidPage(
  # theme = bslib::bs_theme(version = 5L),
  fluidRow(
    column(
      width = 10, offset = 1,
      tags$h3("Filter data with select group module"),
      shinyWidgets::panel(
        select_group_ui(
          id = "my-filters",
          params = list(
            list(inputId = "Manufacturer", label = "Manufacturer:"),
            list(inputId = "Type", label = "Type:"),
            list(inputId = "AirBags", label = "AirBags:"),
            list(inputId = "DriveTrain", label = "DriveTrain:")
          )
        ),
        status = "primary"
      ),
      reactable::reactableOutput(outputId = "table"),
      tags$b("Inputs values:"),
      verbatimTextOutput("inputs")
    )
  )
)

server <- function(input, output, session) {
  res_mod <- select_group_server(
    id = "my-filters",
    data = reactive(MASS::Cars93),
    vars = reactive(c("Manufacturer", "Type", "AirBags", "DriveTrain"))
  )

  output$table <- reactable::renderReactable({
    reactable::reactable(res_mod())
  })

  output$inputs <- renderPrint({
    attr(res_mod(), "inputs")
  })
}
```

```
}  
  
if (interactive())  
  shinyApp(ui, server)
```

show_data	<i>Display a table in a window</i>
-----------	------------------------------------

Description

Display a table in a window

Usage

```
show_data(  
  data,  
  title = NULL,  
  options = NULL,  
  show_classes = TRUE,  
  type = c("popup", "modal"),  
  width = "80%"  
)
```

Arguments

data	a data object (either a matrix or a data.frame).
title	Title to be displayed in window.
options	Arguments passed to <code>reactable::reactable()</code> .
show_classes	Show variables classes under variables names in table header.
type	Display table in a pop-up or in modal window.
width	Width of the window, only used if type = "popup".

Value

No value.

Examples

```
library(shiny)  
library(datamods)  
  
ui <- fluidPage(  
  actionButton(  
    inputId = "show1",  
    label = "Show data in popup",  
    icon = icon("eye")
```

```

    ),
    actionButton(
      inputId = "show2",
      label = "Show data in modal",
      icon = icon("eye")
    ),
    actionButton(
      inputId = "show3",
      label = "Show data without classes",
      icon = icon("eye")
    )
  )
)

server <- function(input, output, session) {
  observeEvent(input$show1, {
    show_data(mtcars, title = "My data")
  })
  observeEvent(input$show2, {
    show_data(mtcars, title = "My data", type = "modal")
  })
  observeEvent(input$show3, {
    show_data(
      data = mtcars,
      title = "My data",
      show_classes = FALSE,
      options = list(searchable = TRUE, highlight = TRUE)
    )
  })
}

if (interactive())
  shinyApp(ui, server)

```

 update-variables

Select, rename and convert variables

Description

Select, rename and convert variables

Usage

```
update_variables_ui(id, title = TRUE)
```

```
update_variables_server(id, data, height = NULL)
```

Arguments

`id` Module's ID

title	Module's title, if TRUE use the default title, use NULL for no title or a shiny.tag for a custom one.
data	a data.frame or a reactive function returning a data.frame.
height	Height for the table.

Value

A reactive function returning the updated data.

Examples

```
library(shiny)
library(datamods)

testdata <- data.frame(
  date_as_char = as.character(Sys.Date() + 0:9),
  date_as_num = as.numeric(Sys.Date() + 0:9),
  datetime_as_char = as.character(Sys.time() + 0:9 * 3600*24),
  datetime_as_num = as.numeric(Sys.time() + 0:9 * 3600*24),
  num_as_char = as.character(1:10),
  char = month.name[1:10],
  char_na = c("A", "A", "B", NA, "B", "A", NA, "B", "A", "B"),
  stringsAsFactors = FALSE
)

ui <- fluidPage(
  tags$h3("Select, rename and convert variables"),
  fluidRow(
    column(
      width = 6,
      # radioButtons()
      update_variables_ui("vars")
    ),
    column(
      width = 6,
      tags$b("original data:"),
      verbatimTextOutput("original"),
      verbatimTextOutput("original_str"),
      tags$b("Modified data:"),
      verbatimTextOutput("modified"),
      verbatimTextOutput("modified_str")
    )
  )
)

server <- function(input, output, session) {

  updated_data <- update_variables_server(
    id = "vars",
    data = reactive(testdata)
  )
}
```

```

output$original <- renderPrint({
  testdata
})
output$original_str <- renderPrint({
  str(testdata)
})

output$modified <- renderPrint({
  updated_data()
})
output$modified_str <- renderPrint({
  str(updated_data())
})
}

if (interactive())
  shinyApp(ui, server)

```

validation_ui

Validation module

Description

Check that a dataset respect some validation expectations.

Usage

```
validation_ui(id, display = c("dropdown", "inline"), max_height = NULL, ...)
```

```

validation_server(
  id,
  data,
  n_row = NULL,
  n_col = NULL,
  n_row_label = "Valid number of rows",
  n_col_label = "Valid number of columns",
  btn_label = "Dataset validation:",
  rules = NULL,
  bs_version = 3
)

```

Arguments

id	Module's ID.
display	Display validation results in a dropdown menu by clicking on a button or display results directly in interface.
max_height	Maximum height for validation results element, useful if you have many rules.

...	Arguments passed to <code>actionButton</code> or <code>uiOutput</code> depending on display mode, you cannot use <code>inputId/outputId</code> , <code>label</code> or <code>icon</code> (button only).
<code>data</code>	a reactive function returning a <code>data.frame</code> .
<code>n_row</code> , <code>n_col</code>	A one-sided formula to check number of rows and columns respectively, see below for examples.
<code>n_row_label</code> , <code>n_col_label</code>	Text to be displayed with the result of the check for number of rows/columns.
<code>btn_label</code>	Label for the dropdown button, will be followed by validation result.
<code>rules</code>	An object of class <code>validator</code> created with <code>validate::validator</code> .
<code>bs_version</code>	Bootstrap version used, it may affect rendering, especially status badges.

Value

- UI: HTML tags that can be included in shiny's UI
- Server: a list with two slots:
 - **status**: a reactive function returning the best status available between "OK", "Failed" or "Error".
 - **details**: a reactive function returning a list with validation details.

Examples

```
library(datamods)
library(shiny)

if (requireNamespace("validate")) {
  library(validate)

  # Define some rules to be applied to data
  myrules <- validator(
    is.character(Manufacturer) | is.factor(Manufacturer),
    is.numeric(Price),
    Price > 12, # we should use 0 for testing positivity, but that's for the example
    !is.na(Luggage.room),
    in_range(Cylinders, min = 4, max = 8),
    Man.trans.avail %in% c("Yes", "No")
  )
  # Add some labels
  label(myrules) <- c(
    "Variable Manufacturer must be character",
    "Variable Price must be numeric",
    "Variable Price must be strictly positive",
    "Luggage.room must not contain any missing values",
    "Cylinders must be between 4 and 8",
    "Man.trans.avail must be 'Yes' or 'No'"
  )
  # you can also add a description()

  ui <- fluidPage(
    tags$h2("Validation"),
```

```

fluidRow(
  column(
    width = 4,
    radioButtons(
      inputId = "dataset",
      label = "Choose dataset:",
      choices = c("mtcars", "MASS::Cars93")
    ),
    tags$p("Dropdown example:"),
    validation_ui("validation1"),

    tags$br(),

    tags$p("Inline example:"),
    validation_ui("validation2", display = "inline")
  ),
  column(
    width = 8,
    tags$b("Status:"),
    verbatimTextOutput("status"),
    tags$b("Details:"),
    verbatimTextOutput("details")
  )
)
)

server <- function(input, output, session) {

  dataset <- reactive({
    if (input$dataset == "mtcars") {
      mtcars
    } else {
      MASS::Cars93
    }
  })

  results <- validation_server(
    id = "validation1",
    data = dataset,
    n_row = ~ . > 20, # more than 20 rows
    n_col = ~ . >= 3, # at least 3 columns
    rules = myrules
  )

  validation_server(
    id = "validation2",
    data = dataset,
    n_row = ~ . > 20, # more than 20 rows
    n_col = ~ . >= 3, # at least 3 columns
    rules = myrules
  )

  output$status <- renderPrint(results$status())
}

```

```
    output$details <- renderPrint(results$details())  
  }  
  
  if (interactive())  
    shinyApp(ui, server)  
}
```

Index

- * **datasets**
 - demo_edit, 2
- data.frame(), 27
- data.table::fread(), 13
- demo_edit, 2

- edit-data, 3
- edit_data_server (edit-data), 3
- edit_data_ui (edit-data), 3

- filter-data, 6
- filter_data_server (filter-data), 6
- filter_data_ui (filter-data), 6

- get_data_packages, 10

- i18n, 11
- i18n_translations (i18n), 11
- import-copypaste, 12
- import-file, 14
- import-globalenv, 16
- import-goolesheets, 19
- import-modal, 20
- import-url, 23
- import_copypaste_server
 - (import-copypaste), 12
- import_copypaste_ui (import-copypaste), 12
- import_file_server (import-file), 14
- import_file_ui (import-file), 14
- import_globalenv_server
 - (import-globalenv), 16
- import_globalenv_ui (import-globalenv), 16
- import_goolesheets_server
 - (import-goolesheets), 19
- import_goolesheets_ui
 - (import-goolesheets), 19
- import_modal (import-modal), 20
- import_server (import-modal), 20

- import_ui (import-modal), 20
- import_url_server (import-url), 23
- import_url_ui (import-url), 23

- list_pkg_data, 25

- module-sample, 25

- reactable::reactable(), 4, 29

- sample_server (module-sample), 25
- sample_ui (module-sample), 25
- select-group, 27
- select_group_server (select-group), 27
- select_group_ui (select-group), 27
- set_i18n (i18n), 11
- shiny::column(), 4
- shiny::dateRangeInput(), 7
- shiny::fileInput(), 14, 21
- shiny::isTruthy(), 4
- shiny::moduleServer(), 7, 26
- shiny::reactive(), 7, 27, 28
- shiny::selectInput(), 7
- shiny::sliderInput(), 7
- shinybusy::notify(), 4
- shinyWidgets::numericRangeInput(), 7
- shinyWidgets::pickerInput(), 7
- shinyWidgets::virtualSelectInput(), 27
- show_data, 29

- update-variables, 30
- update_variables_server
 - (update-variables), 30
- update_variables_ui (update-variables), 30

- validation_server (validation_ui), 32
- validation_ui, 32