

# Package ‘RFormatter’

October 12, 2022

**Title** R Source Code Formatter

**Version** 0.1.1

**Description** The R Formatter formats R source code. It is very much based on formatR, but tries to improve it by heuristics. For example, spaces can be forced around the division operator ```/`.

**Depends** R ( $\geq 3.2.2$ )

**License** GPL-3

**LazyData** true

**Imports** formatR ( $\geq 1.2.1$ )

**Suggests** testthat

**URL** <https://github.com/evolutics/RFormatter>

**BugReports** <https://github.com/evolutics/RFormatter/issues>

**RoxygenNote** 5.0.1

**NeedsCompilation** no

**Author** Benjamin Fischer [aut, cre]

**Maintainer** Benjamin Fischer <[benjamin.fischer@evolutics.info](mailto:benjamin.fischer@evolutics.info)>

**Repository** CRAN

**Date/Publication** 2016-05-13 00:44:27

## R topics documented:

format\_R\_source\_code . . . . . 2

**Index** . . . . . 3

---

format\_R\_source\_code *Formats R source code.*

---

### Description

format\_R\_source\_code is very much based on `formatR`, but tries to improve it by heuristics. For example, spaces can be forced around the division operator `/`.

### Usage

```
format_R_source_code(source, formatR_arguments = list(),
  remove_trailing_whitespace = TRUE, spaced_operators = c("/", "%%",
  "%/%", ":", "^"))
```

### Arguments

`source` String with source code to format. This not the filename of the source file.

`formatR_arguments` List of arguments passed to `formatR` via its `tidy_source`.

`remove_trailing_whitespace` Boolean: should horizontal whitespace at the end of lines be removed?

`spaced_operators` Vector of strings with operators around which spaces are forced.

### Value

String with formatted source code.

### See Also

[tidy\\_source](#)

### Examples

```
format_R_source_code("if (b) { f() }")
format_R_source_code("if (b) { f()\n\nf() }")
format_R_source_code("p = 2", list(arrow = TRUE, width.cutoff = 80))
format_R_source_code("(k/n)^x", spaced_operators = c("/"))

## Not run:
format_R_source_code("f()", text = NULL)
format_R_source_code("f()", output = TRUE)

## End(Not run)
```

# Index

`format_R_source_code`, [2](#)

`tidy_source`, [2](#)