

Package ‘rmoriedata’

October 23, 2026

Type Package

Title Integrated Datasets for the 'rmorie' Package

Version 0.4.1

Description Integrated open data fixtures used by the 'rmorie' package for examples, vignettes, and tests. Contains snapshots of publicly available datasets from open-data portals built on the Comprehensive Knowledge Archive Network ('CKAN', <<https://ckan.org/>>), 'Socrata' (<<https://dev.socrata.com/>>), and 'Opendatasoft' (<<https://www.huwise.com/>>) (Chicago, New York City, Toronto, Vancouver, and others), Statistics Canada Canadian Centre for Justice and Community Safety Statistics ('CCJS') tables, a multi-agent-reviewed corpus of Ontario Special Investigations Unit ('SIU', <<https://www.siu.on.ca/>>) director's reports, and synthetic fixtures for unit tests. Also ships a small set of disclosure-control helpers for aggregate releases: differential privacy (an exact discrete Laplace sampler for counts and the analytic Gaussian mechanism for means, drawing on the operating system's random source, with privacy-budget accounting), k-anonymity and l-diversity checks, and cell suppression audited for exact recovery from the margins.

License AGPL (>= 3)

Encoding UTF-8

Language en-GB

Depends R (>= 4.3.0)

Imports stats, utils, rmoriebricklayer (>= 0.5.1)

LinkingTo rmoriebricklayer

Suggests withr, testthat (>= 3.0.0), nanoparquet, tibble, curl, jsonlite, knitr, rmarkdown

VignetteBuilder knitr

LazyData true

LazyDataCompression xz

Config/testthat/edition 3

URL <https://rootcoder007.github.io/rmoriedata/>,
<https://github.com/rootcoder007/rmoriedata>

BugReports <https://github.com/rootcoder007/rmoriedata/issues>

biocViews Software, ExperimentData

Config/roxygen2/version 8.0.0

NeedsCompilation yes

Author Vansh Singh Ruhela [aut, cre] (ORCID:
[<https://orcid.org/0009-0004-1750-3592>](https://orcid.org/0009-0004-1750-3592))

Maintainer Vansh Singh Ruhela <vsruhela@proton.me>

Repository CRAN

Date/Publication 2026-10-23 09:10:09 UTC

Contents

arrest_sample	3
cellsupp	4
chiclr	5
chiload	6
cihiget	8
cihitbls	9
complaint_sample	10
dpbudget	11
dpgmean	12
dplapcnt	13
dplaphist	14
dpspent	15
hostcat	16
kanonvrf	17
ldivvrf	18
mdask	19
mdcat	20
mddict	21
mdllmconf	22
mdload	22
mdpath	23
mdsums	24
mdverify	24
morie_core	25
rmoriedata-victoria	26
siuload	27

Index	30
--------------	-----------

arrest_sample	<i>Chicago arrests sample</i>
---------------	-------------------------------

Description

A CRAN-safe slice of the City of Chicago "Arrests" dataset. For the full ~1.5M-row dataset use `chiload("arrests", full = TRUE)`.

Usage

```
arrest_sample
```

Format

A base `data.frame` with up to 25,000 rows and 8 columns:

case_number Chicago PD records-division number (character).

date_iso Arrest timestamp as an ISO-8601 string with offset.

date Arrest timestamp as POSIXct (America/Chicago).

race Recorded race of the arrestee (character).

charge_type Charge type of the primary charge (F/M/etc.).

charge_class Charge class of the primary charge.

charge_desc Description of the primary charge.

charge_statute Statute of the primary charge.

Source

City of Chicago Open Data Portal, "Arrests" (dataset dpt3-jri9). <https://data.cityofchicago.org/>

See Also

[chiload](#)

Examples

```
data(arrest_sample)
dim(arrest_sample)
str(arrest_sample)

# Recorded race distribution.
sort(table(arrest_sample$race), decreasing = TRUE)

# Charge severity (F = felony, M = misdemeanour, ...).
sort(table(arrest_sample$charge_type), decreasing = TRUE)

# Most frequent primary charges.
```

```
head(sort(table(arrest_sample$charge_desc), decreasing = TRUE), 5)

# Cross-tab race x charge type.
with(arrest_sample, table(race, charge_type))
```

cellsupp	<i>Cell suppression with complementary suppression and a recoverability audit</i>
----------	---

Description

Suppresses (sets to NA) every count below threshold, then, when `retcomp = TRUE`, hides further cells until no suppressed value can be solved exactly from the table's row and column totals, which a published table normally carries.

Usage

```
cellsupp(tbl, threshold = 5, retcomp = TRUE)
```

Arguments

<code>tbl</code>	A numeric matrix or 2-D table of counts. Will be coerced to matrix; row/column names are preserved.
<code>threshold</code>	Minimum count to remain unsuppressed. Default 5.
<code>retcomp</code>	Logical; if TRUE (default), add complementary suppressions until no hidden cell is recoverable from the row and column totals.

Details

Complements are added to a fixed point. A row or column holding exactly one hidden cell gives that cell away by subtraction, so every line with a hidden cell gets a second one; a complement placed for a row is a hidden cell in its column too, so the passes repeat until no line holds a lone hidden cell. That condition is necessary but not sufficient, so the result is then audited exactly: a hidden cell is recoverable when the linear system of row and column totals determines it (its indicator lies in the row space of the constraints over the hidden cells). Any recoverable cell receives another complement in its row, and the audit repeats. Complements are taken from positive cells, preferring one in a line that already holds a hidden cell (which creates no new lone cell), then the largest such cell, which leaves the widest range for the hidden values. A zero cell is never used as a complement: it would bound the hidden values from below at nothing.

The audit covers exact recovery from the margins. It does not compute the feasible interval of each hidden cell, which bounds from non-negativity can narrow; a table whose hidden values must stay inside a wide interval needs an interval audit (linear programming) on top.

Only finite numeric cells are eligible for suppression. NA cells in the input pass through unchanged and are treated as unpublished.

Value

A list with class "cellsupp":

suppressed numeric matrix, suppressed cells set to NA.

primary_mask logical matrix, TRUE for primary suppressions.

complementary_mask logical matrix, TRUE for complementary suppressions (all FALSE when retcomp = FALSE).

recoverable_mask logical matrix, TRUE for a hidden cell whose value the row and column totals determine exactly.

protected logical, TRUE when no hidden cell is recoverable. Test this before publishing.

n_primary integer.

n_complementary integer.

n_recoverable integer.

threshold the threshold used.

Examples

```
tbl <- matrix(c(120, 3, 47, 88, 2, 99, 14, 51, 60),
  nrow = 3,
  dimnames = list(c("A", "B", "C"), c("X", "Y", "Z"))
)

res <- cellsupp(tbl, threshold = 5)
res$suppressed # NA where suppressed
res$protected # no hidden cell can be solved from the totals
res$n_primary # cells below threshold
res$n_complementary # extra cells hidden to protect them

# Without complements the small cells are hidden but recoverable.
bare <- cellsupp(tbl, threshold = 5, retcomp = FALSE)
bare$protected
bare$recoverable_mask

# Works on a 2-D table too; NA cells pass through untouched.
t2 <- as.table(matrix(c(2, 40, 30, 1), 2,
  dimnames = list(c("a", "b"), c("c", "d"))
))
cellsupp(t2, threshold = 5)$suppressed
```

chiclr

Clear the cache of full Chicago datasets

Description

Deletes the Parquet files that chiload(full = TRUE) wrote to the cache directory: tempdir() by default, or the directory named in options(rmoriedata.cache_dir =).

Usage

```
chiclr()
```

Value

The cache directory, invisibly.

Examples

```
chiclr()
```

chiload	<i>Load Chicago crime or arrest data</i>
---------	--

Description

Returns the bundled sample by default, or fetches the full dataset from the City of Chicago SODA API when `full = TRUE`. A complete fetch is cached as Parquet under `tempdir()` for the session; to keep it across sessions name a directory first, for example `options(rmoredata.cache_dir = tools::R_user_dir("rmoredata", "cache"))`, and drop it with `chiclr()`. Nothing is written outside `tempdir()` unless you set that option. The result can be returned as a base data frame, a tibble, or written to a Parquet file whose path is returned – the last being the recommended bridge for Python (`pandas.read_parquet`).

Usage

```
chiload(
  type = c("arrests", "complaints"),
  as = c("data.frame", "tibble", "parquet_path"),
  full = FALSE,
  mirror = getOption("rmoredata.mirror", NULL),
  limit = NULL,
  fraction = NULL,
  refresh = FALSE
)
```

Arguments

<code>type</code>	One of "arrests" or "complaints".
<code>as</code>	Return format: "data.frame" (default), "tibble", or "parquet_path" (writes a Parquet file under <code>tempdir()</code> and returns its path; nothing is written to the user's home).
<code>full</code>	If TRUE, fetch the complete dataset from Socrata (network, large) instead of the bundled sample; a complete fetch is cached as Parquet (see Description).

mirror	Optional base URL of an r-universe/drat mirror to try before Socrata (offline-friendly fallback). Defaults to <code>getOption("rmoriedata.mirror")</code> . The mirror's <code><type>_full.parquet</code> must use snappy or no compression and data pages v1: the package's own reader supports nothing else.
limit	Optional row cap. For a <code>full = TRUE</code> fetch it is passed to the Socrata <code>\$limit</code> parameter (a bounded fetch skips the mirror and is never written to the full-dataset cache); otherwise it keeps the first <code>limit</code> rows of the bundled sample. Default <code>NULL</code> fetches everything.
fraction	Optional share of the dataset, in $(0, 1]$, for a <code>full = TRUE</code> fetch: the live row count is looked up and <code>limit</code> is set to <code>ceiling(total * fraction)</code> (of the bundled sample's rows otherwise). Give either <code>fraction</code> or <code>limit</code> , not both.
refresh	If <code>TRUE</code> , ignore the cache of the complete dataset and fetch it again (the cache is rewritten). A cache file that cannot be read is discarded and refetched regardless.

Details

Parquet I/O uses this package's own native codec (`R/aaa_parquet.R`), so no **arrow** install is required.

Value

A `data.frame/tibble`, or a length-1 character Parquet path when `as = "parquet_path"`.

Examples

```
# `type` selects the dataset; the bundled sample is returned by default.
comp <- chiload("complaints") # reported incidents
arr <- chiload("arrests") # arrests
nrow(comp)
nrow(arr)
head(sort(table(comp$primary_type), decreasing = TRUE), 5)

# `as = "tibble"` returns a tibble when the package is installed.
if (requireNamespace("tibble", quietly = TRUE)) {
  tb <- chiload("complaints", as = "tibble")
  class(tb)
}

# `as = "parquet_path"` writes a Parquet file and returns its path --
# the recommended bridge to Python (pandas.read_parquet). Offline: the
# bundled sample is written, no network.
pq <- chiload("arrests", as = "parquet_path")
file.exists(pq)

# `full = TRUE` fetches from the live Chicago SODA API; `limit` bounds
# the request (seconds, not minutes) and try() keeps the example
# graceful when the service is unreachable. Omit `limit` for the
# complete multi-million-row dataset (cached, see Description); `mirror`
```

```
# tries an offline-friendly Parquet mirror first when set.
# `fraction = 0.001` takes a share of the dataset (0.1% of all rows)
# instead of a row count; the live total is looked up first.
big <- try(chiload("complaints", full = TRUE, limit = 200))
if (!inherits(big, "try-error")) nrow(big)
```

cihiget

Download a CIHI data table (live, with Wayback fallback)

Description

Resolves a CIHI table from the bundled catalogue and downloads it to `dest`, falling back to the Internet Archive snapshot if the live CIHI URL has rotated or been removed. The download + fallback runs through **rmoriebricklayer**'s shared C++/libcurl foundation (`blfetch()`), the same engine **rmorie** and **morie** use – one implementation across the ecosystem.

Usage

```
cihiget(which, dest = NULL, timeout = 120L)
```

Arguments

<code>which</code>	A row index into <code>cihitbls()</code> , or a string matched (case-insensitively, as a substring) against table titles. Must resolve to exactly one table.
<code>dest</code>	Destination file path. Default: a tempfile with the table's own extension.
<code>timeout</code>	Per-request timeout, seconds.

Value

The `dest` path, invisibly. Errors if both the live URL and its Wayback fallback fail.

Examples

```
# Offline: inspect the catalogue to choose a `which` argument.
cat <- cihitbls()
head(cat$title, 3)

# Downloads a table from the live CIHI web service; try() keeps the
# example graceful when the service is unreachable.
# `which` by title substring (case-insensitive; must match exactly one).
f1 <- try(cihiget("Hospital Beds, 2024")) # -> tempfile path

# `which` by row index into cihitbls(); `dest` chooses the
# output path and `timeout` bounds each request (seconds).
f3 <- try(cihiget(1,
  dest = tempfile(fileext = ".xlsx"),
  timeout = 60
```

```

))

# An ambiguous substring errors and lists the candidates:
try(cihiget("data"))

```

cihitbls	<i>Catalogue of CIHI open data-table workbooks (with Wayback fallbacks)</i>
----------	---

Description

Returns the bundled catalogue of the public data-table .xlsx workbooks published on the Canadian Institute for Health Information (CIHI) “Access data and reports > Data tables” page (<https://www.cihi.ca/en/access-data-and-reports/data-tables>). Each row carries the table title, its direct url, and a wayback_url snapshot on the Internet Archive so the table stays retrievable even if CIHI rotates or removes the live file.

Usage

```
cihitbls(archonly = FALSE)
```

Arguments

archonly	If TRUE, drop rows with no Wayback snapshot. Default FALSE (return the full catalogue).
----------	---

Details

Pair with `rmorie::morie_ingest_cihi_xlsx()` to download + parse any row (that helper tries url first and falls back to wayback_url). The Wayback snapshots were resolved with `rmoriebricklayer::wbsnpurl()`.

Value

A data.frame with columns title, url, wayback_url.

Source

Canadian Institute for Health Information, Data tables (<https://www.cihi.ca/en/access-data-and-reports/data-tables>). Snapshotted to the Internet Archive (<https://web.archive.org>). Catalogue current as of 2026-07.

Examples

```
# Full catalogue: title, live url, Wayback snapshot url.
cat <- cihitbls()
nrow(cat)
names(cat)
head(cat$title, 3)

# `archonly = TRUE` keeps only rows that have a Wayback snapshot,
# i.e. tables still retrievable if CIHI rotates the live file.
arch <- cihitbls(archonly = TRUE)
nrow(arch) # <= nrow(cat)
all(nzchar(arch$wayback_url)) # TRUE

# Find a table by keyword before fetching it.
cat$title[grepl("hospital", cat$title, ignore.case = TRUE)][1:3]
```

complaint_sample	<i>Chicago reported-crime sample ("complaints")</i>
------------------	---

Description

A CRAN-safe slice of the City of Chicago "Crimes – 2001 to present" dataset (reported incidents), filtered to geocoded rows from 2020 onward. For the full dataset use `chiload("complaints", full = TRUE)`.

Usage

```
complaint_sample
```

Format

A base data.frame with up to 25,000 rows and 16 columns:

case_number Chicago PD records-division number (character).
date_iso Incident timestamp as an ISO-8601 string with offset (lossless across R/Python).
date Incident timestamp as POSIXct (America/Chicago).
iucr Illinois Uniform Crime Reporting code (character).
primary_type Primary FBI crime classification.
description Secondary description of the offense.
arrest Whether an arrest was made (logical).
domestic Whether domestic-violence related (logical).
beat,district,ward,community_area Geographic area codes (integer).
fbi_code FBI crime code (character).
year Year of the incident (integer).
latitude,longitude WGS84 coordinates (numeric).

Source

City of Chicago Open Data Portal, "Crimes - 2001 to present" (dataset ijzp-q8t2). <https://data.cityofchicago.org/>

See Also

[chiload](#)

Examples

```
data(complaint_sample)
dim(complaint_sample)
str(complaint_sample)

# Most common offense types.
head(sort(table(complaint_sample$primary_type), decreasing = TRUE), 5)

# Arrest rate among reported incidents.
mean(complaint_sample$arrest)

# Incidents per year (the sample spans 2020+).
table(complaint_sample$year)

# Domestic-violence-flagged incidents by type.
head(sort(table(complaint_sample$primary_type[complaint_sample$domestic]),
  decreasing = TRUE
), 3)
```

dpbudget

A privacy budget that DP releases are charged against

Description

Creates a budget of epsilon (and delta) that the mechanisms in this package draw down when passed as `budget =`. Releases compose by basic composition: the epsilons and deltas of the releases charged to one budget add up, and a release that would exceed the budget is refused before any noise is drawn. A hundred releases at `epsilon = 1` spend `epsilon = 100`; a budget makes that visible and enforceable.

Usage

```
dpbudget(epsilon, delta = 0)
```

Arguments

<code>epsilon</code>	Total epsilon available (positive).
<code>delta</code>	Total delta available (0 for pure DP only).

Value

An object of class "dpbudget" (an environment, so charges persist across calls).

See Also

[dpspent\(\)](#)

Examples

```
b <- dpbudget(epsilon = 2)
dplapcnt(42, epsilon = 1, budget = b)
dpspent(b)
# a second release at epsilon = 1.5 would exceed the remaining 1
try(dplapcnt(42, epsilon = 1.5, budget = b))
```

dpgmean

Differentially-private mean via the analytic Gaussian mechanism

Description

Releases an (ϵ, δ) -DP mean of a bounded numeric vector, as a noised sum over a noised count, each with half the budget. Under the add-or-remove-one relation every mechanism here uses, one record moves the clipped sum by at most $\max(\text{abs}(\text{lower}), \text{abs}(\text{upper}))$ and the count by 1, so neither the sum nor $\text{length}(x)$ is treated as public.

Usage

```
dpgmean(x, lower, upper, epsilon, delta = 1e-06, budget = NULL)
```

Arguments

x	Numeric vector (no NAs).
lower, upper	Hard bounds on x. Values outside are clipped (with a warning); the bounds must be chosen without looking at the data.
epsilon, delta	Privacy parameters for the whole release. delta should be well below $1 / \text{length}(x)$.
budget	Optional dpbudget() to charge against.

Details

Each half is calibrated with the analytic Gaussian mechanism (Balle and Wang 2018), which holds for every $\epsilon > 0$; the classical bound $\sigma = \Delta \sqrt{2 \ln(1.25/\delta)} / \epsilon$ holds only for $\epsilon \leq 1$ and is not used. Noise comes from the operating system's CSPRNG; `set.seed()` has no effect.

Value

A noised mean (single numeric).

References

Balle and Wang (2018), Improving the Gaussian Mechanism for Differential Privacy: Analytical Calibration and Optimal Denoising, ICML.

Examples

```
x <- runif(1000, 0, 1)
dpgmean(x, lower = 0, upper = 1, epsilon = 1.0)
mean(x) # the true mean, for comparison

# Wider bounds raise sensitivity, so the same epsilon adds more noise.
dpgmean(x, lower = -5, upper = 5, epsilon = 1.0)
```

dplapcnt

Differentially-private count via the discrete Laplace mechanism

Description

Releases a count with discrete Laplace noise, $P(y) \propto e^{-\epsilon|y|}$, so the release is a whole number. Use it for the number of records matching a predicate (for example incidents in a division-year). Adding or removing one record changes the count by at most 1, and the release is pure ϵ -DP under that add-or-remove-one relation, the one every mechanism in this package uses.

Usage

```
dplapcnt(truecnt, epsilon, budget = NULL)
```

Arguments

truecnt	Non-negative integer; the true count.
epsilon	Privacy loss (smaller means more noise, stronger privacy).
budget	Optional <code>dpbudget()</code> to charge epsilon against.

Details

The noise is drawn from the operating system's CSPRNG with the exact sampler of Canonne, Kamath and Steinke (2020), in integer arithmetic, so no floating-point artefact separates neighbouring datasets and `set.seed()` has no effect. `epsilon` is used as a rational with denominator 2^{20} , rounded down.

Value

The noised count, a whole number (it can be negative; clip with `pmax(0, x)` for display, which is post-processing and costs no privacy).

References

Canonne, Kamath and Steinke (2020), The Discrete Gaussian for Differential Privacy, NeurIPS.
 Mironov (2012), On Significance of the Least Significant Bits for Differential Privacy, CCS.

Examples

```
# A single noised release of a true count of 42 (different every call).
dplapcnt(truecnt = 42, epsilon = 1.0)

# Smaller epsilon = stronger privacy = more noise.
dplapcnt(42, epsilon = 0.1)
dplapcnt(42, epsilon = 5.0)

# The mechanism is unbiased: averaging many releases returns about the truth
# (for illustration; releasing many answers spends many epsilons).
mean(replicate(500, dplapcnt(42, epsilon = 1.0)))
```

dplaphist

Differentially-private histogram via the discrete Laplace mechanism

Description

Adds independent discrete Laplace noise, $P(y) \propto e^{-\epsilon|y|}$, to each bin count. Adding or removing one record changes exactly one bin by 1, so the whole histogram is pure ϵ -DP under the add-or-remove-one relation. Noise and sampler as in [dplapcnt\(\)](#).

Usage

```
dplaphist(counts, epsilon, budget = NULL)
```

Arguments

counts	Vector of non-negative whole-number bin counts.
epsilon	Privacy loss for the whole histogram (positive scalar).
budget	Optional dpbudget() to charge epsilon against.

Value

A numeric vector of whole numbers, the same length as counts (values may be negative; clip for display).

Examples

```

true <- c(120, 45, 8, 230, 17)
dplaphist(true, epsilon = 0.5)

# Post-process for display: clip negatives (costs no privacy).
pmax(0, dplaphist(true, epsilon = 1.0))

# Release a private histogram straight from tabulated data.
counts <- as.integer(table(complaint_sample$year))
dplaphist(counts, epsilon = 1.0)

```

dpspent	<i>What a privacy budget has spent</i>
---------	--

Description

What a privacy budget has spent

Usage

```
dpspent(budget)
```

Arguments

budget A budget from `dpbudget()`.

Value

A list: epsilon, delta (the totals), spent_epsilon, spent_delta, remaining_epsilon, remaining_delta, releases.

Examples

```

b <- dpbudget(1)
invisible(dplaphist(c(10, 20), epsilon = 0.25, budget = b))
dpspent(b)$remaining_epsilon

```

 hostcat

Curated datasets at data.rmorie.com

Description

Beyond the open data this package ships, the MORIE project keeps more than 160 databases materialised from Google BigQuery public datasets (Chicago crime, EPA air quality, US census, FEC, FDA, NOAA, NHTSA, Hacker News, Ethereum, World Bank, ...) and serves their tables from the edge. They open with the MORIE key that `rmorie`, `morie` or `rmoriebricklayer` store (`rmorie::login`, `rmorie::morie_llm_login()`, `rmoriebricklayer::dlogin()`). `hostcat()` returns every table with its key, description, rows and BigQuery source (the manifest is kept for a day); `hostload("db/table")` returns one table, cached under the package cache directory (`tempdir()` unless `options(rmoriedata.cache_dir = )` names a persistent one).

Usage

```
hostcat(refresh = FALSE)

hostlogin(
  token = NULL,
  email = NULL,
  code = NULL,
  openbro = interactive(),
  ...
)

hostload(key, refresh = FALSE)
```

Arguments

<code>refresh</code>	Fetch again even when a day-old copy is cached.
<code>token, email, code, openbro</code>	Passed to <code>rmoriebricklayer::dlogin()</code> : a key you already hold (keys are personal: sign in with GitHub or an emailed code, or ask at www.rmorie.com/access/), or an email address (a one-time code is sent; pass it as <code>code</code> in a non-interactive session). With neither, the GitHub device flow runs. The service address comes from the signed services document (<code>rmoriebricklayer::svcs()</code>).
<code>...</code>	Passed to <code>rmoriebricklayer::dlogin()</code> : the data access terms and who is asking, which a new key needs (<code>accter</code> , <code>name</code> , <code>affiliation</code> , <code>purpose</code> , <code>restricted</code> , <code>supnm</code> , <code>suprole</code> , <code>supemail</code>); what is not given is asked at the console.
<code>key</code>	A db/table key from the catalog.

Value

`hostlogin()`: the key, invisibly, after storing it in the shared credentials file. `hostcat()`: a data frame with key, name, rows and source; `hostload()`: the table as a data frame.

Examples

```
## Not run:
head(hostcat())
df <- hostload("chicago_crime/incidents")

## End(Not run)
```

kanonvrf	<i>k-anonymity verification</i>
----------	---------------------------------

Description

Checks whether a data.frame satisfies k-anonymity over the supplied quasi-identifier columns. A dataset is k-anonymous if every combination of quasi-identifier values appears in at least k rows.

Usage

```
kanonvrf(data, qids, k = 5)
```

Arguments

data	data.frame.
qids	Character vector of column names.
k	Minimum equivalence-class size. Default 5 (a common public-health / open-data threshold).

Details

A missing value (NA) in a quasi-identifier is treated as a value of its own: rows with an unrecorded ward, age band or race form their own classes and are counted, never dropped. Unrecorded values are often the rarest records, which makes them the most re-identifiable, so they must meet the threshold like any other class. Every row is accounted for: the class sizes sum to nrow(data).

Value

A list with class "morie_k_anon" containing:

satisfies	logical, whether the dataset is k-anonymous.
k	the threshold used.
min_class_size	integer, size of the smallest class.
n_classes	integer, total number of equivalence classes.
n_violations	integer, number of classes below the threshold.
violating_classes	data.frame of class keys plus their .n sizes (empty data.frame when none).
summary	human-readable one-line summary.

Examples

```
df <- data.frame(
  age = c(25, 25, 25, 32, 32, 40),
  sex = c("F", "F", "F", "M", "M", "M")
)

# k = 2: the class {age=40, sex=M} has only 1 row -> VIOLATED.
res <- kanonvrf(df, c("age", "sex"), k = 2)
res$summary
res$satisfies
res$violating_classes # the offending quasi-identifier combos

# Loosening to k = 1 always holds; the default k = 5 is stricter.
kanonvrf(df, c("age", "sex"), k = 1)$satisfies
kanonvrf(df, c("age", "sex"))$satisfies # k = 5

# A single quasi-identifier is fine too.
kanonvrf(df, "sex", k = 3)$min_class_size

# On real bundled data: are (year, arrest) cells 5-anonymous?
kanonvrf(complaint_sample,
  c("year", "arrest"),
  k = 5
)$summary
```

ldivvrf

l-diversity verification

Description

Checks whether a data.frame satisfies l-diversity: within each equivalence class defined by the quasi-identifiers, the sensitive attribute must take at least l distinct values.

Usage

```
ldivvrf(data, qids, sensitive, l = 3)
```

Arguments

data	data.frame.
qids	Character vector of QI column names.
sensitive	Name of the sensitive-attribute column.
l	Minimum number of distinct sensitive values per class. Default 3.

Details

Only known (non-NA) sensitive values count towards diversity: a class whose rows read "HIV", NA, NA tells an adversary the attribute is HIV or withheld, which is diversity 1. Classes are formed as in [kanonvrf\(\)](#), with NA in a quasi-identifier as a level of its own.

Value

A list with class "morie_l_div" containing:

satisfies logical.

l the threshold used.

min_diversity integer, lowest per-class distinct count.

n_classes integer.

n_violations integer, classes below the threshold.

violating_classes data.frame of class keys plus their .diversity count.

summary human-readable.

Examples

```
df <- data.frame(
  age = c(25, 25, 25, 25, 32, 32, 32),
  sex = c("F", "F", "F", "F", "M", "M", "M"),
  dx  = c("A", "B", "C", "A", "X", "Y", "Z")
)

# Class {25,F} has 3 distinct dx (A,B,C); {32,M} has 3 (X,Y,Z) -> l=3 holds.
res <- ldivvrf(df, c("age", "sex"), "dx", l = 3)
res$summary
res$satisfies
res$min_diversity

# Demanding l = 4 fails: no class has 4 distinct sensitive values.
bad <- ldivvrf(df, c("age", "sex"), "dx", l = 4)
bad$satisfies
bad$violating_classes

# k-anonymity and l-diversity are complementary: check both.
kanonvrf(df, c("age", "sex"), k = 3)$satisfies
```

mdask

Ask a language model about the bundled datasets

Description

Sends a question through `rmoriebricklayer::llmask()`, to a language model you bring: an OpenAI-compatible endpoint of your own, a provider whose key is set (OpenAI, Anthropic, Google Gemini, OpenRouter, Groq, Mistral and more: `rmoriebricklayer::llmprvd()`), or an Ollama server. Nothing is sent anywhere you did not set up. The model is given every function of `rmoriedata` and `rmoriebricklayer` and tools to read their help, and this package's catalogue of datasets, so it can name the tables and write the code that loads them. `rmoriebricklayer::llmstat()` shows which route would answer; `mdllmconf()` (or `rmb1` config setup from the shell) saves a provider's key, the route and the model.

Usage

```
mdask(question, model = NULL, route = NULL)
```

Arguments

question	Character scalar.
model	Optional model name; the route's model when NULL.
route	NULL or "auto" (the first route that is set up), "own", "ollama" or a provider id such as "anthropic" (that route only).

Value

Character scalar: the answer, or a sentence saying what went wrong or what to set up (never an error, so a script keeps going).

Examples

```
## Not run:
# These need a language model: a provider's key, Ollama, or your own server.
Sys.setenv(ANTHROPIC_API_KEY = "...")
mdask("which bundled datasets cover Toronto police use-of-force?")
mdask("summarise the SIU director's-report corpus", route = "ollama",
      model = "qwen3:8b")

## End(Not run)

# With no route set up the call returns a setup hint, not an error, and
# reaches no network:
if ("llmstat" %in% getNamespaceExports("rmoriebricklayer")) {
  old <- Sys.getenv(c("OLLAMA_HOST", "MORIE_LLM_BASE_URL"), unset = NA)
  Sys.setenv(OLLAMA_HOST = "off", MORIE_LLM_BASE_URL = "off")
  if (!nrow(subset(rmoriebricklayer::llmstat(),
                  status %in% c("key set", "configured")))) {
    cat(mdask("hello"))
  }
  for (v in names(old)) {
    if (is.na(old[[v]])) Sys.unsetenv(v) else do.call(Sys.setenv, as.list(old[v]))
  }
}
```

mdcat

*Catalog of the bundled datasets***Description**

One row per bundled table or dictionary: slug, source_path (relative to the package's extdata directory), kind, and for tables n_rows, n_cols and parquet_path (the same table as a Parquet file, see [mdpath\(\)](#)).

Usage

```
mdcat()
```

Value

A data frame: slug, source_path, kind (table, dictionary, ...), n_rows, n_cols, parquet_path, and synthetic, TRUE for the tables that are generated stand-ins with the published schema rather than published data (the ARSAU use-of-force tables and the *_synthetic ones).

Examples

```
cat <- mdcat()
cat$slug[cat$synthetic]
tbls <- cat[cat$kind == "table", c("slug", "n_rows", "n_cols")]
head(tbls[order(-tbls$n_rows), ])
```

mddict

Data dictionary for a bundled dataset

Description

Data dictionary for a bundled dataset

Usage

```
mddict(slug)
```

Arguments

slug Dictionary slug; rows with kind == "dictionary" in `mdcat()` list them.

Value

The dictionary as JSON text (a length-one character vector), or NULL invisibly with a message when none is bundled.

Examples

```
d <- mddict("arsau_2023_dictionary")
substr(d, 1, 60)
```

mdllmconf

*Show or save the language-model settings***Description**

The route `mdask()` takes and the address, key and model of each route (your own OpenAI-compatible server, each provider such as Anthropic or OpenAI, a local or LAN Ollama server), shared with **rmoriebricklayer**, **rmorie** and the Python package morie. A thin front to `rmoriebricklayer::llmcf()`, which saves them in `~/.config/morie/llm.json` only when you pass a setting; from the shell, `rmbl config` and `rmbl config setup` do the same.

Usage

```
mdllmconf(...)
```

Arguments

```
...           Settings as key = value, e.g. route = "anthropic", anthropic.key = "...",
              anthropic.model = "claude-opus-5-5", ollama.url = "http://192.168.1.20:11434",
              own.url = "http://localhost:1234/v1"; NULL removes one. With no arguments
              nothing is written.
```

Value

A data frame with one row per setting (key, value, source, env, help).

Examples

```
if ("llmcf" %in% getNamespaceExports("rmoriebricklayer")) {
  mdllmconf() # reading writes nothing
}
## Not run:
mdllmconf(route = "anthropic", anthropic.model = "claude-opus-5-5")
mdllmconf(route = NULL) # back to the automatic order

## End(Not run)
```

mdload

*Load a bundled dataset by slug***Description**

Reads the table's CSV and applies the column names and classes from the bundled schema, so the result is the same typed data frame on every platform regardless of how `read.csv()` would have guessed. Every table also ships as a Parquet file holding the same typed frame; `format = "parquet"` reads that copy instead. The first load of a table is cached for the session; later calls return the cached copy unless `refresh = TRUE`.

Usage

```
mdload(slug, refresh = FALSE, format = c("csv", "parquet"))
```

Arguments

slug	Dataset slug; see the slug column of mdcat() .
refresh	Re-read the file even if a cached copy exists.
format	"csv" (default) or "parquet": which shipped copy to read. Both give the same data frame.

Value

A data frame.

Examples

```
d <- mdload("arsau_2023_uof_main_records")
str(d[, 1:4])
```

mdpath	<i>Path of a bundled table's shipped file</i>
--------	---

Description

The absolute path of the CSV or Parquet copy of a table, verified against the signed manifest first. The Parquet path is the bridge to Python: `pandas.read_parquet(path)` gives the same typed table [mdload\(\)](#) returns.

Usage

```
mdpath(slug, format = c("parquet", "csv"))
```

Arguments

slug	Dataset slug; see the slug column of mdcat() .
format	"parquet" (default) or "csv". A dictionary or other non-table slug has one file, which is returned either way.

Value

A length-1 character path.

Examples

```
p <- mdpath("arsau_2023_uof_main_records")
file.exists(p)
basename(mdpath("arsau_2023_uof_main_records", "csv"))
```

mdsums

*SHA256 checksums of bundled rmoriedata files***Description**

Computes the SHA256 digest of every file rmoriedata bundles in inst/extdata, using the shared provenance layer (rmoriebricklayer::sha256file()), and compares each with the digest the signed manifest records for it (in_manifest). For the full check, signature included, use [mdverify\(\)](#); this function is the per-file record an analysis can pin and compare later.

Usage

```
mdsums()
```

Value

A data frame with one row per bundled file and columns path (relative to the extdata root, forward slashes, unique), file (the bare basename), bytes, sha256, and in_manifest (TRUE when the signed manifest lists the file with this digest; NA for the manifest's own files). Use path to locate a file; several basenames recur in more than one directory.

Examples

```
# One row per bundled file: name, size in bytes, SHA256 digest.
ck <- mdsums()
str(ck)
head(ck)

# Total bundled payload and the largest few files.
sum(ck$bytes)
head(ck[order(-ck$bytes), c("file", "bytes")], 3)

# Provenance workflow: pin the digest of a file you depend on, then
# assert it hasn't changed under you in a later session / reinstall.
if (nrow(ck)) {
  pinned <- ck$sha256[1]
  again <- mdsums()
  stopifnot(again$sha256[again$path == ck$path[1]] == pinned)
}
```

mdverify

*Verify the bundled data store against its signed manifest***Description**

Every file rmoriedata ships is listed with its SHA-256 in a manifest, and the manifest is signed with an XMSS (RFC 8391, SHA-256) key whose public half ships with the package. Loading a table checks its file against the manifest; this function checks all of them at once.

Usage

```
mdverify()
```

Details

A file present in the installed store but absent from the manifest is reported too, as a row with `listed = FALSE` and `ok = FALSE`: a file added to the store is as much a change as a file altered in it.

Value

A data frame with one row per manifest entry, then one per unlisted file: `path`, `bytes`, `sha256` (the manifest digest, or the file's own for an unlisted file), `listed`, `ok` (the file on disk is listed and matches). The attribute `"signature"` is `TRUE` when the manifest's signature verified, and the function errors if it did not.

Examples

```
v <- mdverify()
all(v$ok)
attr(v, "signature")
```

morie_core

Shared C-core helpers (rmorie ecosystem backend)

Description

Thin access to the compiled core that ships in **rmoriebricklayer**. `rmoriedata` links that core via `LinkingTo: rmoriebricklayer`, so these functions call the exact same kernels used across the `rmorie` family – no duplicated C code. They back fast data-integrity hashing and summaries for the bundled datasets without requiring **rmorie**.

Usage

```
mdsha(x)
```

```
mdmean(x)
```

Arguments

`x` For `mdsha()`, a length-1 character vector or a raw vector. For `mdmean()`, a numeric vector (coerced with `as.numeric()`); NA/NaN propagate.

Value

`mdsha()` returns a 64-character lowercase hex digest. `mdmean()` returns a length-1 numeric.

Examples

```
## ---- mdsha(): 64-char lowercase hex digest -----
mdsha("abc") # hash a character scalar
mdsha("") # the empty string still hashes
mdsha(charToRaw("abc")) # identical digest from raw bytes

# character input and its raw-byte equivalent agree:
identical(mdsha("abc"), mdsha(charToRaw("abc")))

# Data-integrity pin: verify a value is byte-for-byte what you expect.
expected <- mdsha("record-42")
stopifnot(mdsha("record-42") == expected)

# Fingerprint a whole object by hashing its serialization.
mdsha(serialize(list(a = 1, b = "x"), NULL))

## ---- mdmean(): fast length-1 mean -----
mdmean(1:10) # 5.5
mdmean(c(2, 4, 6)) # 4
mdmean(c(-1, 0, 1)) # 0
mdmean(c(1, 2, NA)) # NA propagates (no na.rm)
mdmean(complaint_sample$year) # mean over a bundled column
```

rmoriedata-victoria *Victorian crime statistics (Crime Statistics Agency Victoria)*

Description

Ten tables from the Crime Statistics Agency's "Latest Victorian crime data" release, bundled in the CSV store and reached by slug through `mdload()`. Each is Table 01 – the headline series – of the corresponding published workbook, for the year ending March 2026.

Details

`vic_criminal_incidents` Criminal incidents by offence division, subdivision and subgroup, with rate per 100,000.

`vic_recorded_offences` Recorded offences on the same offence hierarchy.

`vic_victim_reports` Victim reports by offence.

`vic_alleged_offender_incidents` Alleged offender incidents, including age and sex breakdowns.

`vic_family_incidents` Family incidents by category and outcome.

`vic_lga_criminal_incidents`, `vic_lga_victim_reports`, `vic_lga_family_incidents` The same measures by police region and Local Government Area.

`vic_indigenous_victim_reports`, `vic_indigenous_family_incidents` Aboriginal and/or Torres Strait Islander status breakdowns, as published.

The workbooks are .xlsx. They were read with rmorie's native reader, so the bundled data comes through the same code path a user hits – no **readxl** or **openxlsx** dependency, and no second parser that could disagree with the first. Rebuild with `data-raw/build_vic_tables.R`.

Counts are as published by the CSA and are subject to its own revisions: figures for a given year change between releases as incidents are reclassified, so a table bundled here is a snapshot of the March 2026 release, not a permanent record of that year.

Source

Crime Statistics Agency Victoria, "Latest Victorian crime data". <https://www.crimestatistics.vic.gov.au/crime-statistics/latest-victorian-crime-data> (the page answers only browsers; archived copy of 7 October 2026: <https://web.archive.org/web/20261007154657/https://www.crimestatistics.vic.gov.au/crime-statistics/latest-victorian-crime-data>). Released under CC BY 4.0.

See Also

`mdcat()`, `mdload()`

Examples

```
# Every bundled Victorian table, by slug.
cat <- mdcat()
cat[grepl("^vic_", cat$slug), c("slug", "n_rows", "n_cols")]

# Headline criminal-incident series.
ci <- mdload("vic_criminal_incidents")
str(ci)

# Incidents by offence division for the most recent year.
latest <- ci[ci$Year == max(ci$Year), ]
tapply(latest$`Incidents Recorded`, latest$`Offence Division`, sum)
```

siuload

Load the Ontario SIU director's-report corpus

Description

Returns the bundled Ontario Special Investigations Unit (SIU) director's-report table: one row per report drid, 66 structured columns (police service, incident / notification / decision dates, investigator and witness / subject-official counts, affected-person demographics, injuries, legislation, charges verdict, director's decision, and news-release linkage), plus a `panel_reviewed` flag.

Usage

```
siuload(
  lang = c("all", "en", "fr"),
  as = c("data.frame", "tibble"),
  format = c("csv", "parquet")
)
```

Arguments

<code>lang</code>	One of "all" (default), "en", or "fr": filter to the English-only, French-only, or all rows.
<code>as</code>	Return format: "data.frame" (default) or "tibble".
<code>format</code>	"csv" (the gzip CSV, default) or "parquet" (the same rows and columns, read from the typed store's Parquet copy and returned as text).

Details

For the English reports marked `panel_reviewed == "TRUE"`, the 16 key columns were verified by a multi-agent LLM review panel against the full report text and the parser's guess resolved to the correct value; the subject-official count is filled for every one of them (witness-officer-only investigations are a genuine 0). A French report carries its English report's reviewed case facts (the dates, the team, the counts, the affected person's age and sex, the charges and the director's view) and `panel_reviewed == "FALSE"`; its text fields stay French, and its `police_service` is its English report's service under the name the SIU's French pages use.

`charges_recommended` is "FALSE", "TRUE" or empty here (every column is text); in the typed table, `mdload("siu_directors_reports")`, it is logical (FALSE, TRUE, or NA when the report does not say). `corrigenda` holds the SIU's correction notice of a report (a corrigendum is applied to the report it corrects, not counted as a report). `narrative_summary` is the opening of the report's own account of the incident (about 900 characters, at most 1,500, cut at a sentence end): its "Incident Narrative" / "Description de l'incident" section, or, in reports without one (2005-2016 and re-opened files), the "Notification of the SIU" / "Avis a l'UES" section, which holds the account there. It is empty on the 8 reports whose page has neither. `supplemental_materials` lists the legislation and case-law links a report cites.

`police_service` is the service of the subject officials – not the force that notified the SIU, which is often a custody, requesting or neighbouring service. Each correction to it is listed with the reason read from the report in `data-raw/siu_police_service_review.csv` of the source repository.

One row is one published report, keyed by `drid` and `_language`. A case number can appear on more than one row: the SIU publishes a further report when a case is reconsidered or reported again, each with its own `drid`. Some schema columns (for example the raw times of injury and notification, evidence types, and weapons used) are not stated in the published reports and are empty throughout; they are kept so the table's shape matches the parser's schema.

This is the machine-readable companion to the SIU parser and data-mining subsystem in **rmorie** / **morie** – the first open-source pipeline for the SIU director's-report corpus, created by Vansh Singh Ruhela as part of the MORIE / MRM framework. The table is regenerated from the parser over the full public corpus; see `rmorie::morie_fetch_siu()` to rebuild it live.

This loader returns the corpus as text: every column is character and an empty cell is "", which is the form the SIU parser writes and **rmorie** reads back. The same table is also in the typed data store: `mdload("siu_directors_reports")` applies the bundled schema (integer `drid` and counts, NA for empty cells), so counts of missing values differ between the two entry points by construction; pick the typed store for analysis and this loader for the parser round trip.

Value

A `data.frame` (or `tibble`) of SIU director's-report rows.

Source

Ontario Special Investigations Unit director's reports, https://www.siu.on.ca/en/directors_reports.php (post-2018) and the Ontario Government archive (pre-2018). Parsed with the **rmorie** SIU subsystem.

Examples

```
# Default: every parsed report, as a base data.frame.
all <- siuload()
nrow(all)
ncol(all)

# `lang` filters the corpus by report language.
en <- siuload(lang = "en") # English director's reports
fr <- siuload(lang = "fr") # French director's reports
nrow(en)
nrow(fr)

# `as = "tibble"` returns a tibble when the tibble package is present.
if (requireNamespace("tibble", quietly = TRUE)) {
  tb <- siuload(lang = "en", as = "tibble")
  class(tb)
}

# The five police services with the most reports.
if (nrow(en)) {
  top <- sort(table(en$police_service), decreasing = TRUE)
  head(top, 5)
}
```

Index

* **datasets**
 arrest_sample, 3
 complaint_sample, 10
 rmoriedata-victoria, 26

arrest_sample, 3
as.numeric(), 25

cellsupp, 4
chiclr, 5, 6
chiload, 3, 6, 11
cihiget, 8
cihitbls, 9
complaint_sample, 10

dpbudget, 11
dpbudget(), 12–15
dpgmean, 12
dplapcnt, 13
dplapcnt(), 14
dplaphist, 14
dpspent, 15
dpspent(), 12

hostcat, 16
hostload(hostcat), 16
hostlogin(hostcat), 16

kanonvrf, 17
kanonvrf(), 18

ldivvrf, 18

mdask, 19, 22
mdcat, 20
mdcat(), 21, 23, 27
mddict, 21
mdllmconf, 19, 22
mdload, 22
mdload(), 23, 26, 27
mdmean(morie_core), 25
mdpath, 23
mdpath(), 20
mdsha(morie_core), 25
mdsums, 24
mdverify, 24
mdverify(), 24
morie_core, 25
rmoriedata-victoria, 26
siuload, 27